



Keep your heavy-duty equipment operating with Deka Commercial Batteries.

- Special computer-aided design and manufacturing means **more durability** for heavy-duty line-haul trucks, buses, farm tractors and off-road equipment.
- Most of our commercial batteries contain premium "deep pocket" **envelope separators**, which protect the plates on all four sides to dramatically reduce shorting and **extend service life**.
- **Genuine calcium lead** alloy provides **longer waterless operation** and extended battery life.
- **Anchor-locked elements** with full-frame grids and tight-packed commercial plates resist the damaging effects of vibration, delivering **more power-per-pound** than other batteries.
- Deka Commercial Batteries are available wet and many can be ordered bone-dry. Our special **dry-charge process** completely eliminates moisture for virtually unlimited shelf life when compared to inferior "moist-dry" types.
- Most popular sizes feature **tough polypropylene cases** which resist breakage and extend service life. Many are also available with handles and special terminals for easy installation.
- Deka offers the **most complete line** of enveloped calcium maintenance-free commercial batteries in the industry. Our line includes such **hard-to-find** group sizes as 3D.
- More than **250 quality control checks** ensure the highest quality.



QUALITY SYSTEM
CERTIFIED
ISO 9001
ISO/TS 16949
ENVIRONMENTAL
SYSTEM CERTIFIED
ISO 14001

"POWERED FOR PERFORMANCE"®
EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4781
Order Department Hotline: 610-682-4231
www.dekabatteries.com

DISTRIBUTED BY:

COMMERCIAL BATTERIES



COMMERCIAL BATTERIES

GROUP NO.	PART NO.	PERFORMANCE LEVEL			WEIGHT (Lbs.) WET	MAXIMUM OVERALL DIMENSIONS						FOOTNOTES
		CCA @ 0°F	RES. CAP.	REF. CA. @ 32°F		LENGTH		WIDTH		HEIGHT		
						in	mm.	in	mm.	in	mm.	
8-VOLT COMMERCIAL SERVICE												
1	801	520	102	650	31.5	8%	225	6%	171	8%	225	12,25
6-VOLT HEAVY-DUTY COMMERCIAL SERVICE												
1	901MF	640	130	800	30	9	229	6%	175	8%	222	21,25
2	902	780	200	940	36.5	10%	264	6%	175	8%	222	12,25
3EH	93EH	875	250	1035	47.5	19%	489	4%	108	10	254	12,25
4	904MF	975	250	1170	47	12%	318	6%	175	9%	241	21,25
5D	905D	880	250	1100	50	13%	340	7%	181	9%	235	12,25
12-VOLT HEAVY-DUTY COMMERCIAL SERVICE												
3ET	93ET	500	120	625	48	19%	489	4%	108	9%	251	12,25
4D	904D	1050	290	1280	99.5	20%	527	8%	216	10%	258	12,17,25
4DLT	94DLT	850	240	1005	80	20	508	8%	206	8%	206	12,19,25
8D	908DFT	1400	430	1700	127	20%	527	11	279	10	254	12,17,21,22,25
	908D	1400	430	1700	130							12,17,25
	708D	1100	325	1340	117.5							12,17,25
17TF	917TF	530	140	630	58.5	17	432	6%	175	8	203	11,15,19,25
28	928MF	550	100	685	41.5	10%	260	6%	171	9%	241	21,22,X
30H	930H	650	150	800	51	13	330	6%	171	9%	241	19,21,22
31	1231MF	1000	185	1190	58	13	330	6%	171	9%	241	17,19,21,22,X
	1131MF	950	175	1140	56.5							17,19,21,22,X
	1031MF	760	170	910	54.5							19,21,22,X
	931MF	650	150	810	51							19,21,22,X
31P	1231PMF	1000	185	1190	58	13	330	6%	171	9%	241	17,19,21,22
	1131PMF	950	175	1140	56.5							17,19,21,22
	1031PMF	760	170	910	54.5							19,21,22
	931PMF	650	150	810	51							19,21,22
12-VOLT HEAVY-DUTY COMMERCIAL SEVERE SERVICE / DUAL PURPOSE												
31	7T31	730	190	940	62.5	13	330	6%	171	9%	241	19,21,22,43,X
31P	7T31P	730	190	940	62.5							19,21,22,43,X
31	DP31CS	700	185	875	57							19,21,22,43,X
12-VOLT HEAVY-DUTY COMMERCIAL DRY CHARGED BATTERIES												
4D	904DY	1050	290	1280	58	20%	527	8%	216	10%	258	12,17,25
8D	908DY	1400	430	1700	80	20%	527	11	279	10	254	12,17,25
31	1231MFD	1000	185	1190	43	13	330	6%	171	9%	241	19,21,22,X

Ratings conform to B.C.I. specifications.

Dry = up to 10% reduced capacity.


All batteries are maintenance-free, calcium grids except where noted.

All batteries manufactured in black polypropylene cases and covers except where noted.

FOOTNOTES:

- S - SAE "automotive type" post
- X - 3/8" x 16 stainless steel stud posts
- 11 - Low maintenance - Low antimony grids
- 12 - Hybrid construction
- 15 - Hard rubber, one-piece cover construction
- 17 - Includes handle
- 19 - Includes lifting ledges

- 21 - Anchor lock elements
- 22 - Flush manifold vented cover
- 25 - With individual vent caps
- 43 - Warranty is 12 months in deep cycle service



MEMBER:

