SPICER®
DRIVETRAIN COMPONENTS
DANA

DRIVELINE COMPONENTS CATALOG
END YOKES

J300P-4
SEPTEMBER 2008

Supersedes
Section 4, Dated
February 2005

Changes from original:
10/16/08 Page 33 - 6-4-4151 & 6-4-4151-1 - counterbore depth = .250
12/1/08 Page 39 - added missing subhead for 2.500-10 Spline
Page 60-61 - Corrected alignment of columns

DANA SPICER® Drivetrain Products

INCLUDED IN THIS CATALOG

This publication represents the most comprehensive listing of Spicer® splined hole end yokes ever published by Dana. We have included all the part numbers currently being produced. We have also included and noted parts that are now discontinued, parts that will be available until current stock is exhausted, as well as parts that have been superceded. Most current stock will be in inventory at our distribution centers, and any numbers not inventoried can be supplied upon request.

- Spicer Life® Series yokes begin on page 2.
- Listings for round, hex, square, tapered hole and steering shaft yokes are listed in this catalog beginning on page 54.
- A chart showing the configuration and dimensions of all slingers used on end yoke Assemblies begins on page 63.
- Listings have been expanded to assist in the identification of parts, and to help find the correct part or an alternate part for the application.
- All styles of end yokes (bearing plate (BP), bearing strap (BS), cap and bolt (CB), constant velocity (CV), half round (HR), snap ring (SR), inside snap ring (ISR), u-bolt (UB), and winged bearing (WB)) are listed under their corresponding series/spline header, allowing easy substitution of one type for another.
- All of the listings are sorted so that all the individual styles of end yokes, along with the many different seal (hub) diameters and lengths are readily accessible. With this sorting method, alternate style substitutions (u-bolt for bearing strap) or acceptable hub diameter substitutions can be made by looking on only one page of the catalog.
- All footnotes except those regarding part status are listed immediately under the yoke dimensional data, alleviating the need to look at the bottom of the page.

IMPORTANT NOTICE: The data listed herein is correct to the best of our knowledge and belief; having been compiled from reliable and official sources of information. However, WE CANNOT ASSUME ANY RESPONSIBILITY for possible error.

©2008 Dana Limited Printed in USA

HOW TO USE THIS CATALOG

To identify any end yoke, there are two pieces of required information:

1. Series (Measurements to determine series can be found in each series header.)
2. Center Hole Type and Size

Center hole type is described at the top center of each page, and series designations are listed in ascending order by center hole type. After determining series and center hole size, and turning to the appropriate page, all sizes of center holes will be listed under the series designation, along with the different types of end yokes (snap ring (SR), u-bolt (UB), bearing strap (BS), etc.).

Example: To find a 1310 Series Yoke with a 1.146-26 Involute splined hole (see sample page below)

1. Find the 1310 Series heading
2. Find the 1.0700-16 Involute Spline sub-heading
3. Find a 1.5520 Ground Hub Diameter dimension
4. Find a 1.5000 Length Through Hole dimension
5. Find a 3.0000 Centerline to End dimension
6. Find a Bearing Strap Style — BS
7. Locate the part number. Assemblies include slingers, order when available.

(1) Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger) Order When Listed	Slinger Part Number	Spicer Part Number
1310 SERIES (Continued) SR: E-3.469 OTHERS E-3.219, D-1.062 USE KIT 5-153X,5-785X,5-810X								
USES U-BOLT ASSY. 2-94-28X, STRAP ASSY. 2-70-18X								
1.1460-26 Involute Spline								
(2) 1.1460	1.5130	2.0000	3.3000	—	SR	2-4-8171X	232184	2-4-8161 *Coupling shaft yoke*
1.1460	1.5520	1.5000	3.0000	—	UB	2-4-8091X	41498	2-4-8081
1.1460	1.5520	1.5000	3.0000	—	BS	2-4-8091-1X	41498	2-4-8081-1
1.1460	(3) 1.8440	(4) 1.3700	(5) 3.1300	.1200	(6) BS	(7) 2-4-8551-1X	232816	2-4-8521-1

Note the following information from the sample above:

2-4-8091-1X (BS style) could easily be substituted for 2-4-8091X (UB style) by using bearing strap assembly 2-70-18X.

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



BS/CV/HR/UB Style

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
SPL55 SERIES		**E-4.188, D-1.375**				**USE KIT SPL55-1X, SPL55-2X, 5-803X, 5-804X**		
USE STRAP ASSY 3-70-38X								
1.567-36 Involute Spline								
1.567	2.618	1.980	4.025	—	BS			55-4-11-1 *Coupling shaft yoke*
1.790-34 Involute Spline								
1.790	2.375	2.188	4.219	—	BS	55-4-41-1X	233034	55-4-31-1 ⅄
1.790	2.564	2.760	4.870	—	BS	55-4-131-1X•	231059	55-4-121-1 ⅄ *For 9" x 3" Brake*
1.790	2.564	2.760	4.870	—	BS	5001480	231059	55-4-201-1 ⅄
1.790	2.564	2.760	4.870	—	BS	55-4-101-1X•	231059	55-4-91-1 ⅄ *For 9" x 3" Brake*
2.024-39 Involute Spline								
2.024	3.000	2.281	4.330	.250	BS	55-4-81-1X•	232511	55-4-71-1 ⅄
SPL70 SERIES		**E-4.964, D-1.375**				**USE KIT SPL70X, SPL70-1X, 5-808X, 5-809X**		
USE STRAP ASSY. 3-70-38X								
1.543-24 Involute Spline								
1.543	2.241	1.844	5.750	—	BS	70-4-271-1X•	— *Flanged yoke w/eight, 7-73-620 bolts*	70-4-261-1 ⅄
1.750-10 Spline								
1.750	2.500	2.000	5.750	—	BS	70-4-171-1X•	— *Flanged yoke w/eight, 7-73-620 bolts*	70-4-161-1 ⅄
1.783-34 Involute Spline								
1.783	2.940	2.236	4.244	—	BS			70-4-11-1 *Coupling shaft yoke*
1.790-34 Involute Spline								
1.790	2.375	2.188	4.000	—	BS	70-4-61-1X	233034	70-4-51-1 ⅄
1.790	2.562	2.750	6.650	—	BS	5001789	231059 *Flanged yoke w/four holes in flange*	5001781•
1.790	2.564	2.750	5.530	—	BS	70-4-191-1X•	231059 *Flanged yoke w/eight, 7-73-620 bolts;*	70-4-181-1 ⅄
2.024-39 Involute Spline								
2.024	3.000	1.844	3.878	.250	BS	5006977	5006975	5001782 ⅄
2.024	3.000	1.847	3.893	.250	BS	5003330	5006975	5003329 ⅄
2.024	3.000	2.281	4.281	.250	BS	70-4-111-1X	232511	70-4-101-1 ⅄
2.143-41 Involute Spline								
2.143	2.938	2.500	4.555	—	BS	70-4-151-1X	232604	70-4-141-1 ⅄

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



BS/CV/HR/UB Style

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
SPL90 SERIES		**E-4.957, D-1.625**						**USE KIT SPL100-1X**
USE STRAP ASSY. 90-70-28X								
1.750-10 Spline								
1.750	2.500	1.938	4.125	—	BS			90-4-371-1
1.774-34 Involute Spline								
1.774	2.500	2.250	4.110	—	BS	90-4-761-1X	231206	90-4-751-1•
1.790-34 Involute Spline								
1.790	2.375	2.188	5.625	—	BS	90-4-551-1X	232198	90-4-541-1•
1.790	2.500	2.250	4.062	—	BS			90-4-11-1 *Coupling shaft yoke*
1.790	2.562	2.750	5.609	—	BS	90-4-191-1X	231059	90-4-181-1•
1.790	2.562	2.750	5.625	—	BS	90-4-501-1X	231059	90-4-461-1 ⅄
1.962-10 Spline								
1.962	2.625	2.250	5.094	—	BS	90-4-211-1X•	230909	90-4-201-1 ⅄
1.962	2.750	2.781	4.984	—	BS			90-4-381-1
1.998-38 Involute Spline								
1.998	2.750	2.125	4.000	—	BS			90-4-71-1
1.998	2.750	2.125	4.250	—	BS			90-4-391-1
1.998	2.750	2.125	7.562	—	BS			90-4-111-1 *Flanged end yoke.*
1.998	3.000	2.125	4.250	—	BS	90-4-571-1X	232200	90-4-561-1•
2.000-10 Spline								
2.000	2.750	3.000	4.969	—	BS			90-4-21-1
2.024-39 Spline								
2.024	3.000	2.312	4.625	—	BS	90-4-321-1X	231359	90-4-311-1
2.024-39 Involute Spline								
2.024	2.626	2.245	4.160	—	BS	90-4-631-1X	232039	90-4-621-1 ⅄
2.024	3.000	2.281	4.750	.250	BS	90-4-251-1X	232511	90-4-241-1
2.114-32 Involute Spline								
2.114	3.000	2.250	4.375	.424	BS	90-4-591-1X	232200	90-4-581-1•
2.141-41 Involute Spline								
2.141	2.938	2.500	4.562	—	BS	90-4-691-1X	232604	90-4-471-1 ⅄
						90-4-691-1X was replaced by 100-4-1061-1X		
2.178-41 Involute Spline								
2.178	3.543	1.882	4.570	—	BS	5001046	5001045	5001036 ⅄
2.178-43 Involute Spline								
2.178	3.547	2.031	4.625	.157	BS			90-4-791-1
2.250-10 Spline								
2.250	3.750	3.000	5.219	—	BS	90-4-171-1X•	231616	90-4-161-1•
2.281-44 Involute Spline								
2.281	2.938	2.344	4.469	—	BS	100-4-1381-1X	232604	90-4-281-1•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



BS/CV/HR/UB Style

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
SPL90 SERIES (Continued) E-4.957, D-1.625								**USE KIT SPL100-1X**
USE STRAP ASSY. 90-70-28X								
2.364-36 Involute Spline								
2.364	3.000	2.688	4.812	—	BS	90-4-611-1X	232200	90-4-601-1•
2.374-46 Involute Spline								
2.374	3.250	2.875	5.188	—	BS	90-4-361-1X•	231615	90-4-351-1•
2.390-46 Involute Spline								
2.390	3.250	2.312	4.641	—	BS	90-4-341-1X	231803	90-4-331-1•
2.390-47 Involute Spline								
2.390	3.344	1.781	4.250	—	BS	90-4-531-1X	232195	90-4-521-1⅄
SPL100 SERIES E-4.958 D-1.626								**USE KIT SPL100-1X**
USE BEARING RETAINER NO. 90-70-28X								
1.771-34 Involute Spline								
1.771	2.750	2.230	4.060	—	BS			100-4-931-1 *Coupling shaft yoke*
1.790-34 Involute Spline								
1.790	2.562	2.750	5.700	—	BS	100-4-901-1X	231059	100-4-891-1⅄ *Flanged end yoke.*
1.790	2.562	2.755	5.630	—	BS	100-4-1021-1X	231059	100-4-1011-1⅄
2.024-39 Involute Spline								
2.024	2.625	2.245	4.160	—	BS	100-4-1081-1X	232167	100-4-1071-1⅄
2.024	2.625	2.245	7.295	—	BS	100-4-1331-1X	232039	100-4-1321-1⅄ *Flanged yoke w/8 tapped holes in flange*
2.024	3.000	1.817	4.150	.250	BS	5006608	5006975	5006607⅄
2.024	3.000	2.269	7.295	—	BS	100-4-1371-1X	232511	100-4-1361-1⅄ *Flanged end yoke*
2.024	3.000	2.284	4.750	—	BS	100-4-961-1X•	232511	100-4-951-1⅄
2.143-41 Involute Spline								
2.143	3.000	2.166	4.310	.310	BS	5002875	5002871	5002874⅄
2.173-26 Involute Spline								
2.173	3.069	1.812	4.330	.197	BS	5003087	5003086	5001694⅄
2.195-34 Involute Spline								
2.950	3.543	1.889	3.823	—	BS			5007598⅄ *OEM only*
SPL140 SERIES E-5.457 IN. D-1.938 IN.								**USE KIT SPL140X**
USE BEARING RETAINER NO. 140-70-18X								
1.774-34 Spline								
1.774	2.500	2.500	4.950	—	HR	140-4-261-1X	231101	140-4-251-1⅄
1.962-10 Spline								
1.962	2.750	2.805	5.810	—	HR			140-4-181-1•
1.998-38 Involute Spline								
1.998	2.750	2.125	4.730	—	HR			140-4-891-1
1.998	2.750	2.125	4.830	—	HR			140-4-111-1

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
SPL140 SERIES (Continued) E-5.457 IN. D-1.938 IN.								**USE KIT SPL140X**
USE BEARING RETAINER NO. 140-70-18X								
1.998-38 Involute Spline (Continued)								
1.998	2.750	2.125	4.830	—	HR			140-4-1131-1•
1.998	2.750	2.125	7.728	—	HR			140-4-1021-1• *Flanged end yoke.*
1.998	2.810	2.745	5.370	—	HR			140-4-11-1 *Coupling shaft yoke*
1.998	3.000	2.125	4.680	—	HR	140-4-911-1X•	232200	140-4-901-1 ⅄
2.024-39 Spline								
2.024	2.750	2.435	5.250	.090	HR	140-4-1431-1X•	231599	140-4-1421-1•
2.024	3.000	2.312	5.680	.090	HR	140-4-231-1X	231359	140-4-211-1 ⅄
2.024	3.000	2.312	5.680	.090	HR	140-4-241-1X	232182	140-4-211-1 ⅄
2.024-39 Involute Spline								
2.024	3.000	2.284	4.940	—	HR	140-4-1161-1X•	232511	140-4-1151-1 ⅄
2.024	3.000	2.284	4.940	.250	HR	140-4-371-1X	232511	140-4-361-1•
2.024	3.000	2.284	7.587	.250	HR	140-4-1401-1X	232511	140-4-1391-1 ⅄ *Metric flanged yoke*
2.114-32 Involute Spline								
2.114	3.000	2.250	4.810	.424	HR	140-4-931-1X•	232200	140-4-921-1 ⅄
2.143-41 Involute Spline								
2.143	2.938	2.500	5.560	—	HR	140-4-431-1X	232604	140-4-421-1 ⅄
2.178-43 Involute Spline								
2.178	3.539	2.050	5.100	.157	HR			140-4-761-1•
2.178	3.541	2.047	5.100	.160	HR			140-4-1231-1•
2.195-34 Involute Spline								
2.195	3.543	1.889	4.421	—	HR			5007599 ⅄ *OEM only*
2.195	3.543	1.889	4.646	—	HR			5007600 ⅄ *OEM only*
2.250-10 Spline								
2.250	3.500	3.000	6.000	—	HR	140-4-1101-1X•	231616	140-4-1091-1 ⅄
2.274-44 Spline								
2.274	3.000	2.500	2.160	.236	HR	140-4-331-1X	232511	140-4-321-1 ⅄ *Metric flanged yoke*
2.274-44 Involute Spline								
2.274	2.938	2.344	5.190	—	HR	140-4-1201-1X•	232604	140-4-1191-1 ⅄
2.274	2.938	2.350	5.190	—	HR	140-4-451-1X	232604	140-4-441-1 ⅄
2.274	3.000	2.500	5.160	.236	HR	140-4-1271-1X•	232511	140-4-1261-1 ⅄
2.374-46 Spline								
2.374	3.250	2.875	6.210	.140	HR	140-4-291-1X	231615	140-4-271-1 ⅄
2.390-46 Involute Spline								
2.390	2.375	3.195	6.440	.580	HR	140-4-391-1X	232610	140-4-381-1 ⅄
2.390	3.250	2.323	5.660	.140	HR	5003557	5003552	140-4-301-1 ⅄
2.390	3.250	2.323	5.660	.140	HR	140-4-311-1X	231803	140-4-301-1 ⅄
2.390	3.312	2.750	5.374	.157	HR			140-4-1011-1
2.390	3.500	3.375	5.920	—	HR			140-4-751-1
2.500-10 Spline								
2.500	3.750	3.000	5.960	—	HR	140-4-1121-1X	231616	140-4-1111-1 ⅄
2.500	3.750	3.000	5.960	—	HR	140-4-51-1X	231616	140-4-41-1•
2.544-49 Involute Spline								
2.544	3.750	3.000	5.570	—	HR	140-4-151-1X•	231616	140-4-141-1 ⅄
2.544	4.000	2.750	6.060	.180	HR			140-4-881-1
2.750-10 Spline								
2.750	3.750	3.000	6.570	—	HR	140-4-71-1X	230902	140-4-61-1 ⅄

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



BS/CV/HR/UB Style

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
SPL140 SERIES (Continued)			**E-5.457 IN.**	**D-1.938 IN.**				**USE KIT SPL140X**
USE BEARING RETAINER NO. 140-70-18X								
2.750-10 Spline (Continued)								
2.750	3.750	3.000	6.570	—	HR	140-4-91-1X	231616	140-4-81-1⅄
2.794-54 Involute Spline								
2.794	—	2.745	6.320	—	HR			140-4-201-1
2.795-55 Involute Spline								
2.795	4.725	2.047	4.980	.150	HR			140-4-771-1
SPL170 SERIES			**E-6.456 IN.**	**D-2.166 IN.**				**USE KIT SPL170-3X**
USE BEARING RETAINER KIT NO. 170-70-18X								
1.774-34 Spline								
1.774	2.500	2.250	6.440	.090	HR	5009705	231101	170-4-631-1• *High angle yoke*
1.790-34 Involute Spline								
1.790	2.500	2.250	5.030	.090	HR			170-4-921-1
1.790	2.625	2.438	5.600	.250	HR	170-4-121-1X	232166	170-4-111-1•
1.790	2.625	2.438	6.250	.250	HR	170-4-141-1X	232166	170-4-131-1⅄ *High angle yoke*
1.989-30 Involute Spline								
1.989	3.000	2.685	6.580	.220	HR			170-4-771-1 *High angle yoke*
1.998-38 Involute Spline								
1.998	2.750	2.125	4.844	—	HR			170-4-541-1
2.024-39 Spline								
2.024	2.750	2.000	5.370	.120	HR	170-4-1261-1X	232042-2	170-4-1251-1 *High angle yoke*
2.024	3.000	2.312	5.090	.105	HR	170-4-651-1X	231359	170-4-641-1
2.024	3.000	2.312	5.090	.105	HR	170-4-701-1X•	232182	170-4-641-1
2.024	3.000	2.312	5.090	.105	HR	170-4-681-1X•	231102	170-4-641-1
2.024	3.000	2.312	6.391	.105	HR	170-4-691-1X	232182	170-4-661-1• *High angle yoke*
2.024	3.000	2.312	6.391	.105	HR	170-4-671-1X	231359	170-4-661-1• *High angle yoke*
2.024-39 Involute Spline								
2.024	2.625	2.250	4.938	.250	HR	170-4-161-1X■	232167	170-4-151-1⅄
2.024	2.625	2.250	6.016	.250	HR	170-4-181-1X■	232167	170-4-171-1⅄ *High angle yoke*
2.024	2.625	2.500	5.266	.250	HR	170-4-221-1X	232514	170-4-211-1•
2.024	2.625	2.500	5.750	.250	HR	5008578	232514	5001768•
2.024	2.625	2.500	6.500	.250	HR	170-4-1651-1X•	232514	170-4-1641-1⅄
2.024	2.625	2.500	6.500	.250	HR	170-4-241-1X	232514	170-4-231-1• *High angle yoke*
2.024	3.000	2.250	5.031	.280	HR	170-4-861-1X	232200	170-4-841-1
2.024	3.000	2.250	5.031	.280	HR	170-4-851-1X	232199	170-4-841-1

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
SPL170 SERIES (Continued)					**E-6.456 IN. D-2.166 IN.**			**USE KIT SPL170-3X**
USE BEARING RETAINER KIT NO. 170-70-18X								
2.024-39 Involute Spline (Continued)								
2.024	3.000	2.250	6.250	.306	HR	170-4-811-1X	232200	170-4-801-1■ *High angle yoke*
2.024	3.000	2.281	5.156	.250	HR	170-4-261-1X	232511	170-4-251-1•
2.024	3.000	2.281	5.540	.250	HR	5008577	232511	5001766•
2.024	3.000	2.281	6.240	.250	HR	170-4-1631-1X•	232511	170-4-1621-1 ⅄
2.024	3.000	2.281	6.240	.250	HR	170-4-281-1X	232511	170-4-271-1 ⅄ *High angle yoke*
2.024	3.000	2.500	5.280	.280	HR			170-4-821-1
2.024	3.000	2.500	6.500	.280	HR			170-4-831-1 *High angle yoke*
2.114-32 Involute Spline								
2.114	3.000	2.250	5.000	.424	HR	170-4-901-1X	232200	170-4-891-1 ⅄
2.114	3.000	2.250	6.312	.424	HR	170-4-961-1X	232200	170-4-951-1• *High angle yoke*
2.143-41 Involute Spline								
2.143	2.938	2.500	5.320	—	HR	170-4-361-1X	232604	170-4-351-1 ⅄
2.143	2.938	2.500	6.680	—	HR	170-4-381-1X	232604	170-4-371-1 ⅄ *High angle yoke*
2.143	2.938	3.000	5.800	.380	HR	170-4-341-1X	232609	170-4-331-1•
2.143	2.938	3.000	7.190	.380	HR	5008448	232168	170-4-1901-1 ⅄ *131451K = 5008448 yoke assy & nut# 128049; Spicer axles only*
2.143	2.938	3.000	7.190	.380	HR	170-4-321-1X	232609	170-4-311-1 ⅄ *High angle yoke*
2.178-43 Involute Spline								
2.178	3.540	2.050	5.340	.157	HR			170-4-1081-1
2.225-6 Spline								
2.225	3.000	3.250	6.030	—	HR			170-4-1441-1
2.250-10 Spline								
2.250	3.500	3.000	5.750	—	HR	170-4-461-1X•	231616	170-4-451-1
2.274-44 Involute Spline								
2.274	2.938	2.350	5.094	—	HR	170-4-31-1X	232604	170-4-21-1 ⅄
2.274	2.938	2.500	5.281	—	HR	170-4-101-1X•	232168	170-4-91-1 ⅄
2.274	3.000	2.500	5.270	.236	HR	170-4-201-1X	232511	170-4-191-1•
2.364-18 Involute Spline								
2.364	3.500	3.375	6.350	—	HR			170-4-1061-1•
2.364-36 Involute Spline								
2.364	3.000	2.685	5.470	—	HR	170-4-1021-1X•	232200	170-4-1011-1 ⅄
2.364	3.000	2.685	6.780	—	HR	170-4-791-1X•	232200	170-4-781-1 ⅄ *High angle yoke*
2.364	3.500	2.485	5.270	.306	HR	170-4-1041-1X	232201	170-4-1031-1
2.374-46 Spline								
2.374	3.250	2.875	5.760	.140	HR	170-4-581-1X•	231179	170-4-571-1■
2.374	3.250	2.875	5.760	.140	HR	170-4-591-1X	231615	170-4-571-1■
2.374	3.250	2.875	7.250	.140	HR	170-4-611-1X	231615	170-4-601-1 ⅄ *High angle yoke*
2.374	3.500	2.406	5.880	—	HR	170-4-1221-1X	232042-10	170-4-1211-1•
2.374	3.500	2.406	6.688	—	HR	170-4-1291-1X	232042-10	170-4-1281-1• *High angle yoke*
2.374	3.750	2.406	5.190	—	HR	170-4-1191-1X		170-4-1171-1 ⅄ *Assy includes electronic speedometer gear #231528*
2.390-46 Involute Spline								
2.390	2.879	2.750	5.590	.157	HR			170-4-1271-1 *Coupling shaft yoke*
2.390	3.250	2.328	5.100	.140	HR	170-4-721-1X	231803	170-4-711-1•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



BS/CV/HR/UB Style

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
SPL170 SERIES (Continued)					**E-6.456 IN. D-2.166 IN.**			**USE KIT SPL170-3X**
USE BEARING RETAINER KIT NO. 170-70-18X								
2.390-46 Involute Spline (Continued)								
2.390	3.250	2.328	5.100	.140	HR	5003558	5003552	170-4-711-1•
2.390	3.250	2.328	6.438	.140	HR	170-4-741-1X	231803	170-4-731-1⅄ *High angle yoke*
2.390	3.250	2.875	5.760	.140	HR			170-4-1681-1
2.390	3.375	3.195	6.531	.580	HR	170-4-301-1X	232610	170-4-291-1•
2.500-10 Spline								
2.500	3.500	2.406	5.188	—	HR	170-4-1351-1X	232042-11	170-4-1341-1•
2.500	3.750	3.000	5.750	—	HR	170-4-481-1X	231616	170-4-471-1■ *Hub machined for speedometer gear*
2.544-49 Involute Spline								
2.544	3.750	3.000	6.000	—	HR	170-4-421-1X	231616	170-4-411-1⅄ *Hub machined for speedometer gear*
2.544	3.818	2.125	6.260	.120	HR	5008451	5008437	170-4-1911-1⅄ *131434K = 5008451 yoke assy & nut# 131095; Spicer axles only*
2.544	3.820	2.135	5.530	.120	HR	5008458	5008437	170-4-1891-1• *131433K = 5008458 yoke assy & nut# 131095; Spicer axles only*
2.544	3.820	2.675	6.810	.240	HR	5008461	5008437	5006714⅄ *132931K = 5008461 yoke assy & nut# 131095; Spicer axles only*
2.544	3.820	2.682	6.040	.240	HR	5008444	5008437	5005217⅄ *132863K = 5008444 yoke assy & nut# 131095; Spicer axles only*
2.544	4.000	2.750	6.050	.180	HR			170-4-1161-1
2.750-10 Spline								
2.750	—	3.000	5.850	—	HR			170-4-531-1• *Hub diameter not ground.*
2.750	3.500	2.992	6.000	—	HR			170-4-1711-1
2.750	3.750	3.000	5.850	—	HR	170-4-501-1X	230902	170-4-491-1•
2.750	3.750	3.000	5.850	—	HR	170-4-521-1X	231616	170-4-511-1
2.750	4.000	2.935	5.800	—	HR			170-4-1141-1•
2.794-54 Involute Spline								
2.794	—	2.750	5.600	—	HR			170-4-561-1 *Hub diameter not ground.*
2.795-55 Involute Spline								
2.795	4.725	2.047	5.200	.150	HR			170-4-1091-1•
SPL250 SERIES			**E-6.412 IN. D-2.362 IN.**					**USE KIT SPL250X**
USE BEARING RETAINED NO. 250-70-18X								
2.024-39 Involute Spline								
2.024	3.000	2.245	5.240	.280	HR	250-4-391-1X	232199	250-4-381-1•
2.114-32 Involute Spline								
2.114	3.000	2.245	5.240	.424	HR	250-4-421-1X	232200	250-4-411-1⅄
2.143-41 Involute Spline								
2.143	2.938	2.500	5.490	—	HR	250-4-141-1X	232604	250-4-131-1⅄

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
SPL250 SERIES (Continued)					**E-6.412 IN. D-2.362 IN.**			**USE KIT SPL250X**
USE BEARING RETAINED NO. 250-70-18X								
2.225-6 Spline								
2.225	3.000	3.250	6.240	—	HR	250-4-541-1X	829-W	250-4-531-1⅄
2.225	3.000	3.250	6.250	—	HR			250-4-811-1
2.274-44 Involute Spline								
2.274	2.938	2.350	5.328	—	HR	250-4-41-1X	232604	250-4-31-1⅄
2.274	2.938	2.500	5.484	—	HR	250-4-61-1X	232168	250-4-51-1⅄
2.274	3.000	2.500	5.490	.236	HR	250-4-81-1X	232511	250-4-71-1•
2.364-36 Involute Spline								
2.364	3.000	2.685	5.680	—	HR	250-4-371-1X■	232199	250-4-361-1
2.374-46 Spline								
2.374	3.250	2.625	5.610	—	HR	250-4-781-1X•	231179	250-4-771-1⅄
2.374	3.250	2.875	5.870	.140	HR	250-4-301-1X	231615	250-4-281-1⅄
2.374	3.250	2.875	5.870	.140	HR	250-4-291-1X	231179	250-4-281-1⅄
2.374	3.500	2.406	6.140	—	HR	250-4-651-1X	232042-10	250-4-641-1
2.374	3.750	2.400	6.650	—	HR	250-4-801-1X		250-4-791-1⅄
						Assy includes electronic speedometer gear #231528		
2.374	3.750	2.406	5.410	—	HR	250-4-621-1X		250-4-601-1⅄
						Assy includes electronic speedometer gear #231528		
2.390-46 Involute Spline								
2.390	3.250	2.312	5.312	.140	HR	250-4-351-1X	231803	250-4-341-1•
2.390	3.250	2.312	5.312	.140	HR	5003560	5003552	250-4-341-1•
2.390	3.344	2.750	5.750	—	HR			250-4-21-1
								Coupling shaft yoke
2.390	3.375	3.195	6.760	.580	HR	250-4-101-1X	232610	250-4-91-1⅄
2.390	3.500	3.375	6.560	—	HR			250-4-471-1•
2.500-10 Spline								
2.500	3.500	2.406	5.500	—	HR	250-4-711-1X	232042-11	250-4-701-1⅄
2.500	3.750	3.000	6.062	—	HR	250-4-201-1X	231616	250-4-191-1■
							Hub machined for speedometer gear	
2.500	3.750	3.000	6.250	—	HR			250-4-561-1
							Hub machined for speedometer gear	
2.544-49 Involute Spline								
2.544	3.750	3.000	6.250	—	HR	250-4-161-1X	231616	250-4-151-1⅄
							Hub machined for speedometer gear	
2.544	3.819	2.125	5.830	.120	HR	5008459	5008437	250-4-1021-1⅄
						131435K = 5008459 yoke assy & nut# 131095; Spicer axles only		
2.544	3.819	2.692	6.200	.240	HR	5008445	5008437	250-4-1031-1⅄
						131446K = 5008445 yoke assy & nut# 131095; Spicer axles only		
2.635-20 Involute Spline								
2.635	3.750	2.750	6.270	—	HR	250-4-521-1X	231745	250-4-511-1•
							Hub machined for speedometer gear	
2.750-10 Spline								
2.750	—	3.000	6.310	—	HR			250-4-251-1•
2.750	3.500	3.000	6.312	—	HR	250-4-761-1X	230674	250-4-751-1•
2.750	3.750	3.000	6.297	—	HR	250-4-241-1X	231616	250-4-231-1•
2.750	3.750	3.000	6.300	—	HR	250-4-221-1X	230902	250-4-211-1⅄
2.750	4.000	2.935	6.370	—	HR			250-4-551-1
							Hub machined for speedometer gear	
2.794-54 Involute Spline								
2.794	—	2.750	5.703	—	HR			250-4-271-1
								Hub diameter not ground.
2.794	3.750	2.770	6.330	—	HR			250-4-901-1•
2.795-55 Involute Spline								
2.795	4.725	2.047	5.413	.150	HR			250-4-501-1•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



BS/CV/HR/UB Style

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
SPL250 SERIES (Continued)					**E-6.412 IN. D-2.362 IN.**			**USE KIT SPL250X**
USE BEARING RETAINED NO. 250-70-18X								
2.922-22 Involute Spline								
2.922	4.067	2.645	6.030	.400	HR			250-4-911-1
3.124-48 Involute Spline								
3.045	4.250	1.955	5.079	—	HR			5005681 ⅄ *OEM only*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Hub Dia.	Set Screw Diameter	Pin Hole Diameter	Location Viewed From Hub	S Centerline to End of Hub	Spicer Part Number
1000 SERIES		**K-1.500 D-.938**				**USE KIT 5-170X**
.875-13 Spline						
1.500	.250	—	6	3.812	10-4-641	
1.625	.375	—	6	2.500	10-4-481	
1.000-6 Spline						
1.625	.375	—	3	2.500	10-4-101	*.375 Dia. set screw @ 3 or 9*
1.125-6 Spline						
1.625	—	.328	THRU HUB	2.500	10-4-11	*.328 dia. pin hole thru hub*
1.250-6 Spline						
1.625	—	.328	THRU HUB	2.500	10-4-21	*.328 dia. pin hole thru hub*
1.375-6 Spline						
2.000	—	.328	THRU HUB	2.500	10-4-31	*.328 dia. pin hole thru hub*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1100 SERIES		**E-2.656**	**D-.938**					**USE KIT 5-101X OR 5-111X**
.878-13 Involute Spline								
.878	2.000	1.250	2.250	—	SR			1-4-1201
1210 SERIES		**E-2.438**	**D-1.062**					**USE KIT 5-443X**
USES U-BOLT ASSY. 2-94-28X, STRAP ASSY. 2-70-18X								
.984-22 Involute Spline								
.984	1.547	1.297	3.305	—	BS	2-4-7221-1X	42735	2-4-7111-1•
1.031-23 Involute Spline								
1.031	1.562	1.500	3.063	—	BS	2-4-5921-1X	41498	2-4-5911-1•
1.146-26 Involute Spline								
1.146	1.594	1.594	2.938	—	BS	2-4-6731-1X	231596	2-4-6721-1• *Coupling shaft yoke*
1.146	1.625	1.156	2.750	—	BS			2-4-5901-1
1.146	1.625	1.156	3.375	—	CV			2-4-5891•
1.146	1.750	1.375	2.938	—	BS			2-4-6191-1 *Hub diameter not ground.*
1310 SERIES		**SR: E-3.469 OTHERS E-3.219, D-1.062**						**USE KIT 5-153X,5-785X,5-810X**
USES U-BOLT ASSY. 2-94-28X, STRAP ASSY. 2-70-18X								
.878-13 Involute Spline								
.878	2.000	1.567	2.562	—	SR			2-4-3331 *.375 Diameter set screw. Hub diameter not ground*
.970-29 Involute Spline								
.970	1.500	1.500	3.000	.299	BS			2-4-8031-1•
.984-10 Spline								
.984	1.562	1.938	3.656	—	UB			2-4-1721
1.010-15 Involute Spline								
1.010	1.594	2.656	3.562	—	SR			2-4-4931
1.010	2.120	1.240	2.312	—	SR			2-4-4921 *Hub diameter not ground.*
1.010	2.120	1.470	2.500	—	SR			2-4-8241 *.375 Diameter set screw. Hub diameter not ground*
1.026-23 Involute Spline								
1.026	1.552	1.500	3.000	—	BS	2-4-6131-1X	41498	2-4-6121-1•
1.070-16 Involute Spline								
1.070	1.625	1.750	3.219	.201	BS	2-4-6981-1X•	—	2-4-6661-1 ⅄ *Assembly includes Balance Disc #231901*
1.125-10 Spline								
1.125	1.552	1.500	3.000	—	UB	2-4-2821X•	15099	2-4-2791•
1.125	1.552	1.500	3.000	—	BS	2-4-2821-1X	15099	2-4-2791-1 ⅄
1.125	1.552	1.500	3.000	—	BS	2-4-2801-1X	31875	2-4-2791-1 ⅄
1.125	1.552	1.500	3.000	.310	BS	2-4-2851-1X•	330851	2-4-2841-1•
1.125	1.552	1.500	3.000	.311	CV	2-4-4061X	330699	2-4-4051•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1310 SERIES (Continued) SR: E-3.469 OTHER0S E-3.219, D-1.062 USE KIT 5-153X,5-785X,5-810X								
USES U-BOLT ASSY. 2-94-28X, STRAP ASSY. 2-70-18X								
1.146-26 Involute Spline								
1.146	1.375	1.750	3.125	—	SR			2-4-3161
1.146	1.453	1.500	3.000	—	BS	2-4-6411-1X•	231877	2-4-6401-1• *Coupling shaft yoke*
1.146	1.467	1.500	3.000	—	BS	2-4-6181-1X•	231579	2-4-6171-1⅄ *Coupling shaft yoke*
1.146	1.469	1.465	3.500	—	BS	2-4-8191-1X•	231579	2-4-8181-1⅄ *High angle yoke*
1.146	1.469	1.484	3.500	—	BS	2-4-7501-1X	231579	2-4-7491-1• *Coupling shaft yoke*
1.146	1.484	1.484	3.000	—	BS	2-4-7291-1X	232020	2-4-7401-1⅄ *Coupling shaft yoke*
1.146	1.500	1.465	3.000	—	BS	2-4-8701-1X•	231970	2-4-8691-1⅄ *Coupling shaft yoke*
1.146	1.500	1.469	3.000	—	BS			2-4-7021-1 *Coupling shaft yoke; Hub diameter not ground*
1.146	1.500	1.736	3.270	—	BS	2-4-8541-1X•	232911-1	2-4-8531-1⅄ *Coupling shaft yoke; Hub diameter not ground*
1.146	1.513	2.000	3.300	—	SR	2-4-8171X•	232184	2-4-8161• *Coupling shaft yoke*
1.146	1.552	1.495	2.995	—	BS			2-4-6561-1
1.146	1.552	1.500	2.914	—	BS			2-4-8321-1•
1.146	1.552	1.500	3.000	—	CV			2-4-4341
1.146	1.552	1.500	3.000	—	BS			2-4-6641-1
1.146	1.552	1.500	3.000	—	BS			2-4-6781-1
1.146	1.552	1.500	3.000	—	UB			2-4-7871•
1.146	1.552	1.500	3.000	—	BS			2-4-7871-1•
1.146	1.552	1.500	3.000	—	UB	2-4-8091X	41498	2-4-8081•
1.146	1.552	1.500	3.000	—	BS	2-4-8091-1X	41498	2-4-8081-1•
1.146	1.552	1.500	3.406	—	UB	2-4-5251X•	41498	2-4-5241⅄ *Spec. yoke w/1.125 dia. brg. caps*
1.146	1.552	1.500	3.156	—	BS	2-4-5331X	15099	2-4-5321• *Attaching hardware by OEM*
1.146	1.552	1.500	3.000	—	BS			2-4-2271-1
1.146	1.844	1.370	3.130	.120	BS	2-4-8551-1X	232816	2-4-8521-1•
1.146	1.844	1.370	3.235	.120	BS			2-4-8311-1
1.146	1.844	1.375	2.938	.120	BS			2-4-4601-1
1.146	1.844	1.375	2.938	.120	BS	2-4-6901-1X	42779	2-4-6891-1⅄
1.172-27 Involute Spline								
1.172	1.688	1.062	2.750	—	BS			2-4-5851-1
1.172-9 Based On 10 Spline								
1.172	1.250	1.438	2.469	—	SR			2-4-1921 *Hub diameter not ground.*
1.183-6 Spline								
1.183	1.620	1.500	2.935	—	UB			2-4-1301 *.188 Dia drilled hole thru hub*
1.215-18 Involute Spline								
1.215	2.120	1.500	2.562	—	SR			2-4-6301 *Hub diameter not ground.*
1.229-28 Involute Spline								
1.229	1.844	1.375	2.938	.120	BS			2-4-3741-1
1.229	1.844	1.375	2.938	.120	BS	2-4-7371-1X■	231935-1	2-4-6161-1 *Zinc plated slinger*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1310 SERIES (Continued) SR: E-3.469 OTHERS E-3.219, D-1.062 USE KIT 5-153X,5-785X,5-810X								
USES U-BOLT ASSY. 2-94-28X, STRAP ASSY. 2-70-18X								
1.250-10 Spline								
1.250	1.750	2.000	3.375	—	CV	2-4-4021X	230881	2-4-4011•
1.250	1.750	2.000	3.625	—	UB			2-4-1831
1.250	1.875	1.500	2.938	—	BS	2-4-1991-1X	30798	2-4-1981-1⅄
1.250	1.875	1.500	2.938	—	UB	2-4-2611X	230421	2-4-2601•
1.250	1.875	1.500	2.938	—	BS	2-4-2611-1X	230421	2-4-2601-1•
1.250	2.000	1.750	3.281	—	UB	2-4-4471X	500166-24	2-4-2901
1.250	2.000	1.750	3.625	—	UB			2-4-7731•
1.268-14 Involute Spline								
1.268	2.000	2.500	3.688	—	SR			2-4-5411
						.375 Dia.set screw @ 6 OR 12, hub diameter not ground.		
1.268	2.120	1.500	2.562	—	SR			2-4-1741
1.268	2.125	1.953	3.453	—	BS			2-4-7141-1
1.274-19 Involute Spline								
1.274	2.000	1.344	2.500	—	SR			2-4-6341
								Hub diameter not ground.
1.276-29 Involute Spline								
1.276	1.875	1.500	2.531	—	UB	2-4-3781X	30798	2-4-3771•
1.276	1.875	1.500	2.938	—	UB	2-4-3801X	34592	2-4-3791•
1.276	1.875	1.500	2.938	—	BS	2-4-3801-1X	34592	2-4-3791-1•
1.276	1.875	1.500	2.996	—	BS	2-4-8391-1X	34592	2-4-8331-1•
1.326-30 Involute Spline								
1.326	1.750	2.000	3.375	—	CV	2-4-5421X	230881	2-4-4801•
1.375-10 Spline								
1.375	2.000	2.000	3.438	.250	UB			2-4-2371
1.375	1.719	1.500	2.938	—	UB			2-4-411
1.375	1.750	1.750	3.219	—	UB			2-4-2671
						Hub diameter not ground. Coupling shaft yoke		
1.375	2.125	1.156	2.594	—	BS			2-4-6001-1
1.375	2.125	1.375	2.938	—	UB			2-4-6011
1.375	2.125	1.375	2.938	—	UB			2-4-7151
1.375	2.125	2.000	3.438	—	UB			2-4-1731
								Hub diameter not ground.
1.375	2.125	2.000	3.438	—	UB	2-4-2411X•	230421	2-4-2401•
1.375	2.125	2.000	3.438	—	BS	2-4-2411-1X	230421	2-4-2401-1
1.375	2.125	2.000	3.469	—	BS			2-4-6671-1•
1.375-6 Spline								
1.375	2.125	1.500	2.969	—	UB			2-4-1311
1.377-21 Involute Spline								
1.377	2.125	1.469	2.562	—	SR			2-4-5781
								Hub diameter not ground.

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1310 SERIES (Continued) SR: E-3.469 OTHERS E-3.219, D-1.062 USE KIT 5-153X,5-785X,5-810X								
USES U-BOLT ASSY. 2-94-28X, STRAP ASSY. 2-70-18X								
1.383-21 Involute Spline								
1.383	2.250	1.650	3.115	—	BS			2-4-7801-1
								Hub diameter not ground.
1.400-32 Involute Spline								
1.400	2.125	2.000	3.438	—	BS			2-4-4191-1
1.401-32 Involute Spline								
1.401	1.875	2.000	3.875	—	CV			2-4-5341
1.403-21 Involute Spline								
1.403	1.620	1.562	3.000	—	CV			2-4-5091
						Hub diameter not ground. Flats on hub, slot thru hub, drilled hole thru hub		
1.403	2.125	1.125	2.594	—	BS			2-4-5991-1
1.500-10 Spline								
1.500	2.125	1.734	3.500	—	BS			2-4-7181-1
								Hub diameter not ground.
1330 SERIES SR: E-3.875 OTHERS:E-3.625, D-1.062 USE KIT 5-213X,5-790X, 5-812X								
USES U-BOLT ASSY. 2-94-28X, STRAP ASSY. 2-70-18X								
1.118-27 Involute Spline								
1.118	1.970	1.785	3.772	.276	BS	5003952	5003953	5002013 ⅄
1.146-26 Involute Spline								
1.146	1.552	1.500	3.000	—	BS	2-4-3581-1X	41498	2-4-3571-1 ⅄
1.146	1.844	1.375	3.562	.120	BS			2-4-7631-1
								High angle yoke
1.200-29 Involute Spline								
1.200	1.653	1.799	3.772	.335	BS	5003950	5003951	5002012 ⅄
1.200	1.653	1.799	3.772	.335	BS	5003954	5003955	5002015 ⅄
1.202-17 Involute Spline								
1.202	1.688	1.719	3.188	.460	BS	2-4-5691-1X•	231302	2-4-5681-1•
1.229-28 Involute Spline								
1.229	1.844	1.375	2.938	.120	BS	2-4-7031-1X	231935-1	2-4-6851-1■
								Zinc plated slinger
1.276-29 Involute Spline								
1.276	1.875	1.500	2.938	—	BS	2-4-4291-1X	34592	2-4-4031-1
1.276	1.875	1.500	2.938	—	BS	2-4-8051-1X	41195	2-4-8041-1 ⅄
1.276	1.875	1.500	3.188	—	BS			2-4-8421-1
1.401-32 Involute Spline								
1.401	1.875	2.000	3.875	—	CV			2-4-5441
1.401	2.125	2.000	3.438	—	BS			2-4-5521-1
1.403-21 Involute Spline								
1.403	1.906	1.719	3.594	—	CV			2-4-6221
								Flats on hub, slot thru hub, drilled hole thru hub
1.403	2.000	2.531	4.062	.240	CV			2-4-6231•
								Hub diameter not ground.
1330-F SERIES SR: E-3.875 OTHERS E-3.625 D-1.125 USE KIT 5-1204X, 5-792X								
USES U-BOLT ASSY NO. 2-94-58X								
1.146-26 Involute Spline								
1.146	1.562	1.500	3.000	—	UB	2-4-6111X	41498	2-4-6101•
1.276-29 Involute Spline								
1.276	1.875	1.500	2.938	—	UB	2-4-5311X	34592	2-4-5301•
1.276	1.875	1.500	2.938	—	UB	2-4-8051X■	41195	2-4-8041 ⅄
1340 SERIES E-3.953 D-1.250 USE KIT NO. 5-243X								
1.375-6 Spline								
1.375	2.375	1.750	3.875	—	SR			3-4-5341•
1.375	2.375	1.875	3.875	—	SR			3-4-5101■

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1350 SERIES			**SR: E-3.875 OTHERS: E-3.625, D-1.188**				**USE KIT 5-178X, 5-799X**	
USES U-BOLT ASSY. 3-94-18X, STRAP ASSY. 3-70-28X								
.970-29 Involute Spline								
.970	1.500	1.500	3.547	.299	BS			3-4-11721-1
1.125-10 Spline								
1.125	1.552	1.500	3.000	—	BS			3-4-2111-1
1.146-26 Involute Spline								
1.146	1.550	1.500	3.000	—	BS			3-4-13761-1
1.146	1.562	1.500	3.000	—	BS	3-4-5761-1X	15099	3-4-5751-1 ⅄
1.181-10 Spline								
1.181	1.875	1.656	3.125	—	BS			3-4-2051-1
1.194-46 Involute Spline								
1.194	2.000	2.203	3.938	—	BS			3-4-9821-1
1.209-27 Involute Spline								
1.209	1.516	1.469	3.250	.290	BS	3-4-11911-1X	232064	3-4-9941-1
1.209	1.516	1.469	3.328	.290	BS	3-4-11231-1X•	231636	3-4-11221-1 ⅄
1.229-28 Involute Spline								
1.229	1.844	1.375	3.031	.120	BS	3-4-11931-1X	231935-1	3-4-11901-1• *Zinc plated slinger*
1.250-10 Spline								
1.250	2.125	1.750	3.312	—	UB			3-4-2781•
1.268-14 Involute Spline								
1.268	—	—	2.688	—	SR			3-4-13161
1.276-29 Involute Spline								
1.276	1.810	1.495	2.995	—	BS			3-4-14621-1 *Coupling shaft yoke*
1.276	1.875	1.500	3.000	—	BS			3-4-12211-1■
1.276	1.875	1.500	3.000	—	BS	3-4-13031-1X•	45799	3-4-12771-1•
1.276	1.875	1.500	3.000	—	BS	3-4-12781-1X ⅄	34592	3-4-12771-1•
1.276	1.875	1.500	3.000	—	BS	3-4-13031-2X	45799	3-4-12771-2 ⅄ *Attaching hardware by OEM*
1.276	1.875	1.500	3.000	—	BS	3-4-14541-1X ⅄	34592	3-4-14531-1
1.276	1.875	1.500	3.000	—	BS	3-4-14701-1X•	52392	3-4-14671-1 ⅄
1.276	1.875	1.500	3.000	—	BS	3-4-5731-1X	34592	3-4-5721-1
1.282-15 Involute Spline								
1.282	1.810	1.450	3.030	—	BS			3-4-11421-1• *Hub diameter not ground.*
1.282	1.812	1.600	3.031	—	BS			3-4-11441-1• *Hub diameter not ground.*
1.282	1.970	2.250	3.875	—	BS			3-4-13601-1 *Hub diameter not ground.*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1350 SERIES (Continued) SR: E-3.875 OTHERS: E-3.625, D-1.188							**USE KIT 5-178X, 5-799X**	
USES U-BOLT ASSY. 3-94-18X, STRAP ASSY. 3-70-28X								
1.284-14 Involute Spline								
1.284	2.000	1.438	2.688	—	SR	3-4-5391X	230859	3-4-5301
1.284	2.000	1.719	2.688	—	SR			3-4-7401
						.375 Dia.set screw @ 6 OR 12, hub diameter not ground.		
1.312-30 Involute Spline								
1.312	1.938	1.156	3.125	—	BS	3-4-8691-1X	231356	3-4-8681-1
1.375-10 Spline								
1.375	1.703	1.375	2.922	—	BS			3-4-11711-1
1.375	1.719	1.781	3.281	—	BS	3-4-178-1X	98-1473	3-4-2171-1•
								Coupling shaft yoke
1.375	1.719	2.000	3.500	—	BS			3-4-1261-1
1.375	1.750	1.812	3.312	—	BS			3-4-1111-1
1.375	2.000	2.000	3.500	.250	BS			3-4-1211-1
1.375	2.000	2.188	4.281	.250	UB	3-4-1371-1	—	3-4-1371•
1.375	2.125	2.000	3.500	—	BS			3-4-3951-1
1.375	2.125	2.000	3.688	—	BS			3-4-3291-1
1.378-31 Based On 32 Spline								
1.378	1.885	4.094	5.594	—	BS			3-4-13211-1
								Uses GM brg. strap
1.378	1.885	4.094	5.594	—	BS			3-4-13731-1
								Nickel plated; uses GM brg. strap
1.378-32 Involute Spline								
1.378	2.000	1.375	3.000	—	SR			3-4-12611•
1.401-32 Involute Spline								
1.401	2.125	2.000	3.500	—	BS			3-4-6211-1
1.401	2.125	2.719	4.750	—	UB			3-4-7241•
1.401	2.125	2.719	4.750	—	BS			3-4-7241-1
1.403-21 Involute Spline								
1.403	1.938	1.938	3.844	—	BS	3-4-13011-1X	2-68-104	3-4-13001-1•
1.403	1.938	2.045	3.835	—	BS			3-4-14461-1
1.403	2.000	1.234	2.953	—	BS			3-4-10591-1
1.403	2.000	2.245	4.285	—	BS			3-4-14451-1
1.498-29 Involute Spline								
1.498	1.969	1.828	3.922	—	BS			3-4-10281-1•
1.498	1.969	2.837	4.984	1.026	BS			3-4-12461-1
1.500-10 Spline								
1.500	1.810	2.000	3.695	—	BS			3-4-13881-1
								Coupling shaft yoke; Hub diameter not ground
1.500	2.250	2.000	3.500	—	BS			3-4-1441-1
1.500	2.250	2.063	3.530	—	BS			3-4-1501-1
1.500	2.253	2.185	3.905	—	BS	3-4-3671-1X•	230386	3-4-2231-1
1.500	2.500	2.000	3.766	.540	BS			3-4-8511-1
1.511-14 Involute Spline								
1.511	2.125	2.531	4.500	—	BS			3-4-8501-1
1.511	2.375	1.828	3.312	—	BS			3-4-8491-1•
1.625-10 Spline								
1.625	2.375	2.125	3.969	—	UB	3-4-9001X•	230895	3-4-3931•
1.625	2.375	2.125	3.969	—	BS	3-4-9001-1X•	230895	3-4-3931-1•
1.750-10 Spline								
1.750	2.375	1.812	3.500	—	BS			3-4-3801-1
1.750	2.375	2.188	4.000	—	BS			3-4-2351-1

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1410 SERIES			**SR: E-4.438 OTHERS: E-4.188, D-1.188**					**USE KIT 5-160X, 5-801X**
USES U-BOLT ASSY, 3-94-18X, STRAP KIT 3-70-28X								
1.250-10 Spline								
1.250	1.875	1.500	3.188	—	BS	3-4-4451-1X	30798	3-4-4441-1 ⅄
1.260-23 Involute Spline								
1.260	1.565	1.609	3.562	.360	BS			3-4-10941-1
1.268-14 Involute Spline								
1.268	1.516	1.750	2.750	—	SR			3-4-5321
								Hub diameter not ground.
1.268	2.250	2.125	4.031	—	BS	3-4-9561-1X	2-68-293	3-4-9551-1
								w/zerk fitting
1.268	2.375	2.250	4.031	—	BS			3-4-7721-1
								.375 Dia.set screw @ 6 OR 12, hub diameter not ground.
1.276-29 Involute Spline								
1.276	1.810	1.500	3.200	—	BS			3-4-14591-1
								Coupling shaft yoke
1.276	1.874	1.420	3.185	—	BS	3-4-11891-1X	34592	3-4-11851-1
1.276	1.875	1.500	3.188	—	BS	3-4-5711-1X	34592	3-4-5701-1•
1.276	1.875	1.500	3.188	—	BS			3-4-8731-1
1.276	1.875	1.500	3.200	—	BS	3-4-14711-1X	52392	3-4-14681-1 ⅄
								Attaching hardware by OEM
1.375-10 Spline								
1.375	1.719	1.781	3.469	—	BS	3-4-2851-1X	98-1473	3-4-2841-1•
								Hub diameter not ground.
1.375	1.719	2.000	3.703	—	BS			3-4-1471-1
1.375	1.875	1.688	3.500	—	BS	3-4-12541-1X•	2-68-164	3-4-12531-1 ⅄
1.375	1.938	2.000	3.688	—	BS			3-4-1481-1
1.375	2.125	2.000	3.685	—	BS			3-4-2271-1
1.375	2.500	1.938	5.750	—	BS			3-4-7141
								Flanged end yoke, strap kit not furnished by Dana
1.375-32 Involute Spline								
1.375	1.886	2.000	3.675	—	BS			3-4-13511-1
								Uses GM brg. strap
1.383-21 Involute Spline								
1.383	2.625	3.312	4.641	1.190	BS			3-4-11471-1
1.400-32 Involute Spline								
1.400	2.125	2.000	3.688	—	BS			3-4-10951-1
1.498-29 Involute Spline								
1.498	1.969	1.828	3.938	—	BS			3-4-10571-1•
1.498	2.000	1.609	3.688	—	BS			3-4-10931-1
1.500-10 Spline								
1.500	1.812	2.000	3.719	—	BS	3-4-6631-1X	231004	3-4-6561-1
								Coupling shaft yoke
1.500	2.125	2.000	3.688	.250	BS			3-4-1901-1

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1410 SERIES (Continued) SR: E-4.438 OTHERS: E-4.188, D-1.188							**USE KIT 5-160X, 5-801X**	
USES U-BOLT ASSY, 3-94-18X, STRAP KIT 3-70-28X								
1.500-10 Spline (Continued)								
1.500	2.125	2.000	3.688	—	BS			3-4-3961-1
1.500	2.125	2.188	3.875	—	UB			3-4-6531■
1.500	2.250	1.750	3.750	—	BS			3-4-1911-1•
1.500	2.250	2.188	3.875	—	BS			3-4-2241-1
1.500	2.312	2.000	3.688	—	BS	3-4-7321-1X	230124	3-4-2941-1
1.500	2.406	2.000	3.688	—	UB			3-4-6751•
1.500	2.625	2.000	3.844	—	BS			3-4-10551-1
								Coupling shaft yoke
1.500-10 Involute Spline								
1.500	1.810	2.000	3.690	—	BS			3-4-13871-1■
								Coupling shaft yoke; Hub diameter not ground
1.506-23 Involute Spline								
1.506	2.375	1.406	3.500	.240	BS			3-4-11811-1
1.525-35 Involute Spline								
1.525	2.125	2.000	3.688	—	BS			3-4-5191-1
1.525	2.500	1.938	3.750	—	BS			3-4-9251-2
								Attaching hardware by OEM
1.525	2.500	1.938	5.750	—	BS			3-4-7151
								Flanged end yoke, strap kit not furnished by Dana
1.527-22 Based On 23 Spline								
1.527	1.889	2.678	4.425	.080	BS			3-4-11741-1•
1.527	1.890	1.605	3.500	—	BS			3-4-11591-1
1.527	1.890	1.614	3.500	—	BS			3-4-10231-1■
1.588-24 Involute Spline								
1.588	2.250	2.125	4.000	.470	BS	3-4-11701-1X	3-68-124	3-4-8701-1•
1.590-30 Involute Spline								
1.590	2.200	1.625	3.719	—	BS	3-4-8001-1X	232037	3-4-7991-1•
1.609-15 Involute Spline								
1.609	2.125	1.938	3.750	—	BS			3-4-7311-1
1.609-37 Involute Spline								
1.609	2.500	2.000	4.300	.240	BS	3-4-14721-1X•	84406	3-4-14371-1
1.609	2.500	2.000	4.300	.240	BS	3-4-14391-1X	232895	3-4-14371-1
1.609	2.500	2.000	4.312	.240	BS	3-4-11081-1X	231872	3-4-9931-1•
1.625-10 Spline								
1.625	2.375	2.125	3.938	—	BS			3-4-3491-1
1.625	2.375	2.125	4.188	—	BS	3-4-5921-1X	230895	3-4-2131-1•
1.650-16 Involute Spline								
1.650	2.375	2.000	3.812	—	UB			3-4-2281•
1.750-10 Spline								
1.750	2.250	2.188	4.188	—	UB			3-4-3351•
1.750	2.359	2.094	4.203	—	BS			3-4-11761-1
1.750	2.375	1.938	3.969	—	BS			3-4-8031-1
1.750	2.375	2.188	4.188	—	BS			3-4-1161-1
1.750	2.375	2.188	4.188	—	BS			3-4-1841-1
1.750	2.500	1.938	5.750	—	BS			3-4-7131
								Flanged end yoke, strap kit not furnished by Dana
1.750	2.501	2.000	4.000	.250	BS			3-4-13911-1
1.750	2.625	2.188	4.000	—	BS	3-4-5881-1X	230909	3-4-3041-1
								.250 deep spline chamfer
1.750	2.625	2.188	4.250	—	BS			3-4-2511-1
								.250 deep spline chamfer
1.750	2.625	2.188	4.250	—	BS			3-4-7031-1
								.250 deep spline chamfer

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1410 SERIES (Continued) SR: E-4.438 OTHERS: E-4.188, D-1.188								**USE KIT 5-160X, 5-801X**
USES U-BOLT ASSY, 3-94-18X, STRAP KIT 3-70-28X								
1.751-27 Involute Spline								
1.751	2.625	1.438	3.465	—	BS			3-4-10541-1•
1.751	2.780	2.060	4.230	—	BS			5004785
								Hub diameter not ground.
1.774-34 Involute Spline								
1.774	2.500	2.250	4.188	—	UB	3-4-8061X	231206	3-4-7551
								3-4-7551 was replaced by 3-4-8061X
1.784-27 Involute Spline								
1.784	2.625	2.000	4.000	—	BS			3-4-8721-1
								Flanged end yoke.
1.790-34 Involute Spline								
1.790	2.625	2.188	4.031	—	BS	3-4-10461-1X	232039	3-4-10251-1
1.878-14 Involute Spline								
1.878	2.564	2.015	4.219	—	UB			3-4-8071•
1.878	2.564	2.015	4.219	—	BS			3-4-8071-1•
1.972-10 Spline								
1.972	2.594	1.844	3.969	—	BS			3-4-2251-1
1480 SERIES			**SR: E-4.438 OTHERS: E-4.188, D-1.375**					**USE KIT 5-188X, 5-803X**
USES U-BOLT ASSY NO.3-94-28X,STRAP ASSY. 3-70-38X								
1.276-29 Involute Spline								
1.276	1.875	1.500	3.500	—	BS	3-4-13391-1X	34592	3-4-9531-1•
1.375-10 Spline								
1.375	2.125	2.000	3.859	—	SR			3-4-13021•
1.375	2.125	2.000	4.031	—	BS			3-4-6701-1
1.375	2.125	2.000	4.031	—	UB			3-4-6701•
1.500-10 Spline								
1.500	1.810	2.000	4.025	—	BS			3-4-13921-1•
								Coupling shaft yoke; Hub diameter not ground
1.500	1.810	2.000	4.031	—	BS	3-4-7391-1X•	231004	3-4-6901-1
1.500	1.810	2.000	4.031	—	BS			3-4-6901-2
								Attaching hardware by OEM
1.500	1.938	2.000	4.031	—	BS	3-4-4421-1X	230124	3-4-3091-1
								Coupling shaft yoke
1.500	2.062	2.000	4.031	—	UB	3-4-3331X•	230207	3-4-3081•
								Coupling shaft yoke; Hub diameter not ground
1.500	2.062	2.000	4.031	—	BS	3-4-3331-1X•	230207	3-4-3081-1
								Coupling shaft yoke; Hub diameter not ground
1.500	2.125	2.000	4.219	.250	BS			3-4-3111-1
1.500	2.125	2.120	3.660	—	BS			3-4-7781•
								Flanged end yoke.

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1480 SERIES (Continued) SR: E-4.438 OTHERS: E-4.188, D-1.375							**USE KIT 5-188X, 5-803X**	
USES U-BOLT ASSY NO.3-94-28X,STRAP ASSY. 3-70-38X								
1.500-10 Spline (Continued)								
1.500	2.125	2.188	4.250	—	UB	3-4-6261X•	230895	3-4-6251•
1.500	2.250	2.188	4.200	—	BS	3-4-6221-1X	230895	3-4-3781-1
1.500	2.250	2.188	4.406	—	BS			3-4-3241-1
1.506-23 Involute Spline								
1.506	2.375	1.403	3.500	.240	BS			3-4-14031-1
1.525-35 Involute Spline								
1.525	2.500	1.938	5.750	—	UB			3-4-7161•
								Flanged end yoke.
1.533-17 Involute Spline								
1.533	2.120	1.950	4.000	—	BS			3-4-13791-1•
1.605-15 Involute Spline								
1.605	2.125	1.938	4.000	—	BS			3-4-9301-1
1.609-37 Involute Spline								
1.609	2.500	2.000	4.328	.240	BS	3-4-14731-1X•	84406	3-4-11171-1 ⅄
1.609	2.500	2.000	4.328	.240	BS	3-4-11281-1X	231872	3-4-11171-1 ⅄
1.625-10 Spline								
1.625	2.375	2.125	4.188	—	BS	3-4-5781-1X•	230895	3-4-3141-1 ⅄
1.625	2.375	2.125	4.312	—	UB			3-4-3771•
1.625-26 Involute Spline								
1.625	1.938	2.000	4.688	—	UB			3-4-9031•
1.750-10 Spline								
1.750	2.250	2.188	4.250	—	BS	3-4-6241-1X•	230895	3-4-6231-1•
1.750	2.250	2.188	4.406	—	BS			3-4-7361-1
1.750	2.362	2.120	4.215	—	BS			3-4-13821-1
1.750	2.362	2.125	4.214	—	BS			3-4-14551-1
1.750	2.375	2.188	4.219	—	BS			3-4-3191-1
1.750	2.375	2.188	4.219	—	BS			3-4-3571-1
1.750	2.500	1.922	3.859	—	UB			3-4-5911•
1.750	2.500	1.922	5.109	—	BS			3-4-11561-1
								Flanged end yoke, strap kit not furnished by Dana
1.750	2.500	1.938	4.000	—	BS			3-4-11871-2
								Attaching hardware by OEM
1.750	2.500	1.938	5.750	—	BS			3-4-7171
								Flanged end yoke, strap kit not furnished by Dana
1.750	2.500	1.953	4.000	—	BS			3-4-9271-1
1.750	2.500	1.953	4.000	—	BS			3-4-9271-2
								Attaching hardware by OEM
1.750	2.500	2.000	4.000	—	BS			3-4-13901-1
1.750	2.500	2.250	4.281	—	BS			3-4-6411-1•
1.750	2.625	1.938	3.969	—	UB			3-4-4051
1.750	2.625	2.188	4.281	—	BS	3-4-5811-1X	230909	3-4-3391-1•
								250 deep spline chamfer
1.750	2.625	2.188	4.750	—	BS			3-4-10301-1
								Flanged yoke w/.250 deep spline chamfer
1.750	2.625	2.250	4.281	—	BS	3-4-5791-1X	230909	3-4-3061-1
								.250 deep spline chamfer
1.750	2.625	2.250	4.469	—	BS			3-4-3121-1
1.750	2.685	2.245	4.276	—	BS			3-4-3541-1
1.750	2.750	2.250	4.281	.500	UB			3-4-9621
1.751-27 Involute Spline								
1.751	2.500	2.063	4.125	—	BS			3-4-11181-1•
1.751	2.625	2.281	4.250	—	BS			3-4-11161-1•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1480 SERIES (Continued) SR: E-4.438 OTHERS: E-4.188, D-1.375							**USE KIT 5-188X, 5-803X**	
USES U-BOLT ASSY NO.3-94-28X,STRAP ASSY. 3-70-38X								
1.751-27 Involute Spline (Continued)								
1.751	3.000	2.469	4.500	.490	BS			3-4-9981-1•
1.774-34 Spline								
1.774	2.500	2.250	4.469	—	BS	3-4-8051-1X	231206	3-4-7541-1⅄
1.774	2.500	2.250	4.469	—	BS			3-4-7541-2■
							Attaching hardware by OEM	
1.790-34 Involute Spline								
1.790	2.375	2.188	4.219	—	BS	3-4-12101-1X	232198	3-4-12091-1•
1.790	2.562	2.750	5.125	—	BS	3-4-9241-1X•	231059	3-4-9231-1•
							Attaching hardware by OEM	
1.790	2.562	2.750	5.125	—	BS	3-4-9241-2X•	231059	3-4-9231-2•
							Attaching hardware by OEM	
1.790	2.562	2.750	5.562	—	BS	3-4-7261-1X	231059	3-4-7251-1⅄
						Flanged end yoke, strap kit not furnished by Dana		
1.790	2.567	2.750	4.885	—	BS	3-4-11621-1X	231059	3-4-11551-1•
						Flanged end yoke, strap kit not furnished by Dana		
1.790	2.625	2.188	4.281	—	UB	3-4-10471X•	232039	3-4-10261•
1.790	2.625	2.188	4.281	—	BS	3-4-10471-1X	232039	3-4-10261-1
1.790	2.625	2.188	4.281	—	BS	3-4-11921-1X•	231935	3-4-10261-1
1.790	2.625	2.188	4.281	—	BS			3-4-13931-1
1.875-10 Spline								
1.875	2.750	2.375	4.406	—	BS	3-4-6671-1X■	230900	3-4-3901-1⅄
1.922-14 Involute Spline								
1.922	2.375	2.188	4.438	—	BS			3-4-11071-1
1.922	2.375	2.188	4.438	—	BS			3-4-7571-1
1.964-10 Spline								
1.964	2.500	2.000	4.688	—	UB			3-4-4211
1.969-10 Spline								
1.969	2.625	2.250	4.406	—	BS	3-4-5821-1X	230897	3-4-3861-1•
							.250 deep spline chamfer	
1.972-10 Spline								
1.972	2.594	1.859	4.500	—	BS			3-4-5441-1
1.972	2.598	1.859	4.525	—	BS			3-4-3051-1
1.998-38 Involute Spline								
1.998	2.750	2.125	4.156	—	BS			3-4-8781-1
1.998	3.000	2.125	4.281	—	BS	3-4-12121-1X•	232200	3-4-12111-1•
2.008-31 Involute Spline								
2.008	2.750	2.441	4.526	.240	BS			3-4-11771-1•
2.008	2.750	3.386	5.710	—	BS			3-4-11121-1•
								Flanged end yoke.

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1480 SERIES (Continued) SR: E-4.438 OTHERS: E-4.188, D-1.375							**USE KIT 5-188X, 5-803X**	
USES U-BOLT ASSY NO.3-94-28X,STRAP ASSY. 3-70-38X								
2.024-39 Involute Spline								
2.024	2.625	2.250	4.344	—	BS	3-4-11061-1X	232039	3-4-11051-1
2.024	2.625	2.250	4.344	.250	BS	3-4-13061-1X	232167	3-4-13051-1 ⅄
2.024	3.000	1.832	3.878	.250	BS	5006976	5006975	3-4-14781-1 ⅄
2.024	3.000	1.832	3.878	.250	BS	3-4-14791-1X	232511	3-4-14781-1 ⅄
2.024	3.000	1.832	3.878	.250	BS	3-4-14841-1X■	233051	3-4-14781-1 ⅄
2.024	3.000	2.281	4.344	.250	BS	3-4-13081-1X	232511	3-4-13071-1
2.114-32 Involute Spline								
2.114	3.000	2.250	4.281	.424	BS	3-4-13351-1X	232200	3-4-13341-1•
1550 SERIES			**SR:E=5.250, ALL OTHERS:E-4.964**			**D-1.375**	**USE KIT 5-155X, 5-808X**	
USES U-BOLT ASSY. 3-94-28X, STRAP ASSY. 3-70-38X								
1.500-10 Spline								
1.500	2.312	2.000	3.775	—	BS			4-4-2051-1 *Coupling shaft yoke*
1.500	2.562	2.000	3.812	—	BS			4-4-4211-1 *Coupling shaft yoke*
1.500	2.562	2.000	3.812	—	BS			4-4-4211-2 *Coupling shaft yoke. Attaching hdwr by OEM*
1.506-23 Involute Spline								
1.506	2.375	1.403	4.345	—	BS			4-4-6711-1
1.605-15 Involute Spline								
1.605	2.125	1.938	4.000	—	BS			4-4-5601-1
1.605	2.125	1.953	4.000	—	BS			4-4-6331-1
1.609-37 Involute Spline								
1.609	2.500	2.016	4.406	.240	BS	4-4-6851-1X	231872	4-4-6841-1•
1.625-10 Spline								
1.625	2.375	2.125	3.938	—	BS			4-4-1921-1
1.625	2.750	1.750	3.750	—	BS			4-4-5571-1•
1.750-10 Spline								
1.750	2.375	2.188	4.000	—	BS			4-4-2041-1
1.750	2.375	2.250	4.281	—	BS			4-4-5111-1•
1.750	2.500	1.915	4.115	—	BS			4-4-6791-2 *Attaching hardware by OEM*
1.750	2.500	1.938	4.125	—	BS			4-4-4781-1
1.750	2.500	1.938	4.125	—	BS			4-4-4781-2 *Attaching hardware by OEM*
1.750	2.500	2.000	4.125	—	BS			4-4-4171-1•
1.750	2.500	2.000	5.750	—	BS	4-4-7861-1X	—	4-4-7421-1 ⅄ *Flanged yoke w/eight 7-73-620 bolts*
1.750	2.500	2.250	4.188	—	BS			4-4-2511-1
1.750	2.500	2.260	4.290	—	BS			4-4-5251-1•
1.750	2.625	2.188	4.281	—	BS			4-4-3841-1•
1.750	2.625	2.234	4.672	—	BS	4-4-3581-1X	230909	4-4-1901-1 *.250 deep spline chamfer*
1.750	2.625	2.250	4.281	—	BS			4-4-2091-1
1.750	2.750	2.245	4.652	—	BS			4-4-3811-1
1.750	2.750	2.250	4.281	—	BS			4-4-1931-1
1.750	2.750	2.250	4.812	—	BS			4-4-5721-1•
1.751-27 Involute Spline								
1.751	2.500	2.094	4.125	—	BS			4-4-6141-1•
1.751	2.750	2.400	4.250	—	BS			4-4-5991-1 *.250 deep spline chamfer*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1550 SERIES (Con't) SR:E=5.250, ALL OTHERS:E-4.964 D-1.375 USE KIT 5-155X, 5-808X								
USES U-BOLT ASSY. 3-94-28X, STRAP ASSY. 3-70-38X								
1.755-13 Involute Spline								
1.755	2.375	2.250	4.031	—	BS			4-4-2931-1
1.755	2.375	2.250	4.063	—	BS	4-4-5241-1X■	4-68-58X	4-4-5231-1⅄
						Hub diameter not ground;	*Contains plug w/zerk fitting #4-68-58X*	
1.774-34 Spline								
1.774	2.500	2.260	4.700	—	BS	4-4-4111-1X	231206	4-4-4101-1
1.790-34 Involute Spline								
1.790	2.375	2.200	4.000	—	BS	4-4-6961-1X	232198	4-4-6951-1•
1.790	2.562	2.750	5.156	—	BS	4-4-4801-1X	231059	4-4-4791-1•
1.790	2.562	2.750	5.156	—	BS	4-4-4801-2X	231059	4-4-4791-2•
							Attaching hardware by OEM	
1.790	2.562	2.750	5.531	—	BS	4-4-7871-1X	231059	4-4-7431-1⅄
								Flanged end yoke
1.790	2.562	2.790	5.125	—	BS	4-4-3861-1X	231059	4-4-3851-1•
1.790	2.625	2.185	4.275	—	BS	4-4-5611-1X	232039	4-4-5551-1•
1.875-10 Spline								
1.875	2.750	2.375	4.406	—	UB			4-4-1941•
1.875	2.750	2.375	4.406	—	BS			4-4-1941-1•
1.922-14 Involute Spline								
1.922	2.375	2.203	4.641	—	BS			4-4-4811-1
1.962-10 Spline								
1.962	2.625	2.266	4.266	—	BS	4-4-4071-1X	230897	4-4-2431-1•
1.962	2.625	2.266	4.266	—	BS	4-4-4071-2X•	230897	4-4-2431-2•
							Attaching hardware by OEM	
1.962	2.750	2.812	5.000	—	BS			4-4-4191-1
1.962	2.750	2.812	5.000	—	BS			4-4-4771-2
							Attaching hardware by OEM	
1.962	2.750	2.812	5.000	—	BS			4-4-6781-2■
							Attaching hardware by OEM	
1.962	2.938	2.530	4.585	—	BS			4-4-5061-1
1.972-10 Spline								
1.972	2.750	2.375	4.422	—	BS			4-4-2381-1
1.998-38 Involute Spline								
1.998	2.750	1.984	4.156	—	UB			4-4-4611
1.998	2.750	1.984	4.156	—	BS			4-4-4611-1•
1.998	2.750	1.984	4.156	—	BS			4-4-4611-2
								Attaching hardware by OEM
1.998	2.750	2.125	4.047	—	BS			4-4-4491-1
1.998	2.750	2.125	4.141	—	BS			4-4-7341-1
1.998	2.750	2.125	7.031	—	BS			4-4-6101-1
								Flanged end yoke.
1.998	3.000	2.125	4.500	—	BS	4-4-6981-1X	232200	4-4-6971-1•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1550 SERIES (Con't) SR:E=5.250, ALL OTHERS:E-4.964 D-1.375 USE KIT 5-155X, 5-808X								
USES U-BOLT ASSY. 3-94-28X, STRAP ASSY. 3-70-38X								
2.000-10 Spline								
2.000	2.484	2.453	4.500	—	BS			4-4-2451-1
2.000	2.625	2.125	4.203	—	BS			4-4-2401-1
2.000	2.625	2.250	4.281	.384	BS			4-4-6211-1•
2.000	2.750	2.000	4.406	—	BS			4-4-2481-1
2.000	2.750	3.000	5.063	—	UB			4-4-2941•
2.000	3.031	3.000	5.125	—	BS	4-4-5171-1X•	231620	4-4-5161-1 ⅄
						Flanged end yoke w/notched slinger for magnetic pick-up.		
2.005-15 Involute Spline								
2.005	2.875	2.680	4.655	.620	BS			4-4-4421-1
2.008-31 Involute Spline								
2.008	2.375	1.406	3.188	—	BS			4-4-4371-1•
2.008	2.625	2.297	4.165	.380	BS	4-4-5941-1X	232189	4-4-5841-1 ⅄
2.008	2.750	3.386	6.078	—	BS			4-4-6641-1•
								Flanged end yoke.
2.008	3.000	2.766	4.938	.490	BS			4-4-5091-1
2.024-39 Involute Spline								
2.024	2.625	2.250	4.266	.250	BS	4-4-7551-1X	232167	4-4-6471-1 ⅄
2.024	2.625	2.255	4.281	—	BS	4-4-5691-1X	232039	4-4-5621-1•
2.024	3.000	2.297	4.281	.250	BS	4-4-7571-1X	232511	4-4-7561-1 ⅄
2.024	3.000	2.312	5.000	—	BS	4-4-6731-1X•	231359	4-4-5261-1
2.070-32 Involute Spline								
2.070	2.875	2.781	2.875	—	BS	4-4-7251-1X	4-68-94	4-4-7241-1•
2.114-32 Involute Spline								
2.114	3.000	2.250	4.312	.424	BS	4-4-7001-1X	232200	4-4-6991-1•
2.125-16 Involute Spline								
2.125	3.000	3.047	5.094	—	BS			4-4-4361-1
2.143-41 Involute Spline								
2.143	2.938	2.500	4.500	—	BS	4-4-5701-1X•	231028	4-4-5581-1•
2.250-10 Spline								
2.250	3.000	3.000	5.047	—	BS			4-4-3931-2
								Attaching hardware by OEM
2.250	3.500	3.000	5.125	—	BS			4-4-3501-1
2.364-18 Involute Spline								
2.364	3.000	2.765	4.777	—	BS			4-4-2531-1•
2.364-36 Involute Spline								
2.364	3.000	2.688	5.078	—	BS	4-4-7111-1X	232200	4-4-7011-1•
2.372-46 Involute Spline								
2.372	3.000	3.375	5.500	.787	BS	4-4-4451-1X	232189	4-4-4381-1 ⅄
2.372	3.020	3.734	6.193	.790	BS			4-4-7211-1M
								Flanged yoke; Flange has 8 threaded metric holes.

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1610 SERIES		**E-5.312**	**D-1.875**					**USE KIT 5-279X, 5-674X**
FOR HR STYLE USE STRAP KIT 5-70-28X								
1.618-18 Involute Spline								
1.618	2.200	2.160	4.125	—	BP			5-4-8041
1.625-10 Spline								
1.625	2.375	2.125	4.125	—	BP			5-4-2401
1.625	2.375	2.185	4.190	—	BP			5-4-9741• *Four slots across end of hub*
1.750-10 Spline								
1.750	2.188	2.250	4.125	.500	BP			5-4-1721 *Forge version does not have counterbore; Coupling shaft yoke*
1.750	2.188	2.250	4.125	.500	HR			5-4-1721-1 *Coupling shaft yoke*
1.750	2.375	2.250	4.906	.250	HR			5-4-6941-1
1.750	2.484	3.000	5.000	—	BP			5-4-871•
1.750	2.500	1.938	4.125	—	BP			5-4-5711
1.750	2.500	1.953	4.125	—	HR			5-4-7631-1•
1.750	2.500	2.188	4.875	—	HR			5-4-7031-1•
1.750	2.500	2.250	4.125	.250	BP			5-4-1051
1.750	2.500	2.250	4.720	—	HR			5-4-7581-1•
1.750	2.625	2.250	4.125	—	BP			5-4-781
1.750	2.625	2.250	4.750	.250	BP	5-4-5111X	230909	5-4-2081
1.750	2.625	2.250	4.750	.250	HR	5-4-5111-1X	230909	5-4-2081-1•
1.750	2.625	2.250	5.062	.250	BP			5-4-2521•
1.750	2.625	2.250	5.344	—	BP			5-4-4461
1.750	2.625	2.250	5.344	—	HR			5-4-4461-1•
1.750	2.625	2.250	5.344	—	BP			5-4-4571
1.750	2.625	2.250	6.000	.250	BP	5-4-4761X	230909	5-4-3901• *High angle yoke*
1.750	2.750	2.250	4.750	—	BP	5-4-3601X	230794	5-4-1931•
1.750	2.750	2.250	5.000	—	BP			5-4-3621
1.750	2.750	2.250	6.000	—	BP	5-4-4441X•	230794	5-4-3861■ *High angle yoke*
1.750-27 Involute Spline								
1.750	2.125	1.891	4.750	—	HR			5-4-6981-1•
1.774-34 Spline								
1.774	2.500	2.250	4.875	—	HR	5-4-5621-1X	231206	5-4-5571-1
1.774	2.500	2.250	5.438	.120	BP	5-4-5081X	231101	5-4-6261■
1.774	2.500	2.250	5.438	.120	HR			5-4-6261-1
1.774	2.500	2.250	6.062	.120	BP	5-4-4901X•	231101	5-4-6251■ *High angle yoke*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1610 SERIES (Continued)	**E-5.312**	**D-1.875**						**USE KIT 5-279X, 5-674X**
FOR HR STYLE USE STRAP KIT 5-70-28X								
1.790-34 Involute Spline								
1.790	2.188	2.250	4.125	.500	HR			5-4-7171-1 *Coupling shaft yoke*
1.790	2.375	2.203	4.125	—	HR	5-4-8571-1X	232198	5-4-8561-1 ⅄
1.790	2.500	2.250	5.438	—	HR			5-4-8911-1
1.790	2.562	2.750	5.312	—	BP	5-4-4841X	231059	5-4-4831•
1.790	2.562	2.750	5.312	—	HR	5-4-4841-1X	231059	5-4-4831-1•
1.790	2.562	2.750	5.312	—	HR	5-4-8061-1X	231059	5-4-7781-1•
1.790	2.567	2.830	5.310	—	BP	5-4-5231X•	231059	5-4-5221•
1.790	2.625	2.188	4.750	—	BP			5-4-7261•
1.790	2.625	2.188	4.750	—	HR	5-4-7301-1X	232039	5-4-7261-1■
1.790	2.625	2.188	5.880	—	HR			5-4-7941-1•
1.790	2.625	2.422	4.938	.250	HR	5-4-8501-1X	232166	5-4-8491-1•
1.790	2.625	2.438	4.938	—	BP			5-4-6341
1.790	2.625	2.438	6.188	—	BP			5-4-6351 *High angle yoke*
1.790	2.625	2.438	6.188	.250	BP	5-4-8441X	232166	5-4-8001• *High angle yoke*
1.875-10 Spline								
1.875	2.750	2.000	4.469	—	HR			5-4-7701-1■
1.875	2.750	2.375	5.000	—	BP			5-4-2501•
1.939-30 Involute Spline								
1.939	3.000	2.250	4.750	—	BP			5-4-4391
1.960-10 Spline								
1.960	2.438	3.000	5.500	—	BP			5-4-4721• *Coupling shaft yoke*
1.960	2.750	2.625	5.125	—	BP	5-4-5281X	98-1362	5-4-3681•
1.960-6 Spline								
1.960	2.750	3.000	5.000	—	BP	5-4-2031X	330287	5-4-1431•
1.962-10 Spline								
1.962	2.500	2.000	4.500	—	BP			5-4-2541•
1.962	2.625	2.250	4.719	.250	BP	5-4-5121X	230909	5-4-1641•
1.962	2.625	2.250	4.719	.250	HR	5-4-5121-1X•	230909	5-4-1641-1 ⅄
1.962	2.625	2.250	4.906	—	HR			5-4-7111-1•
1.962	2.625	2.250	5.062	.250	BP			5-4-3241
1.962	2.625	2.250	5.312	—	HR	5-4-6361-1X	230909	5-4-4471-1•
1.962	2.625	2.250	5.312	.250	HR	5-4-8901-1X	230909	5-4-8851-1 *Chamfered Counterbore*
1.962	2.625	2.250	6.000	.250	BP	5-4-4771X	230909	5-4-3911• *High angle yoke*
1.962	2.750	2.625	5.938	—	BP	5-4-5321X	98-1362	5-4-4221•
1.962	2.750	2.812	5.281	—	HR			5-4-7041-1
1.962	2.750	2.812	5.281	—	HR			5-4-8361-1
1.962	2.940	2.570	5.120	.310	HR			5-4-9511-1
1.962	3.000	2.250	4.750	—	BP			5-4-2531 *Chamfered Counterbore*
1.962	3.000	2.250	5.375	—	BP			5-4-4541
1.964-10 Spline								
1.964	2.500	2.000	5.219	—	BP			5-4-4551
1.964	2.750	2.812	5.000	—	BP			5-4-5091
1.989-30 Involute Spline								
1.989	3.000	2.688	6.000	.220	BP	5-4-7251X	231750	5-4-5721
1.989	3.000	2.688	6.000	.220	HR	5-4-8671-1X	232199	5-4-8661-1• *High angle yoke*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1610 SERIES (Continued)		**E-5.312**		**D-1.875**				**USE KIT 5-279X, 5-674X**
FOR HR STYLE USE STRAP KIT 5-70-28X								
1.998-38 Involute Spline								
1.998	2.750	1.969	4.156	—	BP			5-4-6481•
1.998	2.750	1.969	4.156	—	HR			5-4-6481-1
1.998	2.750	2.125	4.000	—	HR			5-4-6321-1
1.998	2.750	2.125	4.000	—	HR			5-4-8971-1
1.998	2.750	2.125	4.125	—	BP			5-4-6321
1.998	2.750	2.125	7.562	—	HR			5-4-7601-1 *Flanged end yoke.*
1.998	3.000	2.125	4.844	—	BP	5-4-7121X	231750	5-4-6131▪
1.998	3.000	2.125	4.844	—	BP	5-4-5861X	231347	5-4-6131▪
1.998	3.000	2.125	4.844	—	HR	5-4-8591-1X	232200	5-4-8581-1•
2.000-10 Spline								
2.000	2.750	2.000	4.688	—	BP			5-4-1831
2.000	2.750	2.000	4.688	—	HR			5-4-7061-1
2.000	2.750	2.469	5.781	.125	BP			5-4-4381•
2.000	2.750	3.000	5.188	—	BP			5-4-1661
2.000	2.750	3.000	5.469	—	HR			5-4-1661-1
2.000	2.938	2.562	5.188	—	BP	5-4-5131X	98-1361	5-4-1631•
2.000	2.938	3.000	5.000	—	BP			5-4-1221▪
2.000	2.938	3.000	5.000	—	BP			5-4-1521
2.000	2.938	3.000	5.625	—	BP			5-4-1391
2.000	3.031	3.000	5.609	—	HR	5-4-7101-1X•	231620	5-4-6541-1• *Flanged end yoke w/notched slinger for magnetic pick-up.*
2.008-31 Involute Spline								
2.008	—	2.031	4.953	—	HR			5-4-8961-1 *Hub diameter not ground.*
2.008	2.625	2.312	3.969	—	HR	5-4-7691-1X•	232189	5-4-7481-1•
2.024-39 Spline								
2.024	2.750	2.000	4.500	—	BP			5-4-5881
2.024	2.750	2.438	5.938	.120	BP	5-4-6961X	231599	5-4-5441• *High angle yoke*
2.024	2.750	2.438	6.250	.120	BP	5-4-6871X•	231599	5-4-5461 *High angle yoke*
2.024	2.750	2.438	6.250	.120	BP			5-4-5461 *High angle yoke*
2.024	2.750	2.453	5.125	—	BP	5-4-6951X	231599	5-4-5421•
2.024	3.000	2.312	4.875	—	BP	5-4-6431X	231102	5-4-6421•
2.024	3.000	2.312	4.875	—	HR	5-4-6431-1X	231102	5-4-6421-1•
2.024	3.000	2.312	4.875	—	HR	5-4-6441-1X	231359	5-4-6421-1•
2.024	3.000	2.312	5.531	.090	BP	5-4-6281X	231359	5-4-6271▪

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1610 SERIES (Continued)	**E-5.312**	**D-1.875**					**USE KIT 5-279X, 5-674X**	
FOR HR STYLE USE STRAP KIT 5-70-28X								
2.024-39 Spline (Continued)								
2.024	3.000	2.312	6.219	.090	BP	5-4-6291X	231359	5-4-6241 *High angle yoke*
2.024	3.000	2.312	6.219	.090	HR	5-4-6291-1X	231359	5-4-6241-1• *High angle yoke*
2.024-39 Involute Spline								
2.024	2.625	2.234	4.719	—	HR	5-4-8131-1X	232039	5-4-7981-1 ⅄
2.024	2.625	2.250	4.910	.250	HR	5-4-9441-1X	232167	5-4-9431-1•
2.024	2.625	2.250	5.312	—	BP	5-4-5991X	230909	5-4-5981■
2.024	2.625	2.250	5.312	.250	BP	5-4-8411X	232167	5-4-7971•
2.024	2.625	2.250	5.312	.250	HR	5-4-8411-1X	232167	5-4-7971-1•
2.024	2.625	2.250	6.000	—	BP	5-4-5971X	230909	5-4-5961 *High angle yoke*
2.024	2.625	2.250	6.000	.250	BP	5-4-8421X	232167	5-4-7991• *High angle yoke*
2.024	2.625	2.500	6.000	.250	BP	5-4-9271X•	232514	5-4-8301• *High angle yoke*
2.024	3.000	2.250	6.000	.280	HR	5-4-9311-1X	232200	5-4-9291-1• *High angle yoke*
2.024	3.000	2.281	4.875	.250	HR	5-4-9231-1X	232511	5-4-9221-1 ⅄
2.024	3.000	2.281	6.000	.250	HR	5-4-9241-1X	232511	5-4-8261-1• *High angle yoke*
2.024	3.000	2.281	6.000	.250	BP	5-4-9241X■	232511	5-4-8261 *High angle yoke*
2.024	3.000	2.500	5.594	.280	HR			5-4-9351-1
2.032-10 Spline								
2.032	2.750	2.000	4.500	.120	BP			5-4-4401
2.114-32 Involute Spline								
2.114	3.000	2.234	5.375	.424	HR	5-4-8611-1X	232200	5-4-8601-1
2.114	3.000	2.234	6.000	.424	HR	5-4-8691-1X	232200	5-4-8681-1 *High angle yoke*
2.114	3.000	2.250	5.375	.424	BP	5-4-7221X	231750	5-4-5751
2.114	3.000	2.250	6.000	.424	BP	5-4-7181X	231750	5-4-5731
2.143-41 Involute Spline								
2.143	2.938	2.500	5.250	—	HR	5-4-7311-1X	231028	5-4-7271-1•
2.143	2.938	2.500	5.250	—	HR	5-4-9111-1X	232604	5-4-7271-1•
2.143	2.938	2.500	6.000	—	BP	5-4-9121X•	232604	5-4-7561•
2.143	2.938	2.500	6.000	—	BP	5-4-7571X	231028	5-4-7561•
2.143	2.938	2.500	6.000	—	HR	5-4-9121-1X•	232604	5-4-7561-1•
2.143	2.938	2.500	6.000	—	HR	5-4-7571-1X•	231028	5-4-7561-1•
2.143	2.938	3.000	6.500	.380	HR	5-4-9131-1X•	232609	5-4-7551-1•
2.143	2.939	2.500	5.660	—	HR	5-4-9451-1X	232604	5-4-9421-1 ⅄
2.143	3.000	2.188	4.680	.310	HR	5002873	5002871	5002872 ⅄
2.149-16 Spline								
2.149	2.938	3.000	5.660	.380	BP	5-4-6591-1X	231028	5-4-6581-1 ⅄
2.149	2.938	3.000	6.250	.380	BP	5-4-5161X	231028	5-4-5031• *High angle yoke*
2.149	2.938	3.000	6.250	.380	HR	5-4-5161-1X	231028	5-4-5031-1•
2.149	2.938	3.000	6.500	.380	BP	5-4-5511X	231028	5-4-5501• *High angle yoke*
2.149	2.938	3.000	6.500	.380	BP	5-4-8711X	232367	5-4-5501• *High angle yoke*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1610 SERIES (Continued)		**E-5.312**		**D-1.875**				**USE KIT 5-279X, 5-674X**
FOR HR STYLE USE STRAP KIT 5-70-28X								
2.178-43 Involute Spline								
2.178	3.531	2.031	5.406	.157	BP			5-4-9141
2.178	3.531	2.031	5.406	.157	HR			5-4-9141-1
2.178	3.547	2.047	5.219	.157	HR			5-4-8461-1•
2.195-34 Involute Spline								
2.195	3.543	1.889	4.441	—	HR			5008270 ⅄ *OEM only*
2.225-6 Spline								
2.225	3.000	3.250	5.719	—	BP	5-4-4751X	829W	5-4-4741 ⅄
2.250-10 Spline								
2.250	3.000	3.000	5.625	.250	BP	5-4-6891X	230921	5-4-3141•
2.250	3.500	3.000	5.750	—	BP			5-4-4961
2.250	3.500	3.000	5.750	—	HR			5-4-4961-1■
2.250	3.750	3.000	5.750	—	HR	5-4-7391-1X	231616	5-4-7381-1•
2.260-6 Spline								
2.260	3.250	2.250	4.938	—	BP			5-4-1891
2.260	3.250	2.250	4.938	—	HR	5-4-8211-1X	232042-6	5-4-1891-1•
2.274-44 Involute Spline								
2.274	2.938	2.328	4.844	—	HR	5-4-9101-1X	232604	5-4-8021-1•
2.274	2.938	2.328	4.844	—	HR	5-4-8031-1X	231022	5-4-8021-1•
2.274	2.938	2.500	5.000	—	BP	5-4-6381X•	231022	5-4-6371•
2.274	2.938	2.500	5.000	—	HR	5-4-6381-1X	231022	5-4-6371-1•
2.274	2.938	2.500	5.000	—	HR	5-4-8431-1X	232168	5-4-8321-1 ⅄
2.274	3.000	2.500	5.000	.236	BP	5-4-9261-1X•	232511	5-4-8311-1•
2.320-36 Involute Spline								
2.320	3.000	3.040	5.420	—	HR	5004358 ⅄ *OEM only; Assy includes o-ring 232849, welch plug 6-68-134 & snap ring*		5004159
2.343-45 Involute Spline								
2.343	3.750	3.000	5.750	—	HR	5-4-7651-1X•	231616	5-4-7641-1•
2.364-36 Involute Spline								
2.364	3.000	2.688	5.156	—	BP	5-4-7201X	231750	5-4-5631■
2.364	3.000	2.688	5.156	—	BP	5-4-7211X•	231755	5-4-7191 ⅄
2.364	3.000	2.688	5.156	—	HR	5-4-8631-1X	232200	5-4-8621-1•
2.364	3.000	2.688	5.156	—	HR	5-4-8651-1X	231755	5-4-8641-1•
2.364	3.000	2.703	6.000	—	BP	5-4-7231X	231750	5-4-5741•
2.372-46 Involute Spline								
2.372	2.938	3.375	6.234	.500	HR			5-4-6521-1 *Flanged end yoke*
2.372	3.000	3.000	4.547	.120	HR	5-4-7441-1X	500166-46	5-4-7431-1 ⅄

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1610 SERIES (Continued) E-5.312 D-1.875								**USE KIT 5-279X, 5-674X**
FOR HR STYLE USE STRAP KIT 5-70-28X								
2.372-46 Involute Spline (Contined)								
2.372	3.000	3.165	5.890	—	HR			5-4-9191-1M *Metric bolt holes*
2.372	3.000	3.391	5.740	.500	HR			5-4-6161-1•
2.372	3.000	3.500	5.891	.500	HR	5-4-6151-1X•	500166-46	5-4-6141-1•
2.372	3.000	3.550	5.890	—	HR	5-4-9631-1X	232638	5-4-9621-1⅄
2.374-46 Spline								
2.374	3.250	2.312	4.940	—	HR	5-4-9541-1X	232746	5-4-9581-1⅄
2.374	3.250	2.891	4.547	—	HR	5-4-7361-1X•	231615	5-4-7351-1⅄
2.387-18 Involute Spline								
2.387	3.000	2.891	5.203	—	HR			5-4-5851-1
2.387	3.000	3.094	4.562	.120	HR	5-4-6101-1X•	500166-46	5-4-5831-1•
2.390-46 Involute Spline								
2.390	3.250	2.312	4.938	.140	HR	5-4-7341-1X	231803	5-4-7331-1•
2.390	3.500	3.391	6.125	—	BP			5-4-4861
2.390	3.500	3.391	6.125	—	HR			5-4-4861-1
2.422-18 Involute Spline								
2.422	3.250	2.500	5.260	—	HR			5-4-9571-1
2.422	3.375	3.000	6.125	.380	HR	5-4-5491-1X•	231013	5-4-5361-1•
2.500-10 Spline								
2.500	3.250	3.000	5.688	—	HR	5-4-8351-1X	231179	5-4-8341-1•
2.500	3.750	3.000	6.125	—	BP			5-4-4971 *Hub machined for speedometer gear*
2.547-49 Involute Spline								
2.547	4.000	2.750	5.500	.560	HR			5-4-7951-1•
2.588-40 Involute Spline								
2.588	3.625	2.640	5.280	—	HR	5004899⅄	5001780	5004898⅄ *OEM only*
2.625-20 Involute Spline								
2.625	3.750	2.750	5.062	—	HR			5-4-6531-1• *Hub machined for speedometer gear*
1650 SERIES E-5.594 D-1.625								**USE KIT 5-165X**
USES CAP & BOLT ASSY. 5-70-18X								
1.750-10 Spline								
1.750	2.625	2.250	4.375	.250	CB	5-4-4161X•	230909	5-4-2141• *Chamfered Counterbore*
2.000-10 Spline								
2.000	2.625	2.125	4.375	—	CB			5-4-2331
2.000-15 Involute Spline								
2.000	3.000	3.250	5.406	.105	CB			5-4-4701■
2.359-18 Involute Spline								
2.359	2.875	2.688	5.281	.460	CB			5-4-5821•
2.359	3.000	2.781	5.219	.432	CB			5-4-2341•
1710 SERIES E-6.094 (6.190 FOR HR STYLE) D-1.938								**USE KIT 5-280X, & 5-675X**
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
1.625-10 Spline								
1.625	2.375	2.125	4.750	—	HR			6-4-7751-1•
1.750-10 Spline								
1.750	2.625	2.250	4.500	.250	BP	6-4-5581X■	230909	6-4-2081• *Chamfered Counterbore*
1.750	2.625	2.250	4.500	.250	HR	6-4-5581-1X•	230909	6-4-2081-1⅄ *Chamfered Counterbore*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1710 SERIES (Continued) E-6.094 (6.190 FOR HR STYLE) D-1.938 USE KIT 5-280X, & 5-675X								
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
1.750-10 Spline (Continued)								
1.750	2.625	2.250	5.250	.250	BP	6-4-4301X	230909	6-4-3391• *Chamfered Counterbore*
1.750	2.625	2.250	6.125	.250	BP	6-4-4861X	230909	6-4-4141■ *Chamfered Counterbore; High angle yoke*
1.750	2.750	2.250	4.875	.060	BP			6-4-2381
1.774-34 Spline								
1.774	2.500	2.250	4.875	.090	BP	6-4-5131X	231101	6-4-6331
1.774	2.500	2.250	4.875	.090	HR	6-4-5131-1X	231101	6-4-6331-1■
1.774	2.500	2.250	5.969	.090	BP	6-4-5111X	231101	6-4-6321 *High angle yoke*
1.774	2.500	2.250	5.969	.090	HR			6-4-6321-1 *High angle yoke*
1.775-16 Involute Spline								
1.775	2.375	2.000	4.750	.190	BP			6-4-4271
1.790-34 Involute Spline								
1.790	2.500	2.250	4.875	.090	HR			6-4-9021-1
1.790	2.562	2.750	5.594	—	HR	6-4-5041-1X	231059	6-4-5031-1■
1.790	2.562	2.750	7.188	—	BP	6-4-5041X	231059	6-4-5031• *High angle yoke*
1.790	2.625	2.188	5.438	—	HR	6-4-7581-1X	232039	6-4-7571-1
1.790	2.625	2.438	5.438	.250	BP			6-4-6481
1.790	2.625	2.438	5.438	.250	BP	6-4-8511X	232166	6-4-8081
1.790	2.625	2.438	5.438	.250	HR	6-4-8511-1X	232166	6-4-8081-1■
1.790	2.625	2.438	6.312	.250	BP			6-4-6451 *High angle yoke*
1.790	2.625	2.438	6.312	.250	HR			6-4-6451-1 *High angle yoke*
1.790	2.625	2.438	6.312	.250	BP	6-4-8521X	232166	6-4-8001 *High angle yoke*
1.790	2.625	2.438	6.312	.250	HR	6-4-8521-1X	232166	6-4-8001-1⅄ *High angle yoke*
1.939-30 Involute Spline								
1.939	3.000	2.250	4.562	—	BP			6-4-4371
1.960-10 Spline								
1.960	2.625	2.000	5.000	—	BP			6-4-2391
1.960	2.750	2.625	5.250	—	BP	6-4-4361X	231541	6-4-3221•
1.960	2.750	2.625	6.500	—	BP	6-4-4481X	98-1362	6-4-4131■ *High angle yoke*
1.960	2.812	3.000	5.000	—	BP			6-4-1981 *Coupling shaft yoke*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1710 SERIES (Continued) E-6.094 (6.190 FOR HR STYLE) D-1.938 USE KIT 5-280X, & 5-675X								
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
1.960-10 Spline (Continued)								
1.960	2.812	3.000	5.000	.500	HR			6-4-1981-1 *Coupling shaft yoke*
1.960	2.938	2.219	4.500	.094	BP			6-4-2061
1.962-10 Spline								
1.962	2.500	2.000	6.000	—	BP			6-4-4261 *High angle yoke*
1.962	2.625	2.250	4.500	.250	BP	6-4-4731X■	230998	6-4-4721• *Chamfered Counterbore*
1.962	2.625	2.250	4.500	.250	HR	6-4-4731-1X	230998	6-4-4721-1• *Chamfered counterbore*
1.962	2.625	2.250	5.250	—	BP	6-4-5151X	230909	6-4-5141•
1.962	2.625	2.250	6.125	.250	BP	6-4-4851X	230909	6-4-4151• *High angle yoke*
1.962	2.625	2.250	6.125	.250	HR	6-4-4851-1X•	230909	6-4-4151-1• *High angle yoke*
1.962	2.750	2.812	5.156	—	BP			6-4-3831
1.962	2.750	2.812	5.156	—	HR			6-4-3831-1
1.964-10 Spline								
1.964	2.625	2.250	4.500	.250	BP			6-4-2211 *Chamfered counterbore*
1.964	2.750	2.750	5.250	—	BP			6-4-3901
1.964	3.000	2.250	4.562	—	BP			6-4-3291
1.989-30 Involute Spline								
1.989	3.000	2.700	6.280	.220	BP	6-4-7231X	231750	6-4-5781• *High angle yoke*
1.989	3.000	2.703	6.281	.220	HR	6-4-8741-1X	232199	6-4-8731-1 *High angle yoke*
1.998-38 Involute Spline								
1.998	2.750	2.125	5.250	—	BP			6-4-7301
1.998	2.750	2.125	5.250	—	HR			6-4-7301-1
1.998	2.810	3.000	5.000	.500	BP			6-4-7141 *Coupling shaft yoke*
1.998	2.810	3.000	5.000	.500	HR			6-4-7141-1 *Coupling shaft yoke*
1.998	3.000	2.125	4.840	.425	HR	6-4-9961-1X	232948	6-4-9951-1 ⅄
1.998	3.000	2.125	4.844	—	BP	6-4-7291X	231751	6-4-6201•
1.998	3.000	2.125	4.844	—	HR	6-4-8661-1X	232200	6-4-8651-1 ⅄
2.000-10 Spline								
2.000	2.750	2.000	5.000	—	BP			6-4-2371
2.000	2.750	2.562	5.188	—	BP	6-4-4391X	230794	6-4-3271 ⅄
2.000	2.750	3.000	5.250	—	BP			6-4-2361
2.000	2.750	3.000	5.250	—	BS			6-4-2361-1■
2.000	2.938	2.562	5.188	—	BP	6-4-4291X	98-1361	6-4-3241
2.000	2.938	2.562	5.188	—	BP	6-4-4741X	231015	6-4-3241
2.000	2.938	3.000	5.625	—	BP			6-4-2191
2.000	2.938	3.000	5.625	—	HR	6-4-7741-1X•	98-1361	6-4-2191-1•
2.000	3.250	3.000	5.625	—	BP			6-4-2001
2.000-15 Involute Spline								
2.000	3.250	2.375	4.250	—	BP			6-4-3131 *Tapered spline.*
2.000	3.250	2.688	4.562	.690	BP			6-4-5291
2.002-15 Spline								
2.002	2.625	2.375	4.250	—	BP			6-4-4871

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1710 SERIES (Continued) E-6.094 (6.190 FOR HR STYLE) D-1.938 USE KIT 5-280X, & 5-675X								
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.005-15 Involute Spline								
2.005	2.875	2.500	5.375	.250	BP			6-4-3001
2.024-39 Spline								
2.024	2.750	2.000	5.000	.120	BP	6-4-8331X	232042-2	6-4-5851
2.024	2.750	2.000	5.000	.120	HR	6-4-8331-1X	232042-2	6-4-5851-1
2.024	2.750	2.000	5.875	.120	BP	6-4-8361X	232042-2	6-4-6571▪ *High angle yoke*
2.024	2.750	2.000	5.875	.120	HR	6-4-8361-1X	232042-2	6-4-6571-1• *High angle yoke*
2.024	2.750	2.438	4.812	.090	BP	6-4-6941X	231599	6-4-5541•
2.024	2.750	2.438	5.250	.090	BP	6-4-6951X	231599	6-4-5521
2.024	2.750	2.438	5.250	.090	HR	6-4-6951-1X	231599	6-4-5521-1
2.024	2.750	2.438	6.500	.090	BP	6-4-6871X	231599	6-4-5501
2.024	2.750	2.438	6.500	.090	HR	6-4-6871-1X	231599	6-4-5501-1• *High angle yoke*
2.024	3.000	2.312	5.156	.090	HR	6-4-7631-1X	231102	6-4-7621-1
2.024	3.000	2.312	5.156	.090	HR	6-4-8601-1X▪	232182	6-4-7621-1
2.024	3.000	2.312	5.156	.090	HR	6-4-7641-1X	231359	6-4-7621-1
2.024	3.000	2.312	6.250	.090	BP	6-4-8571X	232182	6-4-6371 *High angle yoke*
2.024	3.000	2.312	6.250	.090	BP	6-4-6381X	231102	6-4-6371 *High angle yoke*
2.024	3.000	2.312	6.250	.090	BP	6-4-6391X	231359	6-4-6371 *High angle yoke*
2.024	3.000	2.312	6.250	.090	HR	6-4-8571-1X	232182	6-4-6371-1 *High angle yoke*
2.024	3.000	2.312	6.250	.090	HR	6-4-6391-1X	231359	6-4-6371-1 *High angle yoke*
2.024	3.000	2.327	5.156	.090	BP	6-4-6421X	231359	6-4-6401
2.024	3.000	2.327	5.156	.090	BP	6-4-6411X	231102	6-4-6401
2.024	3.000	2.327	5.156	.090	HR	6-4-6421-1X	231866	6-4-6401-1▪
2.024	3.000	2.438	5.188	.120	BP	6-4-5101X	231102	6-4-4901▪
2.024	3.000	2.438	6.281	.120	BP			6-4-4971 *High angle yoke*
2.024	3.000	2.500	5.438	.280	HR			6-4-9411-1
2.024-39 Involute Spline								
2.024	2.625	2.250	5.250	.250	BP	6-4-6001X	230909	6-4-5991 *Chamfered counterbore*
2.024	2.625	2.250	5.250	.250	BP	6-4-8531X	232167	6-4-7991
2.024	2.625	2.250	5.250	.250	HR	6-4-8231-1X	232039	6-4-7991-1•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1710 SERIES (Continued) E-6.094 (6.190 FOR HR STYLE) D-1.938 USE KIT 5-280X, & 5-675X								
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.024-39 Involute Spline (Continued)								
2.024	2.625	2.250	5.250	.250	HR	6-4-8531-1X	232167	6-4-7991-1•
2.024	2.625	2.250	6.125	.250	BP	6-4-6021X	230909	6-4-6011
							High angle yoke; Chamfered counterbore	
2.024	2.625	2.250	6.125	.250	HR	6-4-6021-1X	230909	6-4-6011-1 ⅄
							High angle yoke; Chamfered counterbore	
2.024	2.625	2.250	6.125	.250	BP	6-4-8541X	232167	6-4-7981
								High angle yoke
2.024	2.625	2.250	6.125	.250	HR	6-4-8541-1X	232167	6-4-7981-1•
								High angle yoke
2.024	2.625	2.500	5.250	.250	BP	6-4-9041X	232514	6-4-8441
2.024	2.625	2.500	5.250	.250	HR	6-4-9041-1X	232514	6-4-8441-1
2.024	2.625	2.500	6.125	.250	BP	6-4-9001X	232514	6-4-8431
2.024	2.625	2.500	6.125	.250	HR	6-4-9001-1X	232514	6-4-8431-1
2.024	3.000	2.250	4.656	.280	HR	6-4-9441-1X•	232199	6-4-9421-1•
2.024	3.000	2.250	4.656	.280	HR	6-4-9431-1X	232200	6-4-9421-1•
2.024	3.000	2.250	6.000	.280	HR	6-4-9301-1X	232200	6-4-9291-1 ⅄
								High angle yoke
2.024	3.000	2.281	5.250	.250	BP	6-4-9031X	232511	6-4-8421
2.024	3.000	2.281	5.250	.250	HR	6-4-9031-1X	232511	6-4-8421-1
2.024	3.000	2.281	6.125	.250	BP	6-4-8991X	232511	6-4-8411
								High angle yoke
2.024	3.000	2.281	6.125	.250	HR	6-4-8991-1X	232511	6-4-8411-1
2.024	3.000	2.500	6.120	.280	HR			6-4-9281-1
2.032-10 Spline								
2.032	2.750	2.000	5.000	.120	BP			6-4-3791
2.032	2.750	2.391	5.375	.500	BP			6-4-2431
2.114-32 Involute Spline								
2.114	3.000	2.250	4.562	.424	BP	6-4-7221X	231750	6-4-5811■
2.114	3.000	2.250	4.562	.424	HR	6-4-8681-1X	232200	6-4-8671-1
2.114	3.000	2.250	6.062	.424	HR	6-4-8761-1X	232200	6-4-8751-1•
								High angle yoke
2.114	3.000	2.250	6.250	.424	BP	6-4-7171X	231750	6-4-5791
								High angle yoke
2.126-33 Involute Spline								
2.126	3.000	2.500	4.562	—	BP			6-4-5471
2.143-41 Involute Spline								
2.143	2.938	2.500	5.190	—	BP	6-4-9171X	232604	6-4-7311•
2.143	2.938	2.500	5.190	—	HR	6-4-7321-1X	231028	6-4-7311-1
2.143	2.938	2.500	5.190	—	HR	6-4-9171-1X	232604	6-4-7311-1
2.143	2.938	2.500	6.125	—	BP	6-4-9181X	232604	6-4-7551
								High angle yoke
2.143	2.938	2.500	6.125	—	BP	6-4-7561X	231028	6-4-7551
								High angle yoke
2.143	2.938	2.500	6.125	—	HR	6-4-9181-1X	232604	6-4-7551-1 ⅄
								High angle yoke
2.143	2.938	2.500	6.125	—	HR	6-4-7561-1X	231028	6-4-7551-1 ⅄
								High angle yoke
2.143	2.938	3.000	6.620	.380	BP	5008446	232168	6-4-10301 ⅄
						131449K = 5008446 yoke assy & nut# 128049; Spicer axles only; High angle yoke		
2.143	2.938	3.000	6.625	.380	BP	6-4-7651X	231028	6-4-7541
								High angle yoke
2.143	2.938	3.000	6.625	.380	BP	6-4-9191X	232609	6-4-7541
								High angle yoke

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1710 SERIES (Continued) E-6.094 (6.190 FOR HR STYLE) D-1.938 USE KIT 5-280X, & 5-675X								
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.143-41 Involute Spline (Continued)								
2.143	2.938	3.000	6.625	.380	HR	6-4-7651-1X	231028	6-4-7541-1 *High angle yoke*
2.143	2.938	3.000	6.625	.380	HR	6-4-9191-1X	232609	6-4-7541-1 *High angle yoke*
2.143	3.000	2.166	5.380	.310	HR	5002877	5002871	5002876 ⅄ *High angle yoke*
2.149-16 Spline								
2.149	2.938	2.500	5.188	—	BP	6-4-5061X	231022	6-4-4961•
2.149	2.938	3.000	5.500	.380	BP	6-4-4171X	231028	6-4-2181■
2.149	2.938	3.000	5.500	.380	HR	6-4-4171-1X	231028	6-4-2181-1•
2.149	2.938	3.000	6.625	.380	BP	6-4-5481X	231028	6-4-4591 *High angle yoke*
2.149	2.938	3.000	6.625	.380	BP	6-4-9841X	232367	6-4-4591 *High angle yoke*
2.149	2.938	3.000	6.625	.380	HR	6-4-9841-1X•	232367	6-4-4591-1• *High angle yoke*
2.149	3.000	2.500	4.940	.380	BP			6-4-3491
2.170-34 Involute Spline								
2.170	3.543	1.889	4.441	—	HR			5007193 ⅄ *OEM only*
2.178-43 Involute Spline								
2.178	3.539	2.047	4.875	.157	HR			6-4-8561-1
2.178	3.539	2.047	4.875	.157	SR			6-4-9221
2.178	3.539	2.047	4.875	.157	HR			6-4-9221-1
2.225-6 Spline								
2.225	2.875	3.250	5.312	—	BP	6-4-2601X•	98-1361	6-4-2331•
2.225	3.000	3.250	5.312	—	BP	6-4-3041X	829-W	6-4-3031
2.225	3.000	3.250	5.312	—	BP	6-4-3461X	330499	6-4-3031
2.225	3.000	3.250	5.438	—	HR	6-4-3041-1X	829-W	6-4-3031-1•
2.250-10 Spline								
2.250	3.000	2.875	5.250	—	BP			6-4-2511
2.250	3.000	3.000	5.250	—	BP			6-4-3871
2.250	3.000	3.000	6.062	.250	BP	6-4-4411X	230921	6-4-1991
2.250	3.000	3.000	6.062	.250	HR	6-4-4411-1X•	230921	6-4-1991-1•
2.250	3.000	3.000	7.188	.250	BP	6-4-6891X	230921	6-4-4121• *High angle yoke*
2.250	3.125	2.250	5.250	—	BP			6-4-2441
2.250	3.250	2.250	5.250	—	BP			6-4-1971
2.250	3.250	3.000	5.250	.250	BP	6-4-4681X	230746	6-4-2501•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1710 SERIES (Continued) E-6.094 (6.190 FOR HR STYLE) D-1.938 USE KIT 5-280X, & 5-675X								
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.250-10 Spline (Continued)								
2.250	3.500	3.000	5.250	—	BP	6-4-6771X	230674	6-4-2141
2.250	3.500	3.000	5.250	—	HR	6-4-6901-1X	231616	6-4-6861-1•
2.250	3.750	3.000	5.250	—	HR	6-4-7381-1X	231616	6-4-7371-1 ⅄
2.260-6 Spline								
2.260	3.250	2.250	5.300	—	HR	6-4-8291-1X	232042-6	6-4-3501-1 ⅄
2.274-44 Involute Spline								
2.274	2.938	2.359	5.031	—	BP	6-4-7971X	231022	6-4-7961•
2.274	2.938	2.359	5.031	—	BP	6-4-9161X•	232604	6-4-7961•
2.274	2.938	2.359	5.031	—	HR	6-4-7971-1X	231022	6-4-7961-1
2.274	2.938	2.359	5.031	—	HR	6-4-9161-1X	232604	6-4-7961-1
2.274	2.938	2.500	5.188	—	BP	6-4-6041X	231022	6-4-8461
2.274	2.938	2.500	5.188	—	BP	6-4-8551X	232168	6-4-8461
2.274	2.938	2.500	5.188	—	HR	6-4-8551-1X	232168	6-4-8461-1
2.274	2.938	2.500	5.188	—	HR	6-4-6041-1X	231022	6-4-8461-1
2.274	3.000	2.500	5.190	.236	BP	6-4-8981X•	232511	6-4-8451
2.274	3.000	2.500	5.190	.236	HR	6-4-8981-1X	232511	6-4-8451-1
2.343-45 Involute Spline								
2.343	3.750	3.000	5.250	—	BP	6-4-7271X•	231616	6-4-7251 ⅄
2.343	3.750	3.000	5.250	—	HR	6-4-7271-1X	231616	6-4-7251-1•
2.350-16 Spline								
2.350	3.312	2.750	4.938	—	BP	6-4-5071X	230746	6-4-4601 *Coupling shaft yoke*
2.350	3.750	2.750	5.188	—	BP			6-4-5341 *Hub machined for speedometer gear*
2.351-16 Spline								
2.351	3.750	2.750	5.188	—	BP			6-4-4531 *Hub machined for speedometer gear*
2.360-18 Involute Spline								
2.360	3.500	3.375	6.094	—	BP			6-4-5271•
2.364-18 Involute Spline								
2.364	3.000	2.750	5.281	.440	BP			6-4-5831
2.364	3.500	3.375	5.750	—	BP			6-4-4561
2.364	3.500	3.375	5.750	—	HR			6-4-4561-1
2.364	3.500	3.375	6.062	—	BP			6-4-6671•
2.364	3.750	2.344	5.094	—	BP			6-4-6971 *Hub machined for speedometer gear*
2.364	3.750	2.344	5.094	—	BP			6-4-6971-1• *Hub machined for speedometer gear*
2.364-23 Involute Spline								
2.364	3.378	1.785	5.312	—	HR			6-4-9521-1
2.364-36 Involute Spline								
2.364	3.000	2.688	5.438	—	BP	6-4-7191X	231750	6-4-5711■
2.364	3.000	2.688	5.438	—	BP	6-4-7211X	231755	6-4-7201•
2.364	3.000	2.688	5.438	—	HR	6-4-8701-1X	232200	6-4-8691-1
2.364	3.000	2.688	5.438	—	HR	6-4-8721-1X	232199	6-4-8711-1 ⅄
2.364	3.000	2.688	6.500	—	BP	6-4-7241X	231750	6-4-5801 *High angle yoke*
2.364	3.000	2.703	6.500	—	HR	6-4-8781-1X	232200	6-4-8771-1 ⅄ *High angle yoke*
2.364	3.500	2.500	5.234	.306	HR	6-4-8801-1X	232201	6-4-8791-1•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1710 SERIES (Continued) E-6.094 (6.190 FOR HR STYLE) D-1.938 USE KIT 5-280X, & 5-675X								
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.372-46 Involute Spline								
2.372	3.000	3.484	5.734	.490	HR	6-4-7731-1X	231305	6-4-6991-1•
2.372	3.000	3.500	5.750	—	HR	6-4-9321-1XM•	232646	6-4-9311-1M•
						Metric yoke; Part is proprietary to OEM		
2.372	3.000	3.875	6.344	—	HR	6-4-9791-1X	232638	6-4-9781-1⅄
2.372	3.000	4.000	6.344	—	HR	6-4-6241-1X•	500166-46	6-4-6211-1⅄
2.372	3.250	3.220	6.625	.550	HR			6-4-9971-1M
								Metric flanged yoke
2.372	3.125	3.385	6.800	.500	HR			6-4-6231-1
								Flanged end yoke.
2.373-36 Involute Spline								
2.373	3.000	1.844	4.250	.300	BP			6-4-5741•
2.373	3.000	2.094	4.250	.310	HR			6-4-10011-1
2.373	3.000	2.094	4.250	.310	HR			6-4-8831-1•
2.373	3.375	2.500	5.094	—	HR			6-4-7081-1•
2.374-46 Spline								
2.374	3.250	2.625	5.688	—	BP	6-4-5461X	231179	6-4-5451■
2.374	3.250	2.625	5.688	—	HR	6-4-5461-1X	231179	6-4-5451-1•
2.374	3.250	2.875	5.938	.140	BP	6-4-5961X	231179	6-4-5931•
2.374	3.250	2.875	5.938	.140	BP	6-4-6961X	231615	6-4-5931•
2.374	3.250	2.875	5.938	.140	HR	6-4-6961-1X	231615	6-4-5931-1⅄
2.374	3.250	2.875	5.938	.140	HR	6-4-5961-1X■	231179	6-4-5931-1⅄
2.374	3.250	2.891	6.938	.140	BP	6-4-7851X	231615	6-4-7831⅄
								High angle yoke
2.374	3.250	2.891	6.938	.140	HR	6-4-7851-1X	231615	6-4-7831-1⅄
								High angle yoke
2.374	3.500	2.406	5.156	—	BP	6-4-8341X	232042-10	6-4-5841■
2.374	3.500	2.406	5.156	—	HR	6-4-8341-1X	232042-10	6-4-5841-1•
2.374	3.752	2.422	4.938	—	BP	6-4-7881X	231527	6-4-6601
						Hub machined for speedometer gear; Assy inc. mech. speedo gear		
2.374	3.752	2.422	4.938	—	HR	6-4-7881-1X	231527	6-4-6601-1
						Hub machined for speedometer gear; Assy inc. mech. speedo gear		
2.374	3.752	2.422	4.938	—	HR	6-4-7891-1X	231528	6-4-6601-1
						Hub machined for speedometer gear; Assy inc. elec. speedo gear		
2.375-16 Spline								
2.375	3.125	2.812	5.312	.690	BP			6-4-3081•
2.390-46 Spline								
2.390	3.250	2.312	5.125	.140	HR	6-4-9531-1X	232746	6-4-9911-1⅄
2.390	3.250	2.328	5.391	.140	BP	6-4-7181X	231803	6-4-7161⅄
2.390	3.250	2.328	5.391	.140	HR	6-4-7181-1X	231803	6-4-7161-1

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1710 SERIES (Continued) E-6.094 (6.190 FOR HR STYLE) D-1.938 USE KIT 5-280X, & 5-675X								
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.390-46 Spline (Continued)								
2.390	3.250	2.328	5.391	.140	HR	5003553	5003552	6-4-7161-1
2.390	3.250	2.344	6.500	.140	BP	6-4-7771X	231803	6-4-7761• *High angle yoke*
2.390	3.250	2.344	6.500	.140	HR	6-4-7771-1X	231803	6-4-7761-1⅄ *High angle yoke*
2.390-46 Involute Spline								
2.390	2.875	2.750	4.938	.500	HR			6-4-7481-1 *Coupling shaft yoke*
2.390	3.250	2.875	5.938	.140	HR			6-4-9131-1
2.390	3.375	3.188	6.000	.580	BP	6-4-7531X	231013	6-4-7511
2.390	3.375	3.188	6.000	.580	HR	6-4-7531-1X	231013	6-4-7511-1•
2.390	3.375	3.188	6.000	.580	HR	6-4-9201-1X	232610	6-4-7511-1•
2.390	3.500	3.375	5.750	—	BP			6-4-4771
2.390	3.500	3.375	5.750	—	HR			6-4-4771-1
2.422-18 Involute Spline								
2.422	3.375	3.000	5.250	—	BP			6-4-3161
2.422	3.375	3.000	5.812	.380	BP	6-4-4751X	231013	6-4-4581
2.422	3.375	3.000	5.812	.380	HR	6-4-4751-1X	231013	6-4-4581-1•
2.423-18 Involute Spline								
2.423	3.146	2.047	5.125	—	HR			6-4-7491-1•
2.450-47 Involute Spline								
2.450	3.900	2.428	5.190	.750	BP			6-4-8471•
2.500-10 Spline								
2.500	3.250	3.000	4.875	—	BP	6-4-6761X	231179	6-4-2251
2.500	3.250	3.000	5.000	—	HR	6-4-6761-1X	231179	6-4-2251-1⅄
2.500	3.250	3.000	5.750	—	BP	6-4-9151X•	231179	6-4-9141⅄
2.500	3.500	2.406	5.156	—	BP	6-4-8321X•	232042-10	6-4-4421
2.500	3.500	2.406	5.156	—	HR	6-4-8321-1X	232042-10	6-4-4421-1■
2.500	3.500	2.406	5.156	—	HR	6-4-8351-1X	232042-11	6-4-4421-1■
2.500	3.500	3.000	5.750	—	BP			6-4-4781
2.500	3.750	3.000	5.625	—	BP	6-4-6921X	231616 *Hub machined for speedometer gear*	6-4-6611
2.500	3.750	3.000	5.625	—	HR	6-4-6921-1X	231616 *Hub machined for speedometer gear*	6-4-6611-1
2.500-24 Involute Spline								
2.500	3.000	2.422	4.672	—	HR			6-4-8841-1•
2.544-49 Involute Spline								
2.544	3.755	3.000	5.625	—	BP	6-4-7041X	231616 *Hub machined for speedometer gear*	6-4-7051
2.544	3.755	3.000	5.625	—	HR	6-4-7041-1X	231616 *Hub machined for speedometer gear*	6-4-7051-1■
2.544	3.819	2.125	5.570	.120	BP	5008452 *131442K = 5008452 yoke assy & nut# 131095; Spicer axles only*	5008437	6-4-10291⅄
2.544	3.819	2.125	5.570	.120	HR	5008453 *131437K = 5008453 yoke assy & nut# 131095; Spicer axles only*	5008437	6-4-10291-1⅄
2.544	3.819	2.125	6.260	.120	BP	5008449 *131439K = 5008449 yoke assy & nut# 131095; Spicer axles only*	5008437	6-4-10311⅄
2.544	3.819	2.125	6.260	.120	HR	5008450 *131438K = 5008450 yoke assy & nut# 131095; Spicer axles only*	5008437	6-4-10311-1⅄
2.544	3.819	2.677	6.050	.240	BP	5008438 *131530K = 5008438 yoke assy & nut# 131095; Spicer axles only*	5008437	5005579⅄
2.544	3.819	2.677	6.050	.240	HR	5008439 *131519K = 5008439 yoke assy & nut# 131095; Spicer axles only*	5008437	5005580•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1710 SERIES (Continued) E-6.094 (6.190 FOR HR STYLE) D-1.938 USE KIT 5-280X, & 5-675X								
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.544-49 Involute Spline (Continued)								
2.544	4.000	2.750	5.188	.180	BP			6-4-7691•
								Hub machined for speedometer gear
2.544	4.000	2.750	5.188	.180	HR			6-4-7691-1
								Hub machined for speedometer gear
2.588-40 Involute Spline								
2.588	4.000	3.510	6.340	—	HR	6-4-9751-1XM•	232760	6-4-9741-1M⅄
2.588	4.000	3.640	6.340	—	HR	6-4-9571-1XM•	232759	6-4-9561-1M⅄
2.631-25 Involute Spline								
2.631	3.625	2.562	5.250	1.000	BP			6-4-4921
2.631	3.625	3.000	5.250	—	BP			6-4-3021
2.635-20 Involute Spline								
2.635	3.750	2.750	5.188	—	BP	6-4-7071X	231745	6-4-5351■
								Hub Dia. 3.000 if used on Spicer 1241 Aux. Trans.; Hub machined for speedometer gear
2.635	3.750	2.750	5.188	—	HR	6-4-7071-1X	231745	6-4-5351-1■
								Hub Dia. 3.000 if used on Spicer 1241 Aux. Trans.; Hub machined for speedometer gear
2.750-10 Spline								
2.750	3.500	3.000	5.750	—	BP	6-4-5251X	230674	6-4-4551
2.750	3.500	3.000	5.750	—	HR			6-4-4551-1
2.750	3.750	3.000	5.750	—	BP	6-4-6841X	230902	6-4-6631•
2.750	3.750	3.000	5.750	—	HR	6-4-6841-1X	230902	6-4-6631-1⅄
2.750	3.750	3.000	5.750	—	BP	6-4-6931X	231616	6-4-6821⅄
2.750	3.750	3.000	5.750	—	HR	6-4-6931-1X	231616	6-4-6821-1
2.750	3.812	3.000	5.750	—	HR			6-4-7661-1•
								Hub diameter not ground.
2.750	4.000	2.938	5.312	—	BP			6-4-4651
								Hub machined for speedometer gear
2.750	4.000	2.938	5.312	—	HR			6-4-4651-1
								Hub machined for speedometer gear
2.781-21 Involute Spline								
2.781	3.500	3.000	5.812	—	BP			6-4-3671
2.784-55 Involute Spline								
2.784	4.725	2.047	5.000	—	BP			6-4-8851
								Metric spline-.120”
2.784	4.725	2.047	5.000	—	HR			6-4-8851-1
								Metric spline-.120”
2.794-54 Involute Spline								
2.794	—	2.750	5.625	—	BP			6-4-9231
2.794	—	2.750	5.625	—	HR			6-4-9231-1
2.922-22 Involute Spline								
2.922	3.500	2.625	5.250	—	BP			6-4-5201
2.922	3.750	2.641	5.000	—	HR			6-4-8821-1•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1710 SERIES (Continued) E-6.094 (6.190 FOR HR STYLE) D-1.938 USE KIT 5-280X, & 5-675X								
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
3.003-23 Involute Spline								
3.003	4.000	3.000	4.844	—	BP	6-4-9701X	232193	6-4-9691 ⅄
3.003	4.000	3.031	4.844	—	BP			6-4-3141
1760 SERIES E-7.000 (7.094 FOR HR STYLE) D-1.938 USE KIT 5-407X, 5-677X								
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
1.939-30 Involute Spline								
1.939	3.000	2.250	5.250	—	BP			6.3-4-431
1.964-10 Spline								
1.964	2.625	2.250	5.625	.250	BP	6.3-4-221X	230998	6.3-4-111 *Chamfered counterbore*
1.998-38 Involute Spline								
1.998	3.000	2.125	4.844	—	HR	6.3-4-1501-1X•	232200	6.3-4-1491-1 ⅄
2.000-10 Spline								
2.000	2.938	2.562	5.375	—	BP	6.3-4-181X	98-1361	6.3-4-71•
2.024-39 Spline								
2.024	3.000	2.312	5.188	.125	BP	6.3-4-541X	231047	6.3-4-531
2.024	3.000	2.312	5.188	.125	BP	6.3-4-1141-1X•	231866	6.3-4-531-1
2.024	3.000	2.312	5.188	.125	HR	6.3-4-1341-1X•	232028	6.3-4-531-1
2.024	3.000	2.312	5.188	.125	HR	6.3-4-541-1X	231047	6.3-4-531-1
2.024	3.000	2.438	5.188	.120	BP	6.3-4-191X•	231047	6.3-4-81•
2.024-39 Involute Spline								
2.024	3.000	2.250	5.625	.280	HR	6.3-4-1711-1X	232199	6.3-4-1701-1•
2.032-10 Spline								
2.032	2.750	2.000	5.000	—	BP	6.3-4-1261X	232042-2	6.3-4-421•
2.114-32 Involute Spline								
2.114	3.000	2.250	5.000	.424	HR	6.3-4-1521-1X	232200	6.3-4-1511-1
2.143-41 Involute Spline								
2.143	2.938	2.500	5.250	—	BP	6.3-4-1071X	231028	6.3-4-1061•
2.143	2.938	2.500	5.250	—	HR	6.3-4-1631-1X•	232604	6.3-4-1061-1■
2.143	2.938	2.500	5.250	—	HR	6.3-4-1071-1X•	231028	6.3-4-1061-1■
2.143	2.938	3.000	5.812	—	BP	6.3-4-1641X•	232609	6.3-4-1171•
2.149-16 Spline								
2.149	2.938	2.500	5.250	—	BP	6.3-4-231X	231022	6.3-4-121•
2.149	2.938	3.000	5.812	.380	BP	6.3-4-251X■	231028	6.3-4-141•
2.149	2.938	3.000	5.812	.380	HR	6.3-4-251-1X•	231028	6.3-4-141-1 ⅄
2.170-34 Involute Spline								
2.170	3.543	1.889	4.598	—	HR			5007597 ⅄ *OEM only*
2.178-43 Involute Spline								
2.178	3.539	2.050	5.500	.157	HR			6.3-4-1591-1
2.225-6 Spline								
2.225	3.000	3.250	6.000	—	BP	6.3-4-171X	829W	6.3-4-51 ⅄
2.225	3.000	3.250	6.000	—	HR	6.3-4-171-1X	829-W	6.3-4-51-1 ⅄
2.250-10 Spline								
2.250	3.000	3.000	5.844	.250	BP	6.3-4-731X	230921	6.3-4-91■
2.250	3.000	3.000	5.844	.250	HR	6.3-4-731-1X	230921	6.3-4-91-1 ⅄
2.250	3.750	3.000	5.625	—	HR	6.3-4-1101-1X•	231616	6.3-4-1091-1•
2.274-44 Involute Spline								
2.274	2.938	2.328	5.094	—	BP	6.3-4-1621X•	232604	6.3-4-1321 ⅄
2.274	2.938	2.328	5.094	—	BP	6.3-4-1331X	231022	6.3-4-1321 ⅄
2.274	2.938	2.328	5.094	—	HR	6.3-4-1331-1X	231022	6.3-4-1321-1•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1760 SERIES (Cont'd) E-7.000 (7.094 FOR HR STYLE) D-1.938							**USE KIT 5-407X, 5-677X**	
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.274-44 Involute Spline (Continued)								
2.274	2.938	2.328	5.094	—	HR	6.3-4-1621-1X	232604	6.3-4-1321-1•
2.274	2.938	2.500	5.250	—	BP	6.3-4-331X	231022	6.3-4-1421
2.274	2.938	2.500	5.250	—	BP	6.3-4-1481X	232168	6.3-4-1421
2.274	2.938	2.500	5.250	—	HR	6.3-4-331-1X	231022	6.3-4-1421-1
2.274	2.938	2.500	5.250	—	HR	6.3-4-1481-1X	232168	6.3-4-1421-1
2.274	3.000	2.500	5.250	.236	BP	6.3-4-5221X	232511	6.3-4-1411
2.274	3.000	2.500	5.250	.236	HR	6.3-4-5221-1X	232511	6.3-4-1411-1•
2.343-45 Involute Spline								
2.343	3.750	3.000	5.656	—	HR	6.3-4-901-1X•	231616	6.3-4-841-1•
2.350-16 Spline								
2.350	2.875	2.750	5.500	—	BP			6.3-4-161 *Coupling shaft yoke*
2.350	2.875	2.750	5.500	—	HR			6.3-4-161-1 *Coupling shaft yoke*
2.364-18 Involute Spline								
2.364	3.500	3.375	6.125	—	BP			6.3-4-271
2.364	3.500	3.375	6.125	—	HR			6.3-4-271-1
2.364	3.750	2.328	5.500	—	HR			6.3-4-751-1• *Hub machined for speedometer gear*
2.364-36 Involute Spline								
2.364	3.000	2.688	5.438	—	HR	6.3-4-1541-1X	232200	6.3-4-1531-1 ⅄
2.364	3.000	2.688	5.438	—	HR	6.3-4-1561-1X	232199	6.3-4-1551-1■
2.364	3.000	2.688	5.438	—	BP	6.3-4-1021X	231750	6.3-4-441•
2.364	3.000	2.688	5.438	—	BP	6.3-4-851X	231755	6.3-4-831 ⅄
2.364	3.500	2.485	5.230	.306	HR	6.3-4-1611-1X	232201	6.3-4-1601-1•
2.374-46 Spline								
2.374	3.250	2.625	5.438	—	BP	6.3-4-211X	231179	6.3-4-101•
2.374	3.250	2.625	5.438	—	HR	6.3-4-211-1X	231179	6.3-4-101-1•
2.374	3.250	2.875	5.625	.140	BP	6.3-4-861X	231615	6.3-4-291•
2.374	3.250	2.875	5.625	.140	BP	6.3-4-301X	231179	6.3-4-291•
2.374	3.250	2.875	5.625	.140	HR	6.3-4-301-1X	231179	6.3-4-291-1•
2.374	3.250	2.875	5.625	.140	HR	6.3-4-861-1X	231615	6.3-4-291-1•
2.374	3.500	2.406	5.375	—	BP	6.3-4-1391X	232042-10	6.3-4-391
2.374	3.500	2.406	5.375	—	HR	6.3-4-1391-1X	232042-10	6.3-4-391-1•
2.374	3.750	2.422	5.406	—	BP	6.3-4-1281X		6.3-4-641 *Assy includes electronic speedometer #231528*
2.374	3.750	2.422	5.406	—	HR	6.3-4-1281-1X		6.3-4-641-1 *Assy includes electronic speedometer #231528*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1760 SERIES (Cont'd) E-7.000 (7.094 FOR HR STYLE) D-1.938							**USE KIT 5-407X, 5-677X**	
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.374-46 Spline (Continued)								
2.374	3.750	2.422	5.406	—	HR	6.3-4-1271-1X		6.3-4-641-1
						Assy includes mechanical speedometer drive gear #231527		
2.390-46 Involute Spline								
2.390	2.875	2.750	5.500	—	HR			6.3-4-821-1
								Coupling shaft yoke
2.390	3.250	2.328	5.062	.140	BP	6.3-4-1041X	231803	6.3-4-1031•
2.390	3.250	2.328	5.062	.140	HR	6.3-4-1041-1X	231803	6.3-4-1031-1
2.390	3.250	2.328	5.062	.140	HR	5003555	5003552	6.3-4-1031-1
2.390	3.375	3.188	6.000	.580	BP	6.3-4-1161X	231013	6.3-4-1151•
2.390	3.375	3.188	6.000	.580	BP	6.3-4-1651X•	232610	6.3-4-1151•
2.390	3.375	3.188	6.000	.580	HR	6.3-4-1161-1X	231013	6.3-4-1151-1•
2.390	3.375	3.188	6.000	.580	HR	6.3-4-1651-1X	232610	6.3-4-1151-1•
2.390	3.500	3.375	6.000	—	BP			6.3-4-381
2.390	3.500	3.375	6.000	—	HR			6.3-4-381-1
2.422-18 Involute Spline								
2.422	3.375	3.000	6.000	.380	BP	6.3-4-241X	231013	6.3-4-131•
2.422	3.375	3.000	6.000	.380	HR	6.3-4-241-1X•	231013	6.3-4-131-1 ⅄
2.500-10 Spline								
2.500	3.500	2.406	5.406	—	BP	6.3-4-1401X	232042-11	6.3-4-151■
2.500	3.500	2.406	5.406	—	HR	6.3-4-1401-1X	232042-11	6.3-4-151-1•
2.500	3.750	3.000	6.000	—	BP	6.3-4-781X	231616	6.3-4-651
							Hub machined for speedometer gear	
2.500	3.750	3.000	6.031	—	HR	6.3-4-781-1X	231616	6.3-4-651-1
							Hub machined for speedometer gear	
2.503-19 Involute Spline								
2.503	3.344	3.000	5.938	—	BP			6.3-4-521
2.544-49 Involute Spline								
2.544	3.750	3.000	6.031	—	BP	6.3-4-771X	231616	6.3-4-811•
							Hub machined for speedometer gear	
2.544	3.750	3.000	6.031	—	HR	6.3-4-771-1X	231616	6.3-4-811-1 ⅄
							Hub machined for speedometer gear	
2.544	3.818	2.141	5.200	.120	BP	5008454	5008437	6.3-4-1861 ⅄
						131441K = 5008454 yoke assy & nut# 131095; Spicer axles only		
2.544	3.818	2.141	5.200	.120	HR	5008455	5008437	6.3-4-1861-1 ⅄
						131440K = 5008455 yoke assy & nut# 131095; Spicer axles only		
2.544	3.819	2.677	5.750	.240	BP	5008440	5008437	5005581 ⅄
						131518K = 5008440 yoke assy & nut# 131095; Spicer axles only		
2.544	3.819	2.677	6.050	.240	HR	5008441	5008437	5005582 ⅄
						131482K = 5008441 yoke assy & nut# 131095; Spicer axles only		
2.544	4.000	2.750	5.562	.180	BP			6.3-4-1251•
2.544	4.000	2.750	5.562	.180	HR			6.3-4-1251-1
2.635-20 Involute Spline								
2.635	3.750	2.750	5.562	—	BP	6.3-4-871X	231745	6.3-4-41•
							Hub machined for speedometer gear	
2.635	3.750	2.750	5.562	—	HR	6.3-4-871-1X	231745	6.3-4-41-1■
							Hub machined for speedometer gear	
2.750-10 Spline								
2.750	3.750	3.000	5.969	—	BP	6.3-4-721X	230902	6.3-4-661 ⅄
2.750	3.750	3.000	5.969	—	HR	6.3-4-721-1X	230902	6.3-4-661-1■
2.750	3.750	3.000	5.969	—	BP	6.3-4-791X	231616	6.3-4-711
2.750	3.750	3.000	5.969	—	HR	6.3-4-791-1X	231616	6.3-4-711-1
2.750	4.000	2.938	6.000	—	BP			6.3-4-61
							Hub machined for speedometer gear	

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1760 SERIES (Cont'd) E-7.000 (7.094 FOR HR STYLE) D-1.938								**USE KIT 5-407X, 5-677X**
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.750-10 Spline (Continued)								
2.750	4.000	2.938	6.000	—	HR			6.3-4-61-1
								Hub machined for speedometer gear
2.794-54 Involute Spline								
2.794	—	2.750	5.625	—	BP			6.3-4-1681
								Hub diameter not ground.
2.794	—	2.750	5.625	—	HR			6.3-4-1681-1
								Hub diameter not ground.
2.794	3.750	3.000	5.970	—	HR			6.3-4-1051-1•
2.798-21 Involute Spline								
2.798	3.531	2.078	4.844	.080	HR			6.3-4-1191-1
3.045-48 Involute Spline								
3.045	4.250	1.955	4.882	—	HR			5005679⅄
								OEM only
1800 SERIES E-6.594 D-2.312								**USE KIT 5-124X**
2.002-15 Involute Spline								
2.002	3.250	2.703	4.938	.687	BP			6.5-4-2961
1810 SERIES E-7.547 (7.643 FOR HR STYLE) D-1.938								**USE KIT 5-281X, 5-676X**
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
1.939-30 Involute Spline								
1.939	3.000	2.250	5.375	—	BP			6.5-4-2051
1.964-10 Spline								
1.964	2.625	2.250	5.625	.250	BP	6.5-4-2351X	230998	6.5-4-2001
								Chamfered counterbore
2.000-10 Spline								
2.000	2.938	2.562	5.375	—	BP	6.5-4-2341X	98-1361	6.5-4-1921•
2.005-15 Involute Spline								
2.005	2.875	2.500	5.250	.250	BP			6.5-4-2911
2.005	3.250	2.375	5.281	—	BP			6.5-4-2821
								Tapered spline.
2.024-39 Spline								
2.024	2.750	2.000	5.188	.125	BP	6.5-4-4281X	232042-2	6.5-4-3261
2.024	2.750	2.000	5.188	.125	HR	6.5-4-4281-1X	232042-2	6.5-4-3261-1
2.024	2.750	2.438	5.531	.090	BP	6.5-4-3571X	231599	6.5-4-2781•
2.024	2.750	2.438	5.625	.090	HR	6.5-4-3571-1X•	231599	6.5-4-2781-1⅄
2.024	3.000	2.312	5.190	.120	BP	6.5-4-3381X	231047	6.5-4-3371
2.024	3.000	2.312	5.190	.120	HR	6.5-4-4191-1X•	232028	6.5-4-3371-1
2.024	3.000	2.312	5.190	.120	HR	6.5-4-3381-1X	231047	6.5-4-3371-1
2.024	3.000	2.312	5.750	.120	HR	6.5-4-3881-1X	231047	6.5-4-3861-1⅄

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1810 SERIES (Cont'd) E-7.547 (7.643 FOR HR STYLE) D-1.938							**USE KIT 5-281X, 5-676X**	
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.024-39 Spline (Continued)								
2.024	3.000	2.320	5.188	.090	HR	6.5-4-3851-1X	231047	6.5-4-3841-1 ⅄
2.024	3.000	2.438	5.188	.120	BP	6.5-4-2491X	231047	6.5-4-2471•
2.024-39 Involute Spline								
2.024	3.000	2.250	5.000	.280	HR	6.5-4-4661-1X	232199	6.5-4-4651-1•
2.031-10 Spline								
2.031	2.750	2.000	5.250	.125	BP	6.5-4-4251X	232042-2	6.5-4-2261■
2.114-32 Involute Spline								
2.114	3.000	2.250	5.000	.424	HR	6.5-4-4461-1X	232200	6.5-4-4451-1 ⅄
2.143-41 Involute Spline								
2.143	2.938	2.500	5.250	—	BP	6.5-4-4601X■	232604	6.5-4-3681•
2.143	2.938	2.500	5.250	—	BP	6.5-4-3691X	231028	6.5-4-3681•
2.143	2.938	2.500	5.250	—	HR	6.5-4-4601-1X•	232604	6.5-4-3681-1 ⅄
2.143	2.938	2.500	5.250	—	HR	6.5-4-3691-1X•	231028	6.5-4-3681-1 ⅄
2.143	2.938	3.000	5.812	.380	BP	6.5-4-4621X•	232609	6.5-4-3931
2.143	2.938	3.000	5.812	.380	BP			6.5-4-3931
2.143	2.938	3.000	6.620	.380	HR	5008447	232168	6-4-10301-1 ⅄
						131450K = 5008447 yoke assy & nut# 131095; Spicer axles only		
2.149-16 Spline								
2.149	2.938	2.500	5.219	—	BP	6.5-4-2451X	231022	6.5-4-2441■
2.149	2.938	3.000	5.812	.380	BP	6.5-4-2401X	231028	6.5-4-2291•
2.149	2.938	3.000	5.812	.380	HR	6.5-4-2401-1X•	231028	6.5-4-2291-1 ⅄
2.225-6 Spline								
2.225	3.000	3.250	6.000	—	BP	6.5-4-2831X	330499	6.5-4-1971
2.225	3.000	3.250	6.000	—	BP	6.5-4-2271X	829-W	6.5-4-1971
2.225	3.000	3.250	6.000	—	HR			6.5-4-1971-1
2.250-10 Spline								
2.250	2.875	3.000	5.875	.312	BP			6.5-4-2131
2.250	3.000	3.000	5.844	.250	BP	6.5-4-2551X	230921	6.5-4-1911■
2.250	3.125	2.250	5.375	—	HR	6.5-4-4221-1X•	232042-3	6.5-4-2141-1 ⅄
2.250	3.312	2.250	5.375	—	HR	6.5-4-4241-1X	232042-6	6.5-4-4231-1•
2.250	3.500	3.000	5.844	—	BP			6.5-4-2021
2.274-44 Involute Spline								
2.274	2.938	2.344	5.090	—	HR	6.5-4-4591-1X	232604	6.5-4-4081-1
2.274	2.938	2.344	5.090	—	HR	6.5-4-4091-1X	231022	6.5-4-4081-1
2.274	2.938	2.500	5.250	—	BP	6.5-4-4351X	232168	6.5-4-4321
2.274	2.938	2.500	5.250	—	BP	6.5-4-3281X	231022	6.5-4-4321
2.274	2.938	2.500	5.250	—	HR	6.5-4-4351-1X	232168	6.5-4-4321-1
2.274	2.938	2.500	5.250	—	HR	6.5-4-3281-1X	231022	6.5-4-4321-1
2.274	3.000	2.500	5.250	.236	BP	6.5-4-4571X	232511	6.5-4-4311
2.274	3.000	2.500	5.250	.236	HR	6.5-4-4571-1X	232511	6.5-4-4311-1
2.350-16 Spline								
2.350	2.875	2.750	5.500	—	BP	6.5-4-2531X	230746	6.5-4-1891
								Coupling shaft yoke
2.350	2.875	2.750	5.500	—	HR			6.5-4-1891-1
								Coupling shaft yoke
2.350	3.750	2.750	5.562	—	BP			6.5-4-3011
								Hub machined for speedometer gear
2.364-18 Involute Spline								
2.364	3.500	3.375	6.125	—	BP			6.5-4-2581
2.364	3.500	3.375	6.125	—	HR			6.5-4-2581-1
2.364	3.750	2.344	5.625	—	HR			6.5-4-4211-1
								Hub machined for speedometer gear

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1810 SERIES (Cont'd) E-7.547 (7.643 FOR HR STYLE) D-1.938							**USE KIT 5-281X, 5-676X**	
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.364-36 Involute Spline								
2.364	3.000	2.688	5.438	—	BP	6.5-4-3651X	231750	6.5-4-3161■
2.364	3.000	2.688	5.438	—	BP	6.5-4-3641X	231755	6.5-4-3631⅄
2.364	3.000	2.688	5.438	—	HR	6.5-4-4421-1X	232200	6.5-4-4411-1•
2.364	3.000	2.688	5.438	—	HR	6.5-4-4441-1X	232199	6.5-4-4431-1⅄
2.364	3.500	2.500	5.230	.300	HR	6.5-4-4481-1X	232201	6.5-4-4471-1•
2.374-46 Spline								
2.374	3.250	2.625	5.438	—	BP	6.5-4-2711X	231179	6.5-4-2701
2.374	3.250	2.625	5.438	—	HR	6.5-4-2711-1X	231179	6.5-4-2701-1•
2.374	3.250	2.875	5.688	.140	BP	6.5-4-3581X	231615	6.5-4-3201•
2.374	3.250	2.875	5.688	.140	BP	6.5-4-3221X	231179	6.5-4-3201•
2.374	3.250	2.875	5.688	.140	HR	6.5-4-3581-1X	231615	6.5-4-3201-1■
2.374	3.250	2.875	5.688	.140	HR	6.5-4-3221-1X	231179	6.5-4-3201-1■
2.374	3.500	2.406	5.406	—	BP	6.5-4-4271X	232042-10	6.5-4-3251
2.374	3.500	2.406	5.406	—	HR	6.5-4-4271-1X	232042-10	6.5-4-3251-1
2.374	3.750	2.406	5.219	—	BP	6.5-4-4001X•		6.5-4-3441
						Assy includes electronic speedometer gear #231528		
2.374	3.750	2.406	5.219	—	BP	6.5-4-4011X	231528	6.5-4-3441
						Assy iIncludes mechanical speedometer drive gear #231527		
2.374	3.750	2.406	5.219	—	HR	6.5-4-4011-1X		6.5-4-3441-1⅄
						Assy includes electronic speedometer gear #231528		
2.374	3.750	2.406	5.219	—	HR	6.5-4-4001-1X		6.5-4-3441-1⅄
						Assy iIncludes mechanical speedometer drive gear #231527		
2.390-46 Involute Spline								
2.390	2.875	2.750	5.500	—	HR			6.5-4-3591-1
								Coupling shaft yoke
2.390	3.250	2.312	5.156	.140	BP	6.5-4-3731X	231803	6.5-4-3721⅄
2.390	3.250	2.312	5.156	.140	HR	5003556	5003552	6.5-4-3721-1
2.390	3.250	2.312	5.156	.140	HR	6.5-4-4511-1X	211831X	6.5-4-3721-1
2.390	3.250	2.312	5.156	.140	HR	6.5-4-3731-1X	231803	6.5-4-3721-1
2.390	3.250	2.312	5.156	.140	HR	6.5-4-4721-1X	232747	6.5-4-3721-1
2.390	3.375	3.188	6.000	.580	BP	6.5-4-4611X	232610	6.5-4-3911
2.390	3.375	3.188	6.000	.580	BP	6.5-4-3921X	231013	6.5-4-3911
2.390	3.375	3.188	6.000	.580	HR	6.5-4-4611-1X	232610	6.5-4-3911-1
2.390	3.375	3.188	6.000	.580	HR	6.5-4-3921-1X	231013	6.5-4-3911-1
2.390	3.500	3.375	6.156	—	BP			6.5-4-2541
2.390	3.500	3.375	6.156	—	HR			6.5-4-2541-1
2.422-18 Involute Spline								
2.422	3.375	3.000	5.812	.380	BP	6.5-4-2361X	231013	6.5-4-1991
2.422	3.375	3.000	5.812	.380	HR	6.5-4-2361-1X	231013	6.5-4-1991-1•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1810 SERIES (Cont'd) E-7.547 (7.643 FOR HR STYLE) D-1.938							**USE KIT 5-281X, 5-676X**	
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.450-47 Involute Spline								
2.450	3.625	2.500	5.312	.750	BP			6.5-4-2921
2.500-10 Spline								
2.500	3.250	3.000	5.781	—	BP	6.5-4-3711X	231179	6.5-4-2561
2.500	3.250	3.000	5.781	—	HR	6.5-4-3711-1X	231179	6.5-4-2561-1
2.500	3.500	2.406	5.406	—	BP	6.5-4-4291X	232042-11	6.5-4-2101■
2.500	3.500	2.406	5.406	—	HR	6.5-4-4261-1X	232042-11	6.5-4-2101-1
2.500	3.500	2.406	5.406	—	HR	6.5-4-4291-1X	232042-11	6.5-4-2101-1
2.500	3.500	3.000	5.781	—	BP			6.5-4-2151■
2.500	3.750	3.000	5.875	—	BP	6.5-4-3551X	231616	6.5-4-3451•
						Hub machined for speedometer gear		
2.500	3.750	3.000	5.875	—	HR	6.5-4-3551-1X	231616	6.5-4-3451-1
						Hub machined for speedometer gear		
2.544-49 Involute Spline								
2.544	3.750	3.000	5.875	—	BP	6.5-4-3621X•	231616	6.5-4-3611⅄
						Hub machined for speedometer gear		
2.544	3.750	3.000	5.875	—	HR	6.5-4-3621-1X	231616	6.5-4-3611-1•
2.544	3.818	2.141	5.740	.120	BP	5008456	5008437	6.5-4-5091⅄
						131444K = 5008456 yoke assy & nut# 131095; Spicer axles only		
2.544	3.818	2.141	5.740	.120	HR	5008457	5008437	6.5-4-5091-1•
						131443K = 5008457 yoke assy & nut# 131095; Spicer axles only		
2.544	3.819	2.677	5.740	—	BP	5008442	5008437	6.5-4-5101⅄
						131448K = 5008442 yoke assy & nut# 131095; Spicer axles only		
2.544	3.820	2.692	5.740	.240	HR	5008443	5008437	6.5-4-5101-1•
						131447K = 5008443 yoke assy & nut# 131095; Spicer axles only		
2.544	4.000	2.750	5.562	.180	HR			6.5-4-3821-1
2.560-20 Involute Spline								
2.560	3.500	3.344	6.125	—	BP			6.5-4-3361
2.560	3.500	3.344	6.125	—	HR			6.5-4-3361-1
2.631-25 Involute Spline								
2.631	3.625	3.000	5.781	1.000	BP			6.5-4-2181
2.635-20 Involute Spline								
2.635	3.750	2.750	5.562	—	BP			6.5-4-2011
						Hub machined for speedometer gear		
2.635	3.750	2.750	5.562	—	BP	6.5-4-3541X	231745	6.5-4-3021
						Hub Dia. 3.000 if used on Spicer 1241 Aux. Trans.; Hub machined for speedometer gear		
2.635	3.750	2.750	5.562	—	HR	6.5-4-3541-1X	231745	6.5-4-3021-1■
						Hub Dia. 3.000 if used on Spicer 1241 Aux. Trans.; Hub machined for speedometer gear		
2.635	3.750	3.312	6.062	.560	BP	6.5-4-2601X•	230888	6.5-4-1941•
2.635	4.000	3.281	6.062	.560	BP	6.5-4-4551X	230888	6.5-4-4541⅄
2.750-10 Spline								
2.750	3.500	3.000	6.062	—	BP	6.5-4-2931X	230674	6.5-4-1901
2.750	3.750	3.000	6.062	—	BP	6.5-4-3501X	230902	6.5-4-3461•
2.750	3.750	3.000	6.062	—	HR	6.5-4-3501-1X	230902	6.5-4-3461-1•
2.750	3.750	3.000	6.062	.120	BP	6.5-4-3561X	231616	6.5-4-3491■
2.750	3.750	3.000	6.062	.120	HR	6.5-4-3561-1X	231616	6.5-4-3491-1
2.750	3.875	3.000	6.062	—	HR			6.5-4-3801-1
								Hub diameter not ground.
2.750	4.000	2.938	6.000	—	BP			6.5-4-2171
						Hub machined for speedometer gear		
2.750	4.000	2.938	6.000	—	HR			6.5-4-2171-1
						Hub machined for speedometer gear		

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
1810 SERIES (Cont'd) E-7.547 (7.643 FOR HR STYLE) D-1.938							**USE KIT 5-281X, 5-676X**	
FOR HR STYLE USE STRAP KIT 6.5-70-18X								
2.794-54 Involute Spline								
2.794	—	2.750	5.625	—	BP			6.5-4-4631 *Hub diameter not ground.*
2.794	—	2.750	5.625	—	HR			6.5-4-4631-1 *Hub diameter not ground.*
2.795-55 Involute Spline								
2.795	4.719	2.047	5.000	.150	HR			6.5-4-4521-1•
2.798-21 Involute Spline								
2.798	3.531	2.094	4.844	.080	HR			6.5-4-3941-1
2.922-22 Involute Spline								
2.922	3.875	2.625	5.375	—	BP			6.5-4-3081
3.003-23 Involute Spline								
3.003	4.000	3.000	5.750	.310	BP	6.5-4-4401X	232193	6.5-4-2621
3.003	4.000	3.000	5.750	.310	HR	6.5-4-4401-1X	232193	6.5-4-2621-1⅄
3.045-48 Involute Spline								
3.045	4.250	1.955	4.882	—	HR			5005680
3.100-60 Involute Spline								
3.100	4.000	2.500	5.312	—	BP			6.5-4-2681
1880 SERIES		**E-8.094**	**D-2.188**		**USE KIT 5-308X**			
2.625-20 Involute Spline								
2.625	4.500	3.910	7.470	1.160	BP			8-4-791•
2.794-54 Involute Spline								
2.794	3.625	2.315	5.250	.120	BP	8-4-1351X	232746	8-4-1341⅄
3.582-59 Involute Spline								
3.582	4.725	4.406	8.000	—	BP	8-4-1381X•	233038	8-4-1321⅄
3.582	4.725	4.411	8.000	—	BP	5002688•	233038	5002687⅄
1950 SERIES		**E-10.047**	**D-3.062**		**USE KIT 5-192X**			
USES CAP & BOLT ASSY. 9-70-18X								
3.500-27 Involute Spline								
3.500	5.000	4.219	7.844	—	CB	9-4-311X•	230922	9-4-301⅄

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
4C SERIES		**WB STYLE P-4.250**		**T-1.438**	**KEYWAY .375**			**USE KIT 5-4143X**
1.450-27 Involute Spline								
1.450	2.250	1.235	2.695	—	WB			4C-4-11 *Tapped holes in yoke ears*
1.605-15 Involute Spline								
1.605	2.125	1.938	2.840	—	WB			4C-4-21 *Tapped holes in yoke ears*
1.605	2.125	1.938	2.840	—	WB			4C-4-31 *Tapped holes in yoke ears*
1.605	2.125	1.938	3.135	—	WB			4C-4-41 *Tapped holes in yoke ears*
5C SERIES		**P-4.530**		**T-1.688**	**KEYWAY: 0.561**			**USE KIT 5C-1X**
1.450-27 Involute Spline								
1.450	2.250	2.060	3.000	.250	WB			5C-4-41 *Tapped holes in yoke ears*
1.450	2.250	2.060	3.375	.250	WB			5C-4-91 *Flanged WB yoke w/tapped holes in yoke ears*
1.605-15 Involute Spline								
1.605	2.125	1.938	2.820	—	WB			5C-4-51 *Tapped holes in yoke ears*
1.605	2.125	1.938	3.038	—	WB			5C-4-101 *Flanged WB yoke w/tapped holes in yoke ears*
1.605	2.125	1.938	3.500	—	WB			5C-4-61 *Tapped holes in yoke ears*
1.605	2.125	1.938	3.500	—	WB			5C-4-71M *Metric; Tapped holes in yoke ears*
1.922-14 Involute Spline								
1.922	2.375	2.182	3.750	—	WB			5C-4-111 *Flanged WB yoke w/tapped holes in yoke ears*
6C SERIES		**P-5.530**		**T-1.688**	**KEYWAY: 0.561**			**USE KIT 050138000**
1.450-27 Involute Spline								
1.450	2.250	2.062	4.250	.250	WB			6C-4-31 *Flanged WB yoke w/tapped holes in yoke ears*
1.450	2.250	2.062	3.000	.250	WB			6C-4-61 *Tapped holes in yoke ears*
1.605-15 Involute Spline								
1.605	2.125	1.937	3.055	—	WB			6C-4-191 *Flanged WB yoke w/tapped holes in yoke ears*
1.605	2.125	1.937	3.090	—	WB			6C-4-71 *Tapped holes in yoke ears*
1.650-16 Involute Spline								
1.650	2.375	2.000	3.062	—	WB			6C-4-91 *Tapped holes in yoke ears*
1.922-14 Involute Spline								
1.922	2.375	2.183	3.500	—	WB			6C-4-141 *Tapped holes in yoke ears*
1.922	2.375	2.183	3.750	—	WB			6C-4-201 *Flanged WB yoke w/tapped holes in yoke ears*
1.922	2.375	2.188	3.122	.120	WB			6C-4-81 *Tapped holes in yoke ears*
2.005-15 Involute Spline								
2.005	2.875	2.500	3.880	.250	WB			6C-4-101 *Tapped holes in yoke ears*
2.005	2.875	2.500	3.880	.250	WB			6C-4-111 *Tapped holes in yoke ears*
2.289-17 Involute Spline								
2.289	2.750	2.500	3.810	—	WB			6C-4-251 *Tapped holes in yoke ears*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
6C SERIES (Con't)		**P-5.530**	**T-1.688**		**KEYWAY: 0.561**			**USE KIT 050138000**
2.289-17 Involute Spline (Continued)								
2.289	2.750	2.500	4.250	—	WB			6C-4-261 *Flanged yoke w/8 tapped holes in flange*
2.541-19 Involute Spline								
2.541	3.125	3.125	4.589	.250	WB			6C-4-41 *Tapped holes in yoke ears*
7C SERIES		**P-5.842**	**T-1.938**		**KEYWAY: 0.624**			**USE KIT 5-7105X**
1.605-15 Involute Spline								
1.605	2.125	1.938	3.620	—	WB			7C-4-81 *Tapped holes in yoke ears*
1.650-16 Involute Spline								
1.650	2.375	2.000	3.780	—	WB			7C-4-211 *Flanged yoke w/6 drilled holes in flange*
1.650	2.375	2.000	3.250	.380	WB			7C-4-261 *Tapped holes in yoke ears*
1.775-16 Involute Spline								
1.775	2.625	2.250	3.500	—	WB			7C-4-121 *Tapped holes in yoke ears*
1.775	2.625	2.250	3.500	—	WB			7C-4-201 *Flanged yoke w/six, tapped holes in flange*
1.796-34 Involute Spline								
1.796	2.625	2.094	3.520	.200	WB			7C-4-291 *Tapped holes in yoke ears*
1.922-14 Involute Spline								
1.922	2.375	2.188	3.440	.120	WB			7C-4-131 *Tapped holes in yoke ears*
1.922	2.375	2.188	3.690	.120	WB			7C-4-311 *Tapped holes in yoke ears*
1.922	2.375	2.188	3.690	.120	WB			7C-4-141 *Tapped holes in yoke ears*
1.922	2.375	2.188	3.690	.120	WB			7C-4-151M *Metric; Tapped holes in yoke ears*
1.922	2.375	2.188	3.690	.120	WB			7C-4-71 *Tapped holes in yoke ears*
1.922	2.375	2.188	3.750	—	WB			7C-4-251 *Tapped holes in yoke ears; w/6 tapped holes in flange*
1.922	2.375	2.188	4.440	—	WB			7C-4-241 *Flanged yoke w/8 tapped holes in flange*
2.005-15 Involute Spline								
2.005	2.822	2.500	3.880	.250	WB			7C-4-281M *Metric; Tapped holes in yoke ears*
2.005	2.822	2.500	3.880	.250	WB			7C-4-31 *Tapped holes in yoke ears*
2.005	2.822	2.500	3.880	.250	WB			7C-4-41M *Metric; Tapped holes in yoke ears*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
7C SERIES (Con't)		**P-5.842**	**T-1.938**		**KEYWAY: 0.624**			**USE KIT 5-7105X**
2.005-15 Involute Spline (Continued)								
2.005	2.875	2.500	4.880	.250	WB			7C-4-191
						Tapped holes in yoke ears; w/16 tapped holes in flange		
2.005	2.875	2.500	3.880	.250	WB			7C-4-11
						Tapped holes in yoke ears		
2.005	2.875	2.500	3.880	.250	WB			7C-4-271
						Tapped holes in yoke ears		
2.005	2.875	2.500	4.880	.250	WB			7C-4-351
						Tapped holes in yoke ears; w/16 tapped holes in flange		
2.008-31 Involute Spline								
2.008	—	2.750	4.209	.750	WB			7C-4-471M
						Metric; Tapped holes in yoke ears; Hub dia. not ground		
2.289-17 Involute Spline								
2.289	2.750	2.500	4.190	—	WB			7C-4-101
						Tapped holes in yoke ears		
2.289	2.750	2.500	4.190	—	WB			7C-4-111M
						Metric; Tapped holes in yoke ears		
2.289	2.750	2.500	4.190	—	WB			7C-4-91
						Tapped holes in yoke ears		
2.289	2.750	2.500	4.440	—	WB			7C-4-161
						Flanged WB yoke w/tapped holes in yoke ears		
2.289	2.750	2.500	4.440	—	WB			7C-4-321
						Flanged WB yoke w/tapped holes in yoke ears		
2.372-46 Involute Spline								
2.372	—	3.385	4.705	.500	WB			7C-4-401M
						Metric; Tapped holes in yoke ears		
2.447-28 Involute Spline								
2.447	3.375	2.500	4.750	.250	WB			7C-4-171
						Tapped holes in yoke ears; Flanged yoke w/8 drilled holes in		
2.541-19 Involute Spline								
2.541	3.125	3.120	4.590	—	WB			7C-4-61
						Tapped holes in yoke ears		
8C SERIES		**P-8.125**	**T-1.938**		**KEYWAY: 0.624**			**USE KIT 5-8105X**
2.447-28 Involute Spline								
2.447	3.375	2.500	4.750	.250	WB			8C-4-101
						Flanged WB yoke w/tapped holes in yoke ears		
2.541-19 Involute Spline								
2.541	3.125	3.125	4.590	.250	WB			8C-4-51
						Tapped holes in yoke ears		
8.5C SERIES		**P-6.500**	**T-2.812**	**KEYWAY:0.625**				**USE KIT NO. 050246000, 050281000**
1.922-14 Involute Spline								
1.922	2.375	2.182	3.440	.120	WB			8.5C-4-21
						Tapped holes in yoke ears		
1.922	2.375	2.182	4.120	.120	WB			8.5C-4-41
						Tapped holes in yoke ears		
1.922	2.375	2.182	4.120	.120	WB			8.5C-4-71
						Tapped holes in yoke ears		
2.005-15 Involute Spline								
2.005	2.625	2.188	3.440	—	WB			8.5C-4-51
						Tapped holes in yoke ears		
2.289-17 Involute Spline								
2.289	2.750	2.500	4.440	—	WB			8.5C-4-61
						Tapped holes in yoke ears		
2.364-36 Involute Spline								
2.364	—	2.500	4.410	.310	WB			5003634
						Tapped holes in yoke ears; Hub diameter not ground		

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES



Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
8.5C SERIES (Con't)		**P-6.500 T-2.812 KEYWAY:0.625**						**USE KIT NO. 050246000, 050281000**
2.447-28 Involute Spline								
2.447	3.375	2.500	4.750	.250	WB			8.5C-4-11 *Tapped holes in yoke ears*
2.447	3.375	2.500	4.750	.250	WB			8.5C-4-111 *Flanged WB yoke w/tapped holes in yoke ears*
2.541-19 Involute Spline								
2.541	3.125	3.125	4.590	.250	WB			8.5C-4-31 *Tapped holes in yoke ears*
2.588-40 Involute Spline								
2.588	4.000	2.840	4.070	—	WB	5004773	5001687	5004772⅄ *Metric; Tapped holes in yoke ears*
9C/1820 SERIES		**P-8.250 S-2.812**		**KEYWAY: 0.624**				**USE KIT 5-9001X**
2.005-15 Involute Spline								
2.005	2.875	2.500	3.880	.250	WB			9C-4-41• *Drilled holes in yoke ears*
2.344-16 Spline								
2.344	2.875	2.750	4.125	—	WB			8-4-851
2.375-46 Involute Spline								
2.375	3.750	2.375	3.938	—	WB	8-4-1151X		8-4-1141• *Assy includes mechanical speedometer drive gear #231527*
2.375	3.750	2.375	3.938	—	WB	8-4-1161X		8-4-1141• *Assy includes electronic speedometer gear #231528*
2.500-10 Spline								
2.500	3.500	3.234	4.375	—	WB			8-4-1061
2.541-19 Involute Spline								
2.541	3.125	3.125	4.590	.250	WB			9C-4-91
2.541	3.125	3.125	5.250	—	WB			9C-4-111 *Tapped holes in yoke ears*
2.631-25 Involute Spline								
2.631	3.875	4.312	6.810	1.120	WB			9C-4-211• *Tapped holes in yoke ears*
2.784-21 Involute Spline								
2.784	3.375	3.125	4.590	—	WB			9C-4-81
10C SERIES		**P-8.375 S-3.625**		**KEYWAY: 1.000**				**USE KIT 050242000, 050A53000**
2.631-25 Involute Spline								
2.631	3.625	3.000	4.620	1.000	WB			10C-4-21■ *Tapped holes in yoke ears*
3.923-30 Involute Spline								
3.923	4.875	4.625	6.240	—	WB			10C-4-81

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

END YOKES with SPLINED HOLES

Major Diameter	R Ground Hub Dia.	Q Length Thru Hole	S Centerline to End	C'Bore Depth	Style	End Yoke Assy. (includes slinger/plug) Order When Listed	Slinger/Plug Part Number	Spicer Part Number
7290 SERIES		**K-2.625**	**D-1.125**			**USE KIT NO. 5-1309X, 5-354X, 5-811X**		
1.146-26 Involute Spline								
1.146	1.552	1.500	3.350	—	BS	2-4-7651-1X■	232549	2-4-7641-1⅄
1.146	1.844	1.375	3.219	.120	BS			2-4-7661-1
1.263-29 Involute Spline								
1.263	1.875	1.500	3.188	—	BS			2-4-7901-1
1.276-29 Involute Spline								
1.276	1.875	1.500	3.359	—	BS	2-4-7681-1X	34592	2-4-7671-1⅄

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

STRAIGHT ROUND HOLE





ISR Style



SR Style



BP Style



BS/ CB/ CV/ HR/ UB Styles

P	X	W			R	Q	S	STYLE	End Yoke Part Number
Round Hole Diameter	SAE Keyway Width	Set Screw Location in Relation to Keyway			Hub Diameter	Length Thru Hole	C/L to End of Hub		
		Hole Diameter	Location						
			Keyway	Set Screw					
1000 SERIES		**K-1.500**		**D-.938**					**USE KIT 5-170X**
.625	—	—			1.625	1.030	2.500	ISR	10-4-333 *High angle yoke*
.625	.188	.375	12	6	1.625	—	2.500	ISR	10-4-373 *High angle yoke*
.750	—	—			1.624	—	2.500	ISR	10-4-303 *High angle yoke*
.750	.188	.375	12	9	1.625	1.312	1.812	ISR	10-4-693
.750	.188	.375	3	6	1.625	1.030	2.500	ISR	10-4-13 *High angle yoke*
.750	.188	.375	3	6 & 12	1.625	1.030	2.500	ISR	10-4-133 *High angle yoke*
.750	.250	.375	3	9	1.625	1.030	2.500	ISR	10-4-23 *High angle yoke*
.812	.188	.375	3	9	1.625	1.030	2.500	ISR	10-4-33• *High angle yoke*
.812	.250	.375	12	9	1.625	1.312	1.812	ISR	10-4-713
.812	.250	.375	3	6	1.625	1.030	2.500	ISR	10-4-43 *High angle yoke*
.875	—	.375		3	1.625	—	2.500	ISR	10-4-203 *High angle yoke*
.875	.188	.375	3	9	1.625	1.030	2.500	ISR	10-4-53 *High angle yoke*
.875	.250	.375	3	9	1.625	—	2.500	ISR	10-4-453 *High angle yoke*
.875	.250	.375	3	9	1.625	—	2.500	ISR	10-4-63 *High angle yoke*
.938	.250	.375	3	9	1.625	—	2.500	ISR	10-4-73 *High angle yoke*
1.000	—	—			1.625	1.030	2.500	ISR	10-4-443 *High angle yoke; .375 dia. drilled hole thru hub*
1.000	.188	.375	3	9	1.625	1.030	2.500	ISR	10-4-83 *High angle yoke*
1.000	.250	.375	3	12	1.625	1.030	2.500	ISR	10-4-573 *High angle yoke*
1.000	.250	.375	3	9	2.000	1.030	2.500	ISR	10-4-93 *High angle yoke*

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

STRAIGHT ROUND HOLE

P	X	W			R	Q	S	STYLE	
Round Hole Diameter	SAE Keyway Width	Set Screw Location in Relation to Keyway			Hub Diameter	Length Thru Hole	C/L to End of Hub		End Yoke Part Number
		Hole Diameter	Location						
			Keyway	Set Screw					
1000 SERIES (Continued)					**K-1.500**	**D-.938**		**USE KIT 5-170X**	
1.062	.250	.375	9	6	2.000	1.030	2.500	ISR	10-4-163 *High angle yoke*
1.125	.250	.375	3	12	2.000	1.030	2.500	ISR	10-4-143 *High angle yoke*
1.125	.250	.375	3	6	2.000	1.030	2.500	ISR	10-4-103 *High angle yoke*
1.125	.312	.375	3	6	2.000	1.030	2.500	ISR	10-4-1473 *High angle yoke*
1.125	.312	.375	3	9	2.000	1.030	2.500	ISR	10-4-113 *High angle yoke*
1.125	.312	.375	3	9	2.000	1.030	2.500	ISR	10-4-233■ *High angle yoke*
1.188	.312	.375	3	9	2.000	1.030	2.500	ISR	10-4-153 *High angle yoke*
1.250	.250	.375	9	12	2.000	1.030	2.500	ISR	10-4-183 *High angle yoke*
1.250	.312	.375	3	9	2.000	1.030	2.500	ISR	10-4-123 *High angle yoke*
1.250	.312	.375	9	12	2.000	—	2.500	ISR	10-4-193 *High angle yoke*
1.375	.312	.375	3	9	2.000	1.030	2.500	ISR	10-4-293 *High angle yoke*
1.375	.375	.375	3	6	2.250	—	2.500	ISR	10-4-213 *High angle yoke*
1.438	.375	.375	3	9	2.250	—	2.500	ISR	10-4-383 *High angle yoke*
1.500	.375	.375	3	6	2.250	—	2.500	ISR	10-4-223 *High angle yoke*
1110 SERIES			**K-2.656**	**D-.938**				**USE KIT NO. 5-101X**	
.750	.188	.375	12	3	1.688	—	2.250	SR	1-4-783
.750	.188	.375	12	6	1.688	—	2.250	SR	1-4-1383•
.875	.188	.375	9	3	2.000	—	2.250	SR	1-4-803
1.000	.250	.375	9	3	2.000	—	2.250	SR	1-4-823
1.125	.312	.375	3	9	2.000	—	2.250	SR	1-4-943
1.250	.250	.375	3	6	2.000	—	2.250	SR	1-4-1133
1.250	.312	.375	3	9	2.000	—	2.250	SR	1-4-933
1140 SERIES			**K-1.812**	**D-1.062**				**USE KIT NO. 5-242X**	
1.125	.250	.375	12		—	—	—	SR	1-4-3043•
1.250	.250	.375	12		—	—	—	SR	1-4-3093•
1.250	.312	.375	12		—	—	—	SR	1-4-3113•
1.375	.312	.375	9		—	—	—	SR	1-4-3133•
1240 SERIES			**E-2.875**	**D-1.125**				**USE KIT NO 5-129X**	
1.125	.250	.375	12		—	—	—	SR	2-4-1363•
1.250	.250	.375	12		—	—	—	SR	2-4-1413•
1.250	.312	.375	12		—	—	—	SR	2-4-1423•
1.375	.312	.375	12		—	—	—	SR	2-4-1873•
1.500	.375	.375	9		—	—	—	SR	2-4-1463•

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

STRAIGHT ROUND HOLE





ISR Style



SR Style



BP Style





BS/ CB/ CV/ HR/ UB Styles

P	X	W			R	Q	S	STYLE	End Yoke Part Number
Round Hole Diameter	SAE Keyway Width	Set Screw Location in Relation to Keyway			Hub Diameter	Length Thru Hole	C/L to End of Hub		
		Hole Diameter	Location						
			Keyway	Set Screw					
1310 SERIES SR: E-3.469 OTHERS E-3.219, D-1.062							**USE KIT 5-153X,5-785X,5-810X**		
.750	—	—			2.125	—	2.562	SR	2-4-177
.750	.188	.375	12	6	2.125	—	2.562	SR	2-4-433
.812	.250	.375	12	6	2.125	—	2.562	SR	2-4-443
.875	.188	.375	12	6	2.125	—	2.562	SR	2-4-453
.875	.250	.375	12	6	2.125	—	2.562	SR	2-4-583
.938	.250	.375	12	6	2.000	—	2.562	SR	2-4-463
1.000	.250	.375	12	6 & 12	2.125	—	2.562	SR	2-4-473
1.125	.250	.375	12	6	2.125	—	2.562	SR	2-4-503
1.125	.312	.375	12	6	2.125	—	2.562	SR	2-4-523
1.188	.312	.375	12	6	2.125	—	2.562	SR	2-4-553
1.250	—	—			2.125	—	2.562	SR	2-4-853
1.250	—	.375			2.120	—	2.562		2-4-2043
1.250	.250	.375	12	6	2.125	—	2.562	SR	2-4-573
1.250	.312	.375	12		2.125	—	2.561	SR	2-4-613
1.250	.312	.375	12	6	2.125	—	2.562	SR	2-4-533
1.250	.312	.375	12	6, 9, 12	2.125	—	2.562	SR	2-4-2613
1.250	.312	.500	12	6	2.125	—	2.562	SR	2-4-663
1.250	.313	.375	12	6	2.120	—	2.940	UB	2-4-783•
1.250	.314	.375	12	6	2.120	1.495	2.935	SR	2-4-783-1
1.375	.312	.375	12	3	2.000	—	2.562	SR	2-4-1103
1.375	.375	.375	12	6	2.125	1.125	2.594	UB	2-4-1053
1.375	.375	.375	12	6	2.000	—	2.562	SR	2-4-803
1.500	.375	.375	12	6	2.125	—	2.562	SR	2-4-1233
1.503	—	—			2.000	1.625	2.562	SR	2-4-353
							.312 diameter drilled hole thru hub.		
1.688	.375	.375	12	12	2.500	—	2.562	SR	2-4-2013
1340 SERIES		**E-3.953**		**D-1.250**				**USE KIT NO. 5-243X**	
1.375	.312	.375	12	12 & 3	—	—	—	SR	3-4-813•
1350 SERIES		**SR: E-3.875 OTHERS: E-3.625, D-1.188**					**USE KIT 5-178X, 5-799X**		
.750	—	—			2.000	—	4.090	BS	3-4-543-1
1.000	.250	—	12		2.000	—	2.690	SR	3-4-33

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

STRAIGHT ROUND HOLE

P	X	W			R	Q	S	STYLE	End Yoke Part Number
Round Hole Diameter	SAE Keyway Width	Set Screw Location in Relation to Keyway			Hub Diameter	Length Thru Hole	C/L to End of Hub		
		Hole Diameter	Location						
			Keyway	Set Screw					
1350 SERIES (Con't)		**SR: E-3.875 OTHERS: E-3.625, D-1.188**					**USE KIT 5-178X, 5-799X**		
1.125	.250	—	12		2.000	—	2.688	SR	3-4-43
1.250	.312	—	12		2.000	—	2.750	SR	3-4-53
1.250	.312	—	12		2.000	—	2.688	SR	3-4-93
1.250	.312	.375	12		2.000	—	2.750	SR	3-4-13
							Two set screws, 135° & 225° from keyway		
1.250	.312	.375	12	6	2.062	—	3.000	SR	3-4-103
1.250	.314	.375	12	6	2.250	1.500	3.000	BS	3-4-283-1
1.375	.312	.375	12	6	2.250	1.500	3.031	BS	3-4-613-1
1.500	.313	.375	12		—	—	3.500	BS	3-4-243-1
1.500	.375	.375	12	6	—	—	3.469	BS	3-4-333-1
1410 SERIES		**SR: E-4.438 OTHERS: E-4.188, D-1.188**					**USE KIT 5-160X, 5-801X**		
1.250	.250	.500	12	6	2.250	—	3.700	BS	3-4-163-1
1.250	.312	.375	12	6	2.250	2.000	3.688	BS	3-4-343-1
1.250	.313	—	12		2.250	2.000	3.700	UB	3-4-1763•
1.250	.313	—	12		2.252	2.000	3.700	BS	3-4-1763-1
1.500	.377	.500	12	135°	2.690	2.270	4.000	BS	3-4-263-1
							Two set screws, 135° & 225° from keyway		
1.750	.439	.500	12		2.750	—	4.250	BS	3-4-273-1
							Two set screws, 135° & 225° from keyway		
1480 SERIES		**SR: E-4.438 OTHERS: E-4.188, D-1.375**					**USE KIT 5-188X, 5-803X**		
1.375	—	—			2.130	—	1.440		3-4-1743•
1.500	.375	.375	12	12 & 6	3.188	2.063	4.625	SR	3-4-1173•
							.318 dia. hole drilled thru hub		
2.000	.500	.375	3	3 & 9	3.188	2.063	4.625	SR	3-4-1753■
							.318 dia. hole drilled thru hub		
1550 SERIES		**E-5.250**	**D-1.375**				**USE KIT 5-155X, 5-808X**		
1.862	—	—			3.070	2.625	4.685	BS	4-4-843-1
1610 SERIES		**E-5.312**	**D-1.875**				**USE KIT 5-279X, 5-674X**		
1.750	—	—			2.750	—	5.620	BP	5-4-413
									High angle yoke
2.250	—	—			3.344	—	5.620	BP	5-4-453•
									High angle yoke

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

TAPERED HOLE
With U-Bolt and Cap & Bolt Design



P Tapered Hole Diameter	X SAE Keyway Width	R Ground Hub Diameter	Q Length Thru Hole	S Centerline to End of Spline	STYLE	End Yoke Part Number
1310 SERIES SR: E-3.469 OTHERS E-3.219, D-1.062 =USE KIT 5-153X,5-785X,5-810X						
USES U-BOLT ASSY. 2-94-28X, STRAP ASSY. 2-70-18X						
1.125	.312	1.750	1.500	3.000	UB	2-4-154•
1.250	.312	2.125	1.500	2.938	UB	2-4-64
1.375	.375	2.125	2.000	3.438	UB	2-4-824
1.375	.375	2.250	2.000	3.438	UB	2-4-834
1.496	.375	2.200	2.000	3.450	BS	2-4-854•
1350 SERIES SR: E-3.875 OTHERS: E-3.625, D-1.188 USE KIT 5-178X, 5-799X						
USES U-BOLT ASSY. 3-94-18X, STRAP ASSY. 3-70-28X						
1.246	.312	2.250	1.500	3.000	BS	3-4-54-1
1.250	.314	2.620	1.475	3.250	BS	3-4-234-1•
1.375	.375	2.250	2.000	3.531	BS	3-4-24-1
1.496	.375	2.250	2.000	3.500	BS	3-4-84-1
1410 SERIES SR: E-4.438 OTHERS: E-4.188, D-1.188 USE KIT 5-160X, 5-801X						
USES U-BOLT ASSY, 3-94-18X, STRAP KIT 3-70-28X						
1.375	.375	2.250	2.000	3.688	BS	3-4-14-1
1.375	.375	2.250	2.000	3.688	BS	3-4-154-1
1.496	.375	2.500	2.000	3.812	BS	3-4-64-1
1650 SERIES E-5.594 D-1.625 USE KIT 5-165X						
USES CAP & BOLT ASSY. 5-70-18X						
1.750	.438	2.875	2.250	4.312	BS	5-4-1324

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

HEX & SQUARE HOLE



P	R	W		S	
Hex Hole Diameter	Ground Hub Diameter	Set Screw Hole Viewed from Hub End		Centerline to End of Hub	End Yoke Part Number
		Hole Diameter	Location		
1000 SERIES		**K-1.500**	**D-.938**		**USE KIT 5-170X**
.875	2.000	.375	3	2.500	10-4-282
1.125	2.000	.375	3	2.500	10-4-32



P	R	W		S	
Hex Hole Diameter	Ground Hub Diameter	Set Screw Hole Viewed from Hub End		Centerline to End of Hub	End Yoke Part Number
		Hole Diameter	Location		
1000 SERIES	**K-1.500**	**D-.938**			**USE KIT 5-170X**
.750	1.625	.375	3	2.500	10-4-22
.812	1.969	.375	3	2.500	10-4-42
.875	1.620	.375	3	2.875	10-4-62
.875	1.719	—		2.500	10-4-82
		10-4-82 will be replaced by 10-4-92 when supply is exhausted			
.875	1.969	.375	3	2.500	10-4-12
1.000	2.000	.375	3	2.500	10-4-52
1140 SERIES	**K-1.812**	**D-1.062**			**USE KIT NO. 5-242X**
1.000	—	.375		—	1-4-222•
1240 SERIES	**E-2.875**	**D-1.125**			**USE KIT NO 5-129X**
1.000	—	—		—	2-4-152•
1310 SERIES	**SR: E-3.469 OTHERS E-3.219, D-1.062**				**USE KIT 5-153X,5-785X,5-810X**
.875	2.120	—		2.560	2-4-502▪

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

STEERING SHAFT SERRATED HOLE
With Snap Ring Design



Serrated Hole		Bolt Hole Diameter	H	J	L	L1	S	End Yoke Part Number
Major Diameter	Minor Diameter (Nominal)		Center of Bolt Hole to Center of Bearing Hole	Center of Bolt Hole to End of Hub	Top of Bolt Hole to Center of Spline	Center of Bolt Hole to Center of Spline	Centerline to End of Hub	
1000 SERIES		**K-1.500**	**D-.938**					**USE KIT 5-103X**
.735-16 Based On 36 Spline								
.735	.696	.451	2.120	.500	—	.525	2.620	10-4-431SX
.739-21 Based On 36 Spline								
.739	.696	.467	1.780	.470	.748	—	2.250	10-4-871SX
.739-26 Based On 36 Spline								
.739	.696	.467	1.780	.470	.726	.525	2.250	10-4-611SX
.739-30 Based On 36 Spline								
.739	.696	.406	2.030	.470	—	.470	2.500	10-4-631SX
.739	.696	.406	2.030	.470	—	.470	2.500	10-4-931SX
.811-30 Based On 36 Spline								
.811	.764	.405	2.030	.470	.710	—	2.500	10-4-501SX
.811	.764	.405	2.120	.500	.710	—	2.620	10-4-901SX
.811	.764	.406	2.030	.470	.673	—	2.700	10-4-491SX
.811	.764	.467	2.030	.470	.770	—	2.500	10-4-1001SX
.811	.764	.467	2.030	.470	.770	—	2.500	10-4-821SX
.811	.764	.470	2.030	.380	.770	—	2.410	10-4-1181SX•
.813-18 Based On 36 Spline								
.813	.764	.451	2.030	.380	.764	—	2.410	10-4-911SX
.813	.764	.451	2.030	.470	.759	—	2.500	10-4-841SX
.813	.764	.467	1.780	.380	.761	—	2.160	10-4-621SX
.813	.764	.467	1.780	.470	.762	—	2.250	10-4-1281SX•
.813	.764	.467	2.330	.370	.761	—	2.700	10-4-551SX
.870-14 Based On 36 Spline								
.870	.819	.451	2.031	.470	.781	—	2.500	10-4-1061SX
.870-30 Based On 36 Spline								
.870	.819	.403	2.031	.469	.748	—	2.500	10-4-601SX
.870	.819	.405	2.031	.469	.738	—	2.500	10-4-951SX
.870	.819	.451	2.031	.530	.789	—	2.280	10-4-1241SX•
.870	.819	.467	2.031	.469	.815	—	2.500	10-4-741SX
.870	.819	.467	2.031	.470	.780	—	2.500	10-4-991SX•
.870	.819	.467	2.031	.470	.787	—	2.500	10-4-461SX
.990-14 Based On 36 Spline								
.990	.947	.451	2.030	.470	.852	—	2.500	10-4-851SX

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

STEERING SHAFT SERRATED HOLE
With Snap Ring Design



Serrated Hole		Bolt Hole Diameter	H	J	L	L1	S	End Yoke Part Number
Major Diameter	Minor Diameter (Nominal)		Center of Bolt Hole to Center of Bearing Hole	Center of Bolt Hole to End of Hub	Top of Bolt Hole to Center of Spline	Center of Bolt Hole to Center of Spline	Centerline to End of Hub	
1000 SERIES (Continued)		**K-1.500**	**D-.938**					**USE KIT 5-103X**
.994-30 Based On 36 Spline								
.994	.947	.405	1.750	.630	.802	—	2.380	10-4-391SX
.994	.947	.405	1.780	.470	.802	—	2.250	10-4-121SX
.994	.947	.405	1.780	.470	.802	—	2.250	10-4-561SX
.994	.947	.405	2.030	.470	.802	—	2.500	10-4-961SX
.994	.947	.405	2.030	.470	.802	—	2.500	10-4-371SX
.994	.947	.451	2.030	.470	.863	—	2.500	10-4-971SX
.994	.947	.451	2.030	.470	.863	—	2.500	10-4-451SX
.994	.947	.451	4.000	.470	.863	—	4.470	10-4-1201SX
.994	.947	.467	2.030	.470	.835	—	2.500	10-4-731SX
1.006-34 Based On 48 Spline								
1.006	.960	.468	2.030	.470	—	.630	2.500	10-4-661SX
1310 SERIES		**E-3.469**	**D-1.062**					**USE KIT 5-251X**
1.000-30 Based On 36 Spline								
1.000	.947	4.500	2.120	.760	—	.610	2.880	2-4-4411SX
1.000-36 Spline								
1.000	.947	.406	2.125	.437	—	.610	2.562	2-4-4461SX

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

STEERING SHAFT STRAIGHT ROUND HOLE
With Snap Ring Design



STRAIGHT ROUND HOLE		Bolt Hole Diameter	H	J	L	S	End Yoke Part Number
Hole Size Max./Min.	Keyway Width		Center of Bolt Hole to Center of Bearing Hole	Center of Bolt Hole to End of Hub	Center of Bolt Hole to Center of Hub Hole	Centerline to End of Hub	
1000 SERIES	**K-1.500**		**D-.938**			**USE KIT 5-103X**	
.7510/.7500	.1880	.4690	1.7500	.6250	.5100	2.3750	10-4-1673SX
.9860/.9850	.1880	.4670	1.7500	.6250	.5600	2.3750	10-4-1083SX

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

SLINGER STYLES



Style 1



Style 2



Style 3

Slinger Number	Style	A	B	C
232184⅄	1	2.049	1.505	0.382
231302•	1	3.078	1.859	0.422
232064⅄	1	3.399	2.277	0.803
231780⅄	1	3.438	1.609	0.344
231004	1	3.656	2.141	0.438
233034⅄	1	3.823	2.468	1.087
230421	1	3.938	2.188	0.531
230118	1	4.000	2.062	0.562
31875•	1	4.125	1.562	0.406
230124	1	4.134	2.308	0.560
231305⅄	1	4.500	3.110	0.750
232646⅄	1	4.500	3.110	0.750
230909	1	4.635	2.938	0.312
231541	1	4.688	2.954	0.500
231206	1	4.812	2.500	1.000
98-1361	1	4.812	2.953	0.812
231022	1	4.891	3.000	0.688
231959⅄	1	4.891	3.000	0.562
231102	1	4.891	3.141	0.938
231357⅄	1	5.000	3.109	0.750
232189⅄	1	5.000	3.109	0.750
232638⅄	1	5.150	3.095	1.937
5003552	1	5.280	3.489	0.750
232055	1	5.359	3.250	1.375
230795•	1	5.453	3.938	0.656
231263⅄	1	5.656	3.391	0.609
231347•	1	5.672	3.031	0.469
98-1362	1	5.719	2.839	0.875
231179	1	5.750	3.391	0.938
231101■	1	6.000	2.938	0.938
231359	1	6.000	3.125	0.812
232747⅄	1	6.050	3.488	0.690
230674	1	6.125	3.516	0.750
232759⅄	1	6.330	4.262	1.340
231599	1	6.750	3.391	1.500
230921	1	7.000	3.141	0.812
231803	1	7.000	3.484	0.891
231615	1	7.406	3.109	0.750

Slinger Number	Style	A	B	C
230998•	2	4.250	3.500	0.625
230859⅄	2	4.750	2.938	0.312
231047	2	4.891	3.500	0.750
230902	2	5.720	4.067	0.920
232746⅄	2	5.940	3.697	0.710
232002⅄	2	6.000	3.141	0.375
232027⅄	2	6.000	3.141	0.359
231866•	2	6.000	3.500	0.812
231745•	2	7.000	3.750	0.719
15099•	3	2.125	1.562	0.219
41498	3	2.125	1.603	0.219
34592	3	2.438	1.875	0.219
231877•	3	2.531	1.500	0.547
330851•	3	2.844	1.562	0.406
5003953⅄	3	3.150	2.048	0.197
5003955⅄	3	3.150	2.168	0.197
231620⅄	3	3.812	3.031	0.266
232367	3	4.000	3.000	0.812
232039•	3	4.062	2.766	1.125
231028	3	4.328	3.000	0.938
565-W•	3	4.438	2.500	0.531
232042-1⅄	3	4.500	2.375	0.797
230746	3	4.625	2.391	0.875
230910•	3	4.625	2.938	0.312
232372⅄	3	4.688	3.109	1.675
232042-2	3	4.906	2.625	0.500
232042-3⅄	3	5.109	3.000	0.297
232042-6⅄	3	5.297	3.125	0.500
232042-11•	3	5.406	3.375	0.406
230991⅄	3	5.438	3.938	0.656
230888•	3	5.650	4.250	0.656
232042-10	3	5.797	3.375	0.406
232193⅄	3	6.438	4.016	0.500

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

SLINGER STYLES



Style 4



Style 5



Style 6

Slinger Number	Style	A	B	C
42779•	4	3.125	2.188	0.340
232895⅄	4	3.360	2.559	0.330
230794	4	4.750	2.938	0.312
232182•	4	6.000	3.141	0.375
231579⅄	5	2.500	2.281	0.547
231596⅄	5	2.938	1.578	0.438
232166	5	3.425	3.156	0.781
232168	5	3.766	3.000	0.641
232609•	5	3.820	3.000	1.260
231750	5	3.954	3.031	0.375
231755	5	3.954	3.062	0.562
232032⅄	5	4.016	2.438	0.438
232514	5	4.125	2.750	0.390
232610•	5	4.170	3.432	1.260
231616	5	4.594	3.844	0.422
232511	5	5.000	3.125	0.350

Slinger Number	Style	A	B	C
231549•	6	2.266	1.781	0.500
98-1473	6	2.266	1.781	0.500
230881■	6	2.750	1.781	0.500
231636⅄	6	3.000	2.281	0.578
230865⅄	6	3.281	2.188	0.562
230629⅄	6	3.375	2.031	0.719
1015W⅄	6	3.438	2.766	0.750
230386•	6	3.562	2.375	1.250
230587⅄	6	3.562	2.500	0.812
231356	6	3.734	2.281	0.797
5003086⅄	6	3.965	3.094	0.709
230897•	6	4.000	2.688	0.594
232037⅄	6	4.234	2.750	0.781
829W•	6	4.375	3.062	0.625
330287•	6	4.562	2.766	0.891
231366⅄	6	4.672	2.844	0.891
330287•	6	4.710	2.759	0.880
231550⅄	6	4.766	2.750	1.406
231015	6	4.797	2.969	0.562
330499•	6	5.000	3.062	0.812
233038⅄	6	7.368	4.795	0.658

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

SLINGER STYLES



Style 9



Style 10



Style 7



Style 8

Slinger Number	Style	A	B	C
231935⅄	7	2.875	1.188	0.375
41195•	7	2.891	1.891	0.422
232198⅄	7	3.312	2.469	0.562
231872	7	3.469	2.562	0.625
232199	7	3.656	3.094	0.625
232200	7	3.828	3.094	0.562
230207■	7	4.375	2.531	0.875
230895	7	4.625	2.391	0.875
232201	7	4.812	3.594	1.000
232948⅄	7	5.110	3.093	0.760
230900•	7	5.500	2.766	0.844
231058⅄	7	6.125	4.016	0.859

Slinger Number	Style	A	B	C
232816⅄	8	3.696	2.185	0.590
231013	8	5.125	3.438	1.125
232760⅄	8	6.320	4.262	2.126
232167•	9	4.344	2.750	1.000
232604	9	4.781	3.000	1.070
42735	10	2.180	1.535	0.729

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

SLINGER STYLES



Style 11



Style 12



Style 13



Style 14



Style 15

Slinger Number	Style	A	B	C
231970⅄	11	2.840	1.504	0.430
5003951⅄	11	3.654	1.735	0.622
42501	11	5.120	1.875	0.793
233051•	11	5.886	3.135	0.984
5006975⅄	11	5.886	3.135	0.984
5008437•	11	7.598	3.850	0.740

Slinger Number	Style	A	B	C
232020⅄	12	2.176	1.504	0.280
30798	12	3.812	1.875	0.312
5001045⅄	12	4.980	3.879	0.455
232028⅄	13	5.760	3.515	0.060
5001780⅄	14	6.850	4.007	0.430
5001687⅄	14	8.150	4.262	0.430
5002871⅄	15	4.710	3.133	0.984

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

Important: See Safety Information in General Information Section (J300P-GI)

PART NUMBER INDEX

1-4-222• 59
1-4-783 55
1-4-803 55
1-4-823 55
1-4-933 55
1-4-943 55
1-4-1133 55
1-4-1201 12
1-4-1383• 55
1-4-3043• 55
1-4-3093• 55
1-4-3113• 55
1-4-3133• 55
2-4-64 58
2-4-152• 59
2-4-154• 58
2-4-177 56
2-4-353 56
2-4-411 14
2-4-433 56
2-4-443 56
2-4-453 56
2-4-463 56
2-4-473 56
2-4-502■ 59
2-4-503 56
2-4-523 56
2-4-533 56
2-4-553 56
2-4-573 56
2-4-583 56
2-4-613 56
2-4-663 56
2-4-783-1 56
2-4-783• 56
2-4-803 56
2-4-824 58
2-4-834 58
2-4-853 56
2-4-854• 58
2-4-1053 56
2-4-1103 56
2-4-1233 56
2-4-1301 13
2-4-1311 14
2-4-1363• 55
2-4-1413• 55
2-4-1423• 55
2-4-1463• 55
2-4-1721 12
2-4-1731 14
2-4-1741 14
2-4-1831 14
2-4-1873• 55
2-4-1921 13
2-4-1981-1■ 14
2-4-1991-1X 14
2-4-2013 56
2-4-2043 56
2-4-2271-1 13
2-4-2371 14
2-4-2401-1 14
2-4-2401• 14
2-4-2411-1X 14
2-4-2411X• 14
2-4-2601-1• 14
2-4-2601• 14
2-4-2611-1X 14
2-4-2611X 14
2-4-2613 56
2-4-2671 14
2-4-2791-1■ 12
2-4-2791-1■ 12
2-4-2791• 12
2-4-2801-1X 12
2-4-2821-1X 12
2-4-2821X• 12
2-4-2841-1• 12
2-4-2851-1X• 12
2-4-2901 14
2-4-3161 13
2-4-3331 12
2-4-3571-1■ 15
2-4-3581-1X 15
2-4-3741-1 13
2-4-3771• 14
2-4-3781X 14
2-4-3791-1• 14
2-4-3791• 14
2-4-3801-1X 14
2-4-3801X 14
2-4-4011• 14
2-4-4021X 14
2-4-4031-1 15
2-4-4051• 12
2-4-4061X 12
2-4-4191-1 15
2-4-4291-1X 15
2-4-4341 13
2-4-4471X 14
2-4-4601-1 13
2-4-4801• 14
2-4-4921 12
2-4-4931 12
2-4-5091 15
2-4-5241■ 13
2-4-5251X• 13
2-4-5301• 15
2-4-5311X 15
2-4-5321• 13
2-4-5331X 13
2-4-5341 15
2-4-5411 14
2-4-5421X 14
2-4-5441 15
2-4-5521-1 15
2-4-5681-1• 15
2-4-5691-1X• 15
2-4-5781 14
2-4-5851-1 13
2-4-5891• 12
2-4-5901-1 12
2-4-5911-1• 12
2-4-5921-1X 12
2-4-5991-1 15
2-4-6001-1 14
2-4-6011 14
2-4-6101• 15
2-4-6111X 15
2-4-6121-1• 12
2-4-6131-1X 12
2-4-6161-1 13
2-4-6171-1■ 13
2-4-6181-1X• 13
2-4-6191-1 12
2-4-6221 15
2-4-6231• 15
2-4-6301 13
2-4-6341 14
2-4-6401-1• 13
2-4-6411-1X• 13
2-4-6561-1 13
2-4-6641-1 13
2-4-6661-1■ 12
2-4-6671-1• 14
2-4-6721-1• 12
2-4-6731-1X 12
2-4-6781-1 13
2-4-6851-1■ 15
2-4-6891-1■ 13
2-4-6901-1X 13
2-4-6981-1X• 12
2-4-7021-1 13
2-4-7031-1X 15
2-4-7111-1• 12
2-4-7141-1 14
2-4-7151 14
2-4-7181-1 15
2-4-7221-1X 12
2-4-7291-1X 13
2-4-7371-1X■ 13
2-4-7401-1■ 13
2-4-7491-1• 13
2-4-7501-1X 13
2-4-7631-1 15

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

2-4-7641-1■ 53
2-4-7651-1X■ 53
2-4-7661-1 53
2-4-7671-1■ 53
2-4-7681-1X 53

2-4-7731• 14
2-4-7801-1 15
2-4-7871-1• 13
2-4-7871• 13
2-4-7901-1 53

2-4-8031-1• 12
2-4-8041-1■ 15
2-4-8041■ 15
2-4-8051-1X 15
2-4-8051X■ 15

2-4-8081-1• 13
2-4-8081• 13
2-4-8091-1X 13
2-4-8091X 13
2-4-8161• 13

2-4-8171X• 13
2-4-8181-1■ 13
2-4-8191-1X• 13
2-4-8241 12
2-4-8311-1 13

2-4-8321-1• 13
2-4-8331-1• 14
2-4-8391-1X 14
2-4-8421-1 15
2-4-8521-1• 13

2-4-8531-1■ 13
2-4-8541-1X• 13
2-4-8551-1X 13
2-4-8691-1■ 13
2-4-8701-1X• 13

2-4-4411SX 61
2-4-4461SX 61
3-4-13 57
3-4-14-1 58
3-4-24-1 58

3-4-33 56
3-4-43 57
3-4-53 57
3-4-54-1 58
3-4-64-1 58

3-4-84-1 58
3-4-93 57
3-4-103 57
3-4-154-1 58
3-4-163-1 57

3-4-178-1X 17
3-4-234-1• 58
3-4-243-1 57
3-4-263-1 57
3-4-273-1 57

3-4-283-1 57
3-4-333-1 57
3-4-343-1 57
3-4-543-1 56
3-4-613-1 57

3-4-813• 56
3-4-1111-1 17
3-4-1161-1 19
3-4-1173• 57
3-4-1211-1 17

3-4-1261-1 17
3-4-1371-1 17
3-4-1371• 17
3-4-1441-1 17
3-4-1471-1 18

3-4-1481-1 18
3-4-1501-1 17
3-4-1743• 57
3-4-1753■ 57
3-4-1763-1 57

3-4-1763• 57
3-4-1841-1 19
3-4-1901-1 18
3-4-1911-1• 19
3-4-2051-1 16

3-4-2111-1 16
3-4-2131-1• 19
3-4-2171-1• 17
3-4-2231-1 17
3-4-2241-1 19

3-4-2251-1 20
3-4-2271-1 18
3-4-2281• 19
3-4-2351-1 17
3-4-2511-1 19

3-4-2781• 16
3-4-2841-1• 18
3-4-2851-1X 18
3-4-2941-1 19
3-4-3041-1 19

3-4-3051-1 22
3-4-3061-1 21
3-4-3081-1 20
3-4-3081• 20
3-4-3091-1 20

3-4-3111-1 20
3-4-3121-1 21
3-4-3141-1■ 21
3-4-3191-1 21
3-4-3241-1 21

3-4-3291-1 17
3-4-3331-1X• 20
3-4-3331X• 20
3-4-3351• 19
3-4-3391-1• 21

3-4-3491-1 19
3-4-3541-1 21
3-4-3571-1 21
3-4-3671-1X• 17
3-4-3771• 21

3-4-3781-1 21
3-4-3801-1 17
3-4-3861-1• 22
3-4-3901-1■ 22
3-4-3931-1• 17

3-4-3931• 17
3-4-3951-1 17
3-4-3961-1 19
3-4-4051 21
3-4-4211 22

3-4-4421-1X 20
3-4-4441-1■ 18
3-4-4451-1X 18
3-4-5101■ 15
3-4-5191-1 19

3-4-5301 17
3-4-5321 18
3-4-5341• 15
3-4-5391X 17
3-4-5441-1 22

3-4-5701-1• 18
3-4-5711-1X 18
3-4-5721-1 16
3-4-5731-1X 16
3-4-5751-1■ 16

3-4-5761-1X 16
3-4-5781-1X• 21
3-4-5791-1X 21
3-4-5811-1X 21
3-4-5821-1X 22

3-4-5881-1X 19
3-4-5911• 21
3-4-5921-1X 19
3-4-6211-1 17
3-4-6221-1X 21

3-4-6231-1• 21
3-4-6241-1X• 21
3-4-6251• 21
3-4-6261X• 21
3-4-6411-1• 21

3-4-6531■ 19
3-4-6561-1 18
3-4-6631-1X 18
3-4-6671-1X■ 22
3-4-6701-1 20

3-4-6701• 20
3-4-6751• 19
3-4-6901-1 20
3-4-6901-2 20
3-4-7031-1 19

PART NUMBER INDEX

3-4-7131 19
3-4-7141 18
3-4-7151 19
3-4-7161• 21
3-4-7171 21

3-4-7241-1 17
3-4-7241• 17
3-4-7251-1■ 22
3-4-7261-1X 22
3-4-7311-1 19

3-4-7321-1X 19
3-4-7361-1 21
3-4-7391-1X• 20
3-4-7401 17
3-4-7541-1■ 22

3-4-7541-2■ 22
3-4-7551 20
3-4-7571-1 22
3-4-7721-1 18
3-4-7781• 20

3-4-7991-1• 19
3-4-8001-1X 19
3-4-8031-1 19
3-4-8051-1X 22
3-4-8061X 20

3-4-8071-1• 20
3-4-8071• 20
3-4-8491-1• 17
3-4-8501-1 17
3-4-8511-1 17

3-4-8681-1 17
3-4-8691-1X 17
3-4-8701-1• 19
3-4-8721-1 20
3-4-8731-1 18

3-4-8781-1 22
3-4-9001-1X• 17
3-4-9001X• 17
3-4-9031• 21
3-4-9231-1• 22

3-4-9231-2• 22
3-4-9241-1X• 22
3-4-9241-2X• 22
3-4-9251-2 19
3-4-9271-1 21

3-4-9271-2 21
3-4-9301-1 21
3-4-9531-1• 20
3-4-9551-1 18
3-4-9561-1X 18

3-4-9621 21
3-4-9821-1 16
3-4-9931-1• 19
3-4-9941-1 16
3-4-9981-1• 22

3-4-10231-1■ 19
3-4-10251-1 20
3-4-10261-1 22
3-4-10261-1 22
3-4-10261• 22

3-4-10281-1• 17
3-4-10301-1 21
3-4-10461-1X 20
3-4-10471-1X 22
3-4-10471X• 22

3-4-10541-1• 20
3-4-10551-1 19
3-4-10571-1• 18
3-4-10591-1 17
3-4-10931-1 18

3-4-10941-1 18
3-4-10951-1 18
3-4-11051-1 23
3-4-11061-1X 23
3-4-11071-1 22

3-4-11081-1X 19
3-4-11121-1• 22
3-4-11161-1• 21
3-4-11171-1■ 21
3-4-11171-1■ 21

3-4-11181-1• 21
3-4-11221-1■ 16
3-4-11231-1X• 16
3-4-11281-1X 21
3-4-11421-1• 16

3-4-11441-1• 16
3-4-11471-1 18
3-4-11551-1• 22
3-4-11561-1 21
3-4-11591-1 19

3-4-11621-1X 22
3-4-11701-1X 19
3-4-11711-1 17
3-4-11721-1 16
3-4-11741-1• 19

3-4-11761-1 19
3-4-11771-1• 22
3-4-11811-1 19
3-4-11851-1 18
3-4-11871-2 21

3-4-11891-1X 18
3-4-11901-1• 16
3-4-11911-1X 16
3-4-11921-1X• 22
3-4-11931-1X 16

3-4-12091-1• 22
3-4-12101-1X 22
3-4-12111-1• 22
3-4-12121-1X• 22
3-4-12211-1■ 16

3-4-12461-1 17
3-4-12531-1■ 18
3-4-12541-1X• 18
3-4-12611• 17
3-4-12771-1• 16

3-4-12771-1• 16
3-4-12771-2■ 16
3-4-12781-1X■ 16
3-4-13001-1• 17
3-4-13011-1X 17

3-4-13021• 20
3-4-13031-1X• 16
3-4-13031-2X 16
3-4-13051-1■ 23
3-4-13061-1X 23

3-4-13071-1 23
3-4-13081-1X 23
3-4-13161 16
3-4-13211-1 17
3-4-13341-1• 23

3-4-13351-1X 23
3-4-13391-1X 20
3-4-13511-1 18
3-4-13601-1 16
3-4-13731-1 17

3-4-13761-1 16
3-4-13791-1• 21
3-4-13821-1 21
3-4-13871-1■ 19
3-4-13881-1 17

3-4-13901-1 21
3-4-13911-1 19
3-4-13921-1• 20
3-4-13931-1 22
3-4-14031-1 21

3-4-14371-1 19
3-4-14371-1 19
3-4-14391-1X 19
3-4-14451-1 17
3-4-14461-1 17

3-4-14531-1 16
3-4-14541-1X■ 16
3-4-14551-1 21
3-4-14591-1 18
3-4-14621-1 16

3-4-14671-1■ 16
3-4-14681-1■ 18
3-4-14701-1X• 16
3-4-14711-1X 18
3-4-14721-1X• 19

3-4-14731-1X• 21
3-4-14781-1■ 23
3-4-14781-1■ 23
3-4-14781-1■ 23
3-4-14791-1X 23

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

3-4-14841-1X■ 23
4-4-843-1 57
4-4-1901-1 23
4-4-1921-1 23
4-4-1931-1 23
4-4-1941-1• 24
4-4-1941• 24
4-4-2041-1 23
4-4-2051-1 23
4-4-2091-1 23
4-4-2381-1 24
4-4-2401-1 25
4-4-2431-1• 24
4-4-2431-2• 24
4-4-2451-1 25
4-4-2481-1 25
4-4-2511-1 23
4-4-2531-1• 25
4-4-2931-1 24
4-4-2941• 25
4-4-3501-1 25
4-4-3581-1X 23
4-4-3811-1 23
4-4-3841-1• 23
4-4-3851-1• 24
4-4-3861-1X 24
4-4-3931-2 25
4-4-4071-1X 24
4-4-4071-2X• 24
4-4-4101-1 24
4-4-4111-1X 24
4-4-4171-1• 23
4-4-4191-1 24
4-4-4211-1 23
4-4-4211-2 23
4-4-4361-1 25
4-4-4371-1• 25
4-4-4381-1■ 25
4-4-4421-1 25
4-4-4451-1X 25
4-4-4491-1 24
4-4-4611-1• 24
4-4-4611-2 24
4-4-4611 24
4-4-4771-2 24
4-4-4781-1 23
4-4-4781-2 23
4-4-4791-1• 24
4-4-4791-2• 24
4-4-4801-1X 24
4-4-4801-2X 24
4-4-4811-1 24
4-4-5061-1 24
4-4-5091-1 25
4-4-5111-1• 23
4-4-5161-1■ 25
4-4-5171-1X• 25
4-4-5231-1■ 24
4-4-5241-1X■ 24
4-4-5251-1• 23
4-4-5261-1 25
4-4-5551-1• 24
4-4-5571-1• 23
4-4-5581-1• 25
4-4-5601-1 23
4-4-5611-1X 24
4-4-5621-1• 25
4-4-5691-1X 25
4-4-5701-1X• 25
4-4-5721-1• 23
4-4-5841-1■ 25
4-4-5941-1X 25
4-4-5991-1 23
4-4-6101-1 24
4-4-6141-1• 23
4-4-6211-1• 25
4-4-6331-1 23
4-4-6471-1■ 25
4-4-6641-1• 25
4-4-6711-1 23
4-4-6731-1X• 25
4-4-6781-2■ 24
4-4-6791-2 23
4-4-6841-1• 23
4-4-6851-1X 23
4-4-6951-1• 24
4-4-6961-1X 24
4-4-6971-1• 24
4-4-6981-1X 24
4-4-6991-1• 25
4-4-7001-1X 25
4-4-7011-1• 25
4-4-7111-1X 25
4-4-7211-1M 25
4-4-7241-1• 25
4-4-7251-1X 25
4-4-7341-1 24
4-4-7421-1■ 23
4-4-7431-1■ 24
4-4-7551-1X 25
4-4-7561-1■ 25
4-4-7571-1X 25
4-4-7861-1X 23
4-4-7871-1X 24
5-4-413 57
5-4-453• 57
5-4-781 26
5-4-871• 26
5-4-1051 26
5-4-1221■ 28
5-4-1324 58
5-4-1391 28
5-4-1431• 27
5-4-1521 28
5-4-1631• 28
5-4-1641-1■ 27
5-4-1641• 27
5-4-1661-1 28
5-4-1661 28
5-4-1721-1 26
5-4-1721 26
5-4-1831 28
5-4-1891-1• 30
5-4-1891 30
5-4-1931• 26
5-4-2031X 27
5-4-2081-1• 26
5-4-2081 26
5-4-2141• 31
5-4-2331 31
5-4-2341• 31
5-4-2401 26
5-4-2501• 27
5-4-2521• 26
5-4-2531 27
5-4-2541• 27
5-4-3141• 30
5-4-3241 27
5-4-3601X 26
5-4-3621 26
5-4-3681• 27
5-4-3861■ 26
5-4-3901• 26
5-4-3911• 27
5-4-4161X• 31
5-4-4221• 27
5-4-4381• 28
5-4-4391 27
5-4-4401 29
5-4-4441X• 26
5-4-4461-1• 26
5-4-4461 26
5-4-4471-1• 27
5-4-4541 27
5-4-4551 27
5-4-4571 26
5-4-4701■ 31
5-4-4721• 27
5-4-4741■ 30
5-4-4751X 30
5-4-4761X 26
5-4-4771X 27
5-4-4831-1• 27
5-4-4831• 27
5-4-4841-1X 27

PART NUMBER INDEX

5-4-4841X 27
5-4-4861-1 31
5-4-4861 31
5-4-4901X• 26
5-4-4961-1■ 30

5-4-4961 30
5-4-4971 31
5-4-5031-1• 29
5-4-5031• 29
5-4-5081X 26

5-4-5091 27
5-4-5111-1X 26
5-4-5111X 26
5-4-5121-1X• 27
5-4-5121X 27

5-4-5131X 28
5-4-5161-1X 29
5-4-5161X 29
5-4-5221• 27
5-4-5231X• 27

5-4-5281X 27
5-4-5321X 27
5-4-5361-1• 31
5-4-5421• 28
5-4-5441• 28

5-4-5461 28
5-4-5461 28
5-4-5491-1X• 31
5-4-5501• 29
5-4-5501• 29

5-4-5511X 29
5-4-5571-1 26
5-4-5621-1X 26
5-4-5631■ 30
5-4-5711 26

5-4-5721 27
5-4-5731 29
5-4-5741• 30
5-4-5751 29
5-4-5821• 31

5-4-5831-1• 31
5-4-5851-1 31
5-4-5861X 28
5-4-5881 28
5-4-5961 29

5-4-5971X 29
5-4-5981■ 29
5-4-5991X 29
5-4-6101-1X• 31
5-4-6131■ 28

5-4-6131■ 28
5-4-6141-1• 31
5-4-6151-1X• 31
5-4-6161-1• 31
5-4-6241-1• 29

5-4-6241 29
5-4-6251■ 26
5-4-6261-1 26
5-4-6261■ 26
5-4-6271■ 28

5-4-6281X 28
5-4-6291-1X 29
5-4-6291X 29
5-4-6321-1 28
5-4-6321 28

5-4-6341 27
5-4-6351 27
5-4-6361-1X 27
5-4-6371-1• 30
5-4-6371• 30

5-4-6381-1X 30
5-4-6381X• 30
5-4-6421-1• 28
5-4-6421-1• 28
5-4-6421• 28

5-4-6431-1X 28
5-4-6431X 28
5-4-6441-1X 28
5-4-6481-1 28
5-4-6481• 28

5-4-6521-1 30
5-4-6531-1• 31
5-4-6541-1• 28
5-4-6581-1■ 29
5-4-6591-1X 29

5-4-6871X• 28
5-4-6891X 30
5-4-6941-1 26
5-4-6951X 28
5-4-6961X 28

5-4-6981-1• 26
5-4-7031-1• 26
5-4-7041-1 27
5-4-7061-1 28
5-4-7101-1X• 28

5-4-7111-1• 27
5-4-7121X 28
5-4-7171-1 27
5-4-7181X 29
5-4-7191■ 30

5-4-7201X 30
5-4-7211X• 30
5-4-7221X 29
5-4-7231X 30
5-4-7251X 27

5-4-7261-1■ 27
5-4-7261• 27
5-4-7271-1• 29
5-4-7271-1• 29
5-4-7301-1X 27

5-4-7311-1X 29
5-4-7331-1• 31
5-4-7341-1X 31
5-4-7351-1■ 31
5-4-7361-1X• 31

5-4-7381-1• 30
5-4-7391-1X 30
5-4-7431-1■ 30
5-4-7441-1X 30
5-4-7481-1• 28

5-4-7551-1• 29
5-4-7561-1• 29
5-4-7561-1• 29
5-4-7561• 29
5-4-7561• 29

5-4-7571-1X• 29
5-4-7571X 29
5-4-7581-1• 26
5-4-7601-1 28
5-4-7631-1• 26

5-4-7641-1• 30
5-4-7651-1X• 30
5-4-7691-1X• 28
5-4-7701-1■ 27
5-4-7781-1• 27

5-4-7941-1• 27
5-4-7951-1• 31
5-4-7971-1• 29
5-4-7971• 29
5-4-7981-1■ 29

5-4-7991• 29
5-4-8001• 27
5-4-8021-1• 30
5-4-8021-1• 30
5-4-8031-1X 30

5-4-8041 26
5-4-8061-1X 27
5-4-8131-1X 29
5-4-8211-1X 30
5-4-8261-1• 29

5-4-8261 29
5-4-8301• 29
5-4-8311-1• 30
5-4-8321-1■ 30
5-4-8341-1• 31

5-4-8351-1X 31
5-4-8361-1 27
5-4-8411-1X 29
5-4-8411X 29
5-4-8421X 29

5-4-8431-1X 30
5-4-8441X 27
5-4-8461-1• 30
5-4-8491-1• 27
5-4-8501-1X 27

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

5-4-8561-1▪ 27
5-4-8571-1X 27
5-4-8581-1• 28
5-4-8591-1X 28
5-4-8601-1 29
5-4-8611-1X 29
5-4-8621-1• 30
5-4-8631-1X 30
5-4-8641-1• 30
5-4-8651-1X 30
5-4-8661-1• 27
5-4-8671-1X 27
5-4-8681-1 29
5-4-8691-1X 29
5-4-8711X 29
5-4-8851-1 27
5-4-8901-1X 27
5-4-8911-1 27
5-4-8961-1 28
5-4-8971-1 28
5-4-9101-1X 30
5-4-9111-1X 29
5-4-9121-1X• 29
5-4-9121X• 29
5-4-9131-1X• 29
5-4-9141-1 30
5-4-9141 30
5-4-9191-1M 31
5-4-9221-1▪ 29
5-4-9231-1X 29
5-4-9241-1X 29
5-4-9241X▪ 29
5-4-9261-1X• 30
5-4-9271X• 29
5-4-9291-1• 29
5-4-9311-1X 29
5-4-9351-1 29
5-4-9421-1▪ 29
5-4-9431-1• 29
5-4-9441-1X 29
5-4-9451-1X 29
5-4-9511-1 27
5-4-9541-1X 31
5-4-9571-1 31
5-4-9581-1▪ 31
5-4-9621-1▪ 31
5-4-9631-1X 31
5-4-9741• 26
6-4-1971 36
6-4-1981-1 33
6-4-1981 32
6-4-1991-1• 36
6-4-1991 36
6-4-2001 33
6-4-2061 33
6-4-2081-1▪ 31
6-4-2081• 31
6-4-2141 37
6-4-2181-1• 36
6-4-2181▪ 36
6-4-2191-1• 33
6-4-2191 33
6-4-2211 33
6-4-2251-1▪ 39
6-4-2251 39
6-4-2331• 36
6-4-2361-1▪ 33
6-4-2361 33
6-4-2371 33
6-4-2381 32
6-4-2391 32
6-4-2431 35
6-4-2441 36
6-4-2501• 36
6-4-2511 36
6-4-2601X• 36
6-4-3001 34
6-4-3021 40
6-4-3031-1• 36
6-4-3031 36
6-4-3031 36
6-4-3041-1X 36
6-4-3041X 36
6-4-3081• 38
6-4-3131 33
6-4-3141 41
6-4-3161 39
6-4-3221• 32
6-4-3241 33
6-4-3241 33
6-4-3271▪ 33
6-4-3291 33
6-4-3391• 32
6-4-3461X 36
6-4-3491 36
6-4-3501-1▪ 37
6-4-3671 40
6-4-3791 35
6-4-3831-1 33
6-4-3831 33
6-4-3871 36
6-4-3901 33
6-4-4121• 36
6-4-4131▪ 32
6-4-4141▪ 32
6-4-4151-1• 33
6-4-4151• 33
6-4-4171-1X 36
6-4-4171X 36
6-4-4261 33
6-4-4271 32
6-4-4291X 33
6-4-4301X 32
6-4-4361X 32
6-4-4371 32
6-4-4391X 33
6-4-4411-1X• 36
6-4-4411X 36
6-4-4421-1▪ 39
6-4-4421-1▪ 39
6-4-4421 39
6-4-4481X 32
6-4-4531 37
6-4-4551-1 40
6-4-4551 40
6-4-4561-1 37
6-4-4561 37
6-4-4581-1• 39
6-4-4581 39
6-4-4591-1• 36
6-4-4591 36
6-4-4591 36
6-4-4601 37
6-4-4651-1 40
6-4-4651 40
6-4-4681X 36
6-4-4721-1• 33
6-4-4721• 33
6-4-4731-1X 33
6-4-4731X▪ 33
6-4-4741X 33
6-4-4751-1X 39
6-4-4751X 39
6-4-4771-1 39
6-4-4771 39
6-4-4781 39
6-4-4851-1X• 33
6-4-4851X 33
6-4-4861X 32
6-4-4871 33
6-4-4901▪ 34
6-4-4921 40
6-4-4961• 36
6-4-4971 34
6-4-5031-1▪ 32
6-4-5031• 32
6-4-5041-1X 32
6-4-5041X 32
6-4-5061X 36
6-4-5071X 37
6-4-5101X 34
6-4-5111X 32
6-4-5131-1X 32
6-4-5131X 32
6-4-5141• 33

PART NUMBER INDEX

6-4-5151X 33
6-4-5201 40
6-4-5251X 40
6-4-5271• 37
6-4-5291 33

6-4-5341 37
6-4-5351-1▪ 40
6-4-5351▪ 40
6-4-5451-1• 38
6-4-5451▪ 38

6-4-5461-1X 38
6-4-5461X 38
6-4-5471 35
6-4-5481X 36
6-4-5501-1• 34

6-4-5501 34
6-4-5521-1 34
6-4-5521 34
6-4-5541• 34
6-4-5581-1X• 31

6-4-5581X▪ 31
6-4-5711▪ 37
6-4-5741• 38
6-4-5781• 33
6-4-5791 35

6-4-5801 37
6-4-5811▪ 35
6-4-5831 37
6-4-5841-1• 38
6-4-5841▪ 38

6-4-5851-1 34
6-4-5851 34
6-4-5931-1▪ 38
6-4-5931-1▪ 38
6-4-5931• 38

6-4-5931• 38
6-4-5961-1X▪ 38
6-4-5961X 38
6-4-5991 34
6-4-6001X 34

6-4-6011-1▪ 35
6-4-6011 35
6-4-6021-1X 35
6-4-6021X 35
6-4-6041-1X 37

6-4-6041X 37
6-4-6201• 33
6-4-6211-1▪ 38
6-4-6231-1 38
6-4-6241-1X• 38

6-4-6321-1 32
6-4-6321 32
6-4-6331-1▪ 32
6-4-6331 32
6-4-6371-1 34

6-4-6371-1 34
6-4-6371 34
6-4-6371 34
6-4-6371 34
6-4-6381X 34

6-4-6391-1X 34
6-4-6391X 34
6-4-6401-1▪ 34
6-4-6401 34
6-4-6401 34

6-4-6411X 34
6-4-6421-1X 34
6-4-6421X 34
6-4-6451-1 32
6-4-6451 32

6-4-6481 32
6-4-6571-1• 34
6-4-6571▪ 34
6-4-6601-1 38
6-4-6601-1 38

6-4-6601 38
6-4-6611-1 39
6-4-6611 39
6-4-6631-1▪ 40
6-4-6631• 40

6-4-6671• 37
6-4-6761-1X 39
6-4-6761X 39
6-4-6771X 37
6-4-6821-1 40

6-4-6821▪ 40
6-4-6841-1X 40
6-4-6841X 40
6-4-6861-1• 37
6-4-6871-1X 34

6-4-6871X 34
6-4-6891X 36
6-4-6901-1X 37
6-4-6921-1X 39
6-4-6921X 39

6-4-6931-1X 40
6-4-6931X 40
6-4-6941X 34
6-4-6951-1X 34
6-4-6951X 34

6-4-6961-1X 38
6-4-6961X 38
6-4-6971-1• 37
6-4-6971 37
6-4-6991-1• 38

6-4-7041-1X 39
6-4-7041X 39
6-4-7051-1▪ 39
6-4-7051 39
6-4-7071-1X 40

6-4-7071X 40
6-4-7081-1• 38
6-4-7141-1 33
6-4-7141 33
6-4-7161-1 38

6-4-7161-1 39
6-4-7161▪ 38
6-4-7171X 35
6-4-7181-1X 39
6-4-7181X 38

6-4-7191X 37
6-4-7201• 37
6-4-7211X 37
6-4-7221X 35
6-4-7231X 33

6-4-7241X 37
6-4-7251-1• 37
6-4-7251▪ 37
6-4-7271-1X 37
6-4-7271X• 37

6-4-7291X 33
6-4-7301-1 33
6-4-7301 33
6-4-7311-1 35
6-4-7311-1 35

6-4-7311• 35
6-4-7321-1X 35
6-4-7371-1▪ 37
6-4-7381-1X 37
6-4-7481-1 39

6-4-7491-1• 39
6-4-7511-1• 39
6-4-7511-1• 39
6-4-7511 39
6-4-7531-1X 39

6-4-7531X 39
6-4-7541-1 36
6-4-7541-1 36
6-4-7541 35
6-4-7541 35

6-4-7551-1▪ 35
6-4-7551-1▪ 35
6-4-7551 35
6-4-7551 35
6-4-7561-1X 35

6-4-7561X 35
6-4-7571-1 32
6-4-7581-1X 32
6-4-7621-1 34
6-4-7621-1 34

6-4-7621-1 34
6-4-7631-1X 34
6-4-7641-1X 34
6-4-7651-1X 36
6-4-7651X 35

6-4-7661-1• 40
6-4-7691-1 40
6-4-7691• 40
6-4-7731-1X 38
6-4-7741-1X• 33

6-4-7751-1• 31
6-4-7761-1■ 39
6-4-7761• 39
6-4-7771-1X 39
6-4-7771X 39

6-4-7831-1■ 38
6-4-7831■ 38
6-4-7851-1X 38
6-4-7851X 38
6-4-7881-1X 38

6-4-7881X 38
6-4-7891-1X 38
6-4-7961-1 37
6-4-7961-1 37
6-4-7961• 37

6-4-7961• 37
6-4-7971-1X 37
6-4-7971X 37
6-4-7981-1• 35
6-4-7981 35

6-4-7991-1• 34
6-4-7991-1• 35
6-4-7991 34
6-4-8001-1■ 32
6-4-8001 32

6-4-8081-1■ 32
6-4-8081 32
6-4-8231-1X 34
6-4-8291-1X 37
6-4-8321-1X 39

6-4-8321X• 39
6-4-8331-1X 34
6-4-8331X 34
6-4-8341-1X 38
6-4-8341X 38

6-4-8351-1X 39
6-4-8361-1X 34
6-4-8361X 34
6-4-8411-1 35
6-4-8411 35

6-4-8421-1 35
6-4-8421 35
6-4-8431-1 35
6-4-8431 35
6-4-8441-1 35

6-4-8441 35
6-4-8451-1 37
6-4-8451 37
6-4-8461-1 37
6-4-8461-1 37

6-4-8461 37
6-4-8461 37
6-4-8471• 39
6-4-8511-1X 32
6-4-8511X 32

6-4-8521-1X 32
6-4-8521X 32
6-4-8531-1X 35
6-4-8531X 34
6-4-8541-1X 35

6-4-8541X 35
6-4-8551-1X 37
6-4-8551X 37
6-4-8561-1 36
6-4-8571-1X 34

6-4-8571X 34
6-4-8601-1X■ 34
6-4-8651-1■ 33
6-4-8661-1X 33
6-4-8671-1 35

6-4-8681-1X 35
6-4-8691-1 37
6-4-8701-1X 37
6-4-8711-1■ 37
6-4-8721-1X 37

6-4-8731-1 33
6-4-8741-1X 33
6-4-8751-1• 35
6-4-8761-1X 35
6-4-8771-1■ 37

6-4-8781-1X 37
6-4-8791-1• 37
6-4-8801-1X 37
6-4-8821-1• 40
6-4-8831-1• 38

6-4-8841-1• 39
6-4-8851-1 40
6-4-8851 40
6-4-8981-1X 37
6-4-8981X• 37

6-4-8991-1X 35
6-4-8991X 35
6-4-9001-1X 35
6-4-9001X 35
6-4-9021-1 32

6-4-9031-1X 35
6-4-9031X 35
6-4-9041-1X 35
6-4-9041X 35
6-4-9131-1 39

6-4-9141■ 39
6-4-9151X• 39
6-4-9161-1X 37
6-4-9161X• 37
6-4-9171-1X 35

6-4-9171X 35
6-4-9181-1X 35
6-4-9181X 35
6-4-9191-1X 36
6-4-9191X 35

6-4-9201-1X 39
6-4-9221-1 36
6-4-9221 36
6-4-9231-1 40
6-4-9231 40

6-4-9281-1 35
6-4-9291-1■ 35
6-4-9301-1X 35
6-4-9311-1M• 38
6-4-9321-1XM• 38

6-4-9411-1 34
6-4-9421-1• 35
6-4-9421-1• 35
6-4-9431-1X 35
6-4-9441-1X• 35

6-4-9521-1 37
6-4-9531-1X 38
6-4-9561-1M■ 40
6-4-9571-1XM• 40
6-4-9691■ 41

6-4-9701X 41
6-4-9741-1M■ 40
6-4-9751-1XM• 40
6-4-9781-1■ 38
6-4-9791-1X 38

6-4-9841-1X• 36
6-4-9841X 36
6-4-9911-1■ 38
6-4-9951-1■ 33
6-4-9961-1X 33

6-4-9971-1M 38
6-4-10011-1 38
6-4-10291-1■ 39
6-4-10291■ 39
6-4-10301-1■ 45

6-4-10301■ 35
6-4-10311-1■ 39
6-4-10311■ 39
6.3-4-41-1■ 43
6.3-4-41• 43

6.3-4-51-1■ 41
6.3-4-51■ 41
6.3-4-61-1 44
6.3-4-61 43
6.3-4-71• 41

6.3-4-81• 41
6.3-4-91-1■ 41
6.3-4-91■ 41
6.3-4-101-1• 42
6.3-4-101• 42

PART NUMBER INDEX

6.3-4-111 41
6.3-4-121• 41
6.3-4-131-1▪ 43
6.3-4-131• 43
6.3-4-141-1▪ 41
6.3-4-141• 41
6.3-4-151-1• 43
6.3-4-151▪ 43
6.3-4-161-1 42
6.3-4-161 42
6.3-4-171-1X 41
6.3-4-171X 41
6.3-4-181X 41
6.3-4-191X• 41
6.3-4-211-1X 42
6.3-4-211X 42
6.3-4-221X 41
6.3-4-231X 41
6.3-4-241-1X• 43
6.3-4-241X 43
6.3-4-251-1X• 41
6.3-4-251X▪ 41
6.3-4-271-1 42
6.3-4-271 42
6.3-4-291-1• 42
6.3-4-291-1• 42
6.3-4-291• 42
6.3-4-291• 42
6.3-4-301-1X 42
6.3-4-301X 42
6.3-4-331-1X 42
6.3-4-331X 42
6.3-4-381-1 43
6.3-4-381 43
6.3-4-391-1• 42
6.3-4-391 42
6.3-4-421• 41
6.3-4-431 41
6.3-4-441• 42
6.3-4-521 43
6.3-4-531-1 41
6.3-4-531-1 41
6.3-4-531-1 41
6.3-4-531 41
6.3-4-541-1X 41
6.3-4-541X 41
6.3-4-641-1 43
6.3-4-641-1 42
6.3-4-641 42
6.3-4-651-1 43
6.3-4-651 43
6.3-4-661-1▪ 43
6.3-4-661▪ 43
6.3-4-711-1 43
6.3-4-711 43
6.3-4-721-1X 43
6.3-4-721X 43
6.3-4-731-1X 41
6.3-4-731X 41
6.3-4-751-1• 42
6.3-4-771-1X 43
6.3-4-771X 43
6.3-4-781-1X 43
6.3-4-781X 43
6.3-4-791-1X 43
6.3-4-791X 43
6.3-4-811-1▪ 43
6.3-4-811• 43
6.3-4-821-1 43
6.3-4-831▪ 42
6.3-4-841-1• 42
6.3-4-851X 42
6.3-4-861-1X 42
6.3-4-861X 42
6.3-4-871-1X 43
6.3-4-871X 43
6.3-4-901-1X• 42
6.3-4-1021X 42
6.3-4-1031-1 43
6.3-4-1031-1 43
6.3-4-1031• 43
6.3-4-1041-1X 43
6.3-4-1041X 43
6.3-4-1051-1• 44
6.3-4-1061-1▪ 41
6.3-4-1061-1▪ 41
6.3-4-1061• 41
6.3-4-1071-1X• 41
6.3-4-1071X 41
6.3-4-1091-1• 41
6.3-4-1101-1X• 41
6.3-4-1141-1X• 41
6.3-4-1151-1• 43
6.3-4-1151-1• 43
6.3-4-1151• 43
6.3-4-1151• 43
6.3-4-1161-1X 43
6.3-4-1161X 43
6.3-4-1171• 41
6.3-4-1191-1 44
6.3-4-1251-1 43
6.3-4-1251• 43
6.3-4-1261X 41
6.3-4-1271-1X 43
6.3-4-1281-1X 42
6.3-4-1281X 42
6.3-4-1321-1• 41
6.3-4-1321-1• 42
6.3-4-1321▪ 41
6.3-4-1321▪ 41
6.3-4-1331-1X 41
6.3-4-1331X 41
6.3-4-1341-1X• 41
6.3-4-1391-1X 42
6.3-4-1391X 42
6.3-4-1401-1X 43
6.3-4-1401X 43
6.3-4-1411-1• 42
6.3-4-1411 42
6.3-4-1421-1 42
6.3-4-1421-1 42
6.3-4-1421 42
6.3-4-1421 42
6.3-4-1481-1X 42
6.3-4-1481X 42
6.3-4-1491-1▪ 41
6.3-4-1501-1X• 41
6.3-4-1511-1 41
6.3-4-1521-1X 41
6.3-4-1531-1▪ 42
6.3-4-1541-1X 42
6.3-4-1551-1▪ 42
6.3-4-1561-1X 42
6.3-4-1591-1 41
6.3-4-1601-1• 42
6.3-4-1611-1X 42
6.3-4-1621-1X 42
6.3-4-1621X• 41
6.3-4-1631-1X• 41
6.3-4-1641X• 41
6.3-4-1651-1X 43
6.3-4-1651X• 43
6.3-4-1681-1 44
6.3-4-1681 44
6.3-4-1701-1• 41
6.3-4-1711-1X 41
6.3-4-1861-1▪ 43
6.3-4-1861▪ 43
6.3-4-5221-1X 42
6.3-4-5221X 42
6.5-4-1891-1 45
6.5-4-1891 45
6.5-4-1901 47
6.5-4-1911▪ 45
6.5-4-1921• 44
6.5-4-1941• 47
6.5-4-1971-1 45
6.5-4-1971 45
6.5-4-1971 45
6.5-4-1991-1• 46
6.5-4-1991 46
6.5-4-2001 44
6.5-4-2011 47
6.5-4-2021 45
6.5-4-2051 44

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

6.5-4-2101-1 47
6.5-4-2101-1 47
6.5-4-2101▪ 47
6.5-4-2131 45
6.5-4-2141-1▪ 45

6.5-4-2151▪ 47
6.5-4-2171-1 47
6.5-4-2171 47
6.5-4-2181 47
6.5-4-2261▪ 45

6.5-4-2271X 45
6.5-4-2291-1▪ 45
6.5-4-2291• 45
6.5-4-2341X 44
6.5-4-2351X 44

6.5-4-2361-1X 46
6.5-4-2361X 46
6.5-4-2401-1X• 45
6.5-4-2401X 45
6.5-4-2441▪ 45

6.5-4-2451X 45
6.5-4-2471• 45
6.5-4-2491X 45
6.5-4-2531X 45
6.5-4-2541-1 46

6.5-4-2541 46
6.5-4-2551X 45
6.5-4-2561-1 47
6.5-4-2561 47
6.5-4-2581-1 45

6.5-4-2581 45
6.5-4-2601X• 47
6.5-4-2621-1▪ 48
6.5-4-2621 48
6.5-4-2681 48

6.5-4-2701-1• 46
6.5-4-2701 46
6.5-4-2711-1X 46
6.5-4-2711X 46
6.5-4-2781-1▪ 44

6.5-4-2781• 44
6.5-4-2821 44
6.5-4-2831X 45
6.5-4-2911 44
6.5-4-2921 47

6.5-4-2931X 47
6.5-4-2961 44
6.5-4-3011 45
6.5-4-3021-1▪ 47
6.5-4-3021 47

6.5-4-3081 48
6.5-4-3161▪ 46
6.5-4-3201-1▪ 46
6.5-4-3201-1▪ 46
6.5-4-3201• 46

6.5-4-3201• 46
6.5-4-3221-1X 46
6.5-4-3221X 46
6.5-4-3251-1 46
6.5-4-3251 46

6.5-4-3261-1 44
6.5-4-3261 44
6.5-4-3281-1X 45
6.5-4-3281X 45
6.5-4-3361-1 47

6.5-4-3361 47
6.5-4-3371-1 44
6.5-4-3371-1 44
6.5-4-3371 44
6.5-4-3381-1X 44

6.5-4-3381X 44
6.5-4-3441-1▪ 46
6.5-4-3441-1▪ 46
6.5-4-3441 46
6.5-4-3441 46

6.5-4-3451-1 47
6.5-4-3451• 47
6.5-4-3461-1• 47
6.5-4-3461• 47
6.5-4-3491-1 47

6.5-4-3491▪ 47
6.5-4-3501-1X 47
6.5-4-3501X 47
6.5-4-3541-1X 47
6.5-4-3541X 47

6.5-4-3551-1X 47
6.5-4-3551X 47
6.5-4-3561-1X 47
6.5-4-3561X 47
6.5-4-3571-1X• 44

6.5-4-3571X 44
6.5-4-3581-1X 46
6.5-4-3581X 46
6.5-4-3591-1 46
6.5-4-3611-1• 47

6.5-4-3611▪ 47
6.5-4-3621-1X 47
6.5-4-3621X• 47
6.5-4-3631▪ 46
6.5-4-3641X 46

6.5-4-3651X 46
6.5-4-3681-1▪ 45
6.5-4-3681-1▪ 45
6.5-4-3681• 45
6.5-4-3681• 45

6.5-4-3691-1X• 45
6.5-4-3691X 45
6.5-4-3711-1X 47
6.5-4-3711X 47
6.5-4-3721-1 46

6.5-4-3721-1 46
6.5-4-3721-1 46
6.5-4-3721▪ 46
6.5-4-3731-1X 46

6.5-4-3731X 46
6.5-4-3801-1 47
6.5-4-3821-1 47
6.5-4-3841-1▪ 45
6.5-4-3851-1X 45

6.5-4-3861-1▪ 44
6.5-4-3881-1X 44
6.5-4-3911-1 46
6.5-4-3911-1 46
6.5-4-3911 46

6.5-4-3911 46
6.5-4-3921-1X 46
6.5-4-3921X 46
6.5-4-3931 45
6.5-4-3931 45

6.5-4-3941-1 48
6.5-4-4001-1X 46
6.5-4-4001X• 46
6.5-4-4011-1X 46
6.5-4-4011X 46

6.5-4-4081-1 45
6.5-4-4081-1 45
6.5-4-4091-1X 45
6.5-4-4191-1X• 44
6.5-4-4211-1 45

6.5-4-4221-1X• 45
6.5-4-4231-1• 45
6.5-4-4241-1X 45
6.5-4-4251X 45
6.5-4-4261-1X 47

6.5-4-4271-1X 46
6.5-4-4271X 46
6.5-4-4281-1X 44
6.5-4-4281X 44
6.5-4-4291-1X 47

6.5-4-4291X 47
6.5-4-4311-1 45
6.5-4-4311 45
6.5-4-4321-1 45
6.5-4-4321-1 45

6.5-4-4321 45
6.5-4-4321 45
6.5-4-4351-1X 45
6.5-4-4351X 45
6.5-4-4401-1X 48

6.5-4-4401X 48
6.5-4-4411-1• 46
6.5-4-4421-1X 46
6.5-4-4431-1▪ 46
6.5-4-4441-1X 46

PART NUMBER INDEX

6.5-4-4451-1■ 45
6.5-4-4461-1X..... 45
6.5-4-4471-1•..... 46
6.5-4-4481-1X..... 46
6.5-4-4511-1X..... 46

6.5-4-4521-1•..... 48
6.5-4-4541■..... 47
6.5-4-4551X..... 47
6.5-4-4571-1X..... 45
6.5-4-4571X..... 45

6.5-4-4591-1X..... 45
6.5-4-4601-1X• 45
6.5-4-4601X■ 45
6.5-4-4611-1X..... 46
6.5-4-4611X 46

6.5-4-4621X•..... 45
6.5-4-4631-1 48
6.5-4-4631 48
6.5-4-4651-1•..... 45
6.5-4-4661-1X..... 45

6.5-4-4721-1X..... 46
6.5-4-5091-1•..... 47
6.5-4-5091■..... 47
6.5-4-5101-1•..... 47
6.5-4-5101■..... 47

8-4-791•..... 48
8-4-851 52
8-4-1061 52
8-4-1141• 52
8-4-1141• 52

8-4-1151X 52
8-4-1161X 52
8-4-1321■..... 48
8-4-1341■..... 48
8-4-1351X..... 48

8-4-1381X•..... 48
9-4-301■..... 48
9-4-311X•..... 48
10-4-11..... 11
10-4-12 59

10-4-13 54
10-4-21 11
10-4-22 59
10-4-23 54
10-4-31 11

10-4-32 59
10-4-33•..... 54
10-4-42 59
10-4-43 54
10-4-52 59

10-4-53 54
10-4-62 59
10-4-63 54
10-4-73 54
10-4-82 59

10-4-83 54
10-4-93 54
10-4-101 11
10-4-103 55
10-4-113..... 55

10-4-121SX 61
10-4-123 55
10-4-133 54
10-4-143 55
10-4-153 55

10-4-163 55
10-4-183 55
10-4-193 55
10-4-203 54
10-4-213 55

10-4-223 55
10-4-233■..... 55
10-4-282 59
10-4-293 55
10-4-303 54

10-4-333 54
10-4-371SX 61
10-4-373 54
10-4-383 55
10-4-391SX 61

10-4-431SX 60
10-4-443 54
10-4-451SX 61
10-4-453 54
10-4-461SX 60

10-4-481 11
10-4-491SX 60
10-4-501SX 60
10-4-551SX 60
10-4-561SX 61

10-4-573 54
10-4-601SX 60
10-4-611SX..... 60
10-4-621SX 60
10-4-631SX 60

10-4-641 11
10-4-661SX 61
10-4-693 54
10-4-713 54
10-4-731SX 61

10-4-741SX 60
10-4-821SX 60
10-4-841SX 60
10-4-851SX 60
10-4-871SX 60

10-4-901SX 60
10-4-911SX..... 60
10-4-931SX 60
10-4-951SX 60
10-4-961SX 61

10-4-971SX 61
10-4-991SX• 60
10-4-1001SX 60
10-4-1061SX 60
10-4-1083SX 62

10-4-1181SX• 60
10-4-1183SX..... 62
10-4-1201SX 61
10-4-1241SX• 60
10-4-1281SX• 60

10-4-1473 55
10-4-1673SX 62
55-4-11-1 2
55-4-31-1■ 2
55-4-41-1X..... 2

55-4-71-1■ 2
55-4-81-1X• 2
55-4-91-1■ 2
55-4-101-1X• 2
55-4-121-1■ 2

55-4-131-1X• 2
55-4-201-1■ 2
70-4-11-1 2
70-4-51-1■ 2
70-4-61-1X..... 2

70-4-101-1■ 2
70-4-111-1X 2
70-4-141-1■ 2
70-4-151-1X..... 2
70-4-161-1■ 2

70-4-171-1X• 2
70-4-181-1■ 2
70-4-191-1X• 2
70-4-261-1■ 2
70-4-271-1X• 2

90-4-11-1 3
90-4-21-1 3
90-4-71-1 3
90-4-111-1..... 3
90-4-161-1•..... 3

90-4-171-1X• 3
90-4-181-1•..... 3
90-4-191-1X..... 3
90-4-201-1■ 3
90-4-211-1X•..... 3

90-4-241-1 3
90-4-251-1X..... 3
90-4-281-1•..... 3
90-4-311-1 3
90-4-321-1X..... 3

90-4-331-1•..... 4
90-4-341-1X..... 4
90-4-351-1•..... 4
90-4-361-1X• 4
90-4-371-1 3

90-4-381-1 3
90-4-391-1 3
90-4-461-1▪ 3
90-4-471-1▪ 3
90-4-501-1X 3

90-4-521-1▪ 4
90-4-531-1X 4
90-4-541-1• 3
90-4-551-1X 3
90-4-561-1• 3

90-4-571-1X 3
90-4-581-1• 3
90-4-591-1X 3
90-4-601-1• 4
90-4-611-1X 4

90-4-621-1▪ 3
90-4-631-1X 3
90-4-691-1X 3
90-4-751-1• 3
90-4-761-1X 3

90-4-791-1 3
100-4-891-1▪ 4
100-4-901-1X 4
100-4-931-1 4
100-4-951-1▪ 4

100-4-961-1X• 4
100-4-1011-1▪ 4
100-4-1021-1X 4
100-4-1071-1▪ 4
100-4-1081-1X 4

100-4-1321-1▪ 4
100-4-1331-1X 4
100-4-1361-1▪ 4
100-4-1371-1X 4
100-4-1381-1X 3

140-4-11-1 5
140-4-41-1• 5
140-4-51-1X 5
140-4-61-1▪ 5
140-4-71-1X 5

140-4-81-1▪ 6
140-4-91-1X 6
140-4-111-1 4
140-4-141-1▪ 5
140-4-151-1X• 5

140-4-181-1• 4
140-4-201-1 6
140-4-211-1▪ 5
140-4-211-1▪ 5
140-4-231-1X 5

140-4-241-1X 5
140-4-251-1▪ 4
140-4-261-1X 4
140-4-271-1▪ 5
140-4-291-1X 5

140-4-301-1▪ 5
140-4-301-1▪ 5
140-4-311-1X 5
140-4-321-1▪ 5
140-4-331-1X 5

140-4-361-1• 5
140-4-371-1X 5
140-4-381-1▪ 5
140-4-391-1X 5
140-4-421-1▪ 5

140-4-431-1X 5
140-4-441-1▪ 5
140-4-451-1X 5
140-4-751-1 5
140-4-761-1• 5

140-4-771-1 6
140-4-881-1 5
140-4-891-1 4
140-4-901-1▪ 5
140-4-911-1X• 5

140-4-921-1▪ 5
140-4-931-1X• 5
140-4-1011-1 5
140-4-1021-1• 5
140-4-1091-1▪ 5

140-4-1101-1X• 5
140-4-1111-1▪ 5
140-4-1121-1X 5
140-4-1131-1• 5
140-4-1151-1▪ 5

140-4-1161-1X• 5
140-4-1191-1▪ 5
140-4-1201-1X• 5
140-4-1231-1• 5
140-4-1261-1▪ 5

140-4-1271-1X• 5
140-4-1391-1▪ 5
140-4-1401-1X 5
140-4-1421-1• 5
140-4-1431-1X• 5

170-4-21-1▪ 7
170-4-31-1X 7
170-4-91-1▪ 7
170-4-101-1X• 7
170-4-111-1• 6

170-4-121-1X 6
170-4-131-1▪ 6
170-4-141-1X 6
170-4-151-1▪ 6
170-4-161-1X▪ 6

170-4-171-1▪ 6
170-4-181-1X▪ 6
170-4-191-1• 7
170-4-201-1X 7
170-4-211-1• 6

170-4-221-1X 6
170-4-231-1• 6
170-4-241-1X 6
170-4-251-1• 7
170-4-261-1X 7

170-4-271-1▪ 7
170-4-281-1X 7
170-4-291-1• 8
170-4-301-1X 8
170-4-311-1▪ 7

170-4-321-1X 7
170-4-331-1• 7
170-4-341-1X 7
170-4-351-1▪ 7
170-4-361-1X 7

170-4-371-1▪ 7
170-4-381-1X 7
170-4-411-1▪ 8
170-4-421-1X 8
170-4-451-1 7

170-4-461-1X• 7
170-4-471-1▪ 8
170-4-481-1X 8
170-4-491-1• 8
170-4-501-1X 8

170-4-511-1 8
170-4-521-1X 8
170-4-531-1• 8
170-4-541-1 6
170-4-561-1 8

170-4-571-1▪ 7
170-4-571-1▪ 7
170-4-581-1X• 7
170-4-591-1X 7
170-4-601-1▪ 7

170-4-611-1X 7
170-4-631-1• 6
170-4-641-1 6
170-4-641-1 6
170-4-641-1 6

170-4-651-1X 6
170-4-661-1• 6
170-4-661-1• 6
170-4-671-1X 6
170-4-681-1X• 6

170-4-691-1X 6
170-4-701-1X• 6
170-4-711-1• 7
170-4-711-1• 8
170-4-721-1X 7

170-4-731-1▪ 8
170-4-741-1X 8
170-4-771-1 6
170-4-781-1▪ 7
170-4-791-1X• 7

PART NUMBER INDEX

170-4-801-1▪ 7
170-4-811-1X 7
170-4-821-1 7
170-4-831-1 7
170-4-841-1 6

170-4-841-1 6
170-4-851-1X 6
170-4-861-1X 6
170-4-891-1▪ 7
170-4-901-1X 7

170-4-921-1 6
170-4-951-1• 7
170-4-961-1X 7
170-4-1011-1▪ 7
170-4-1021-1X• 7

170-4-1031-1 7
170-4-1041-1X 7
170-4-1061-1• 7
170-4-1081-1 7
170-4-1091-1• 8

170-4-1141-1• 8
170-4-1161-1 8
170-4-1171-1▪ 7
170-4-1191-1X 7
170-4-1211-1• 7

170-4-1221-1X 7
170-4-1251-1 6
170-4-1261-1X 6
170-4-1271-1 7
170-4-1281-1• 7

170-4-1291-1X 7
170-4-1341-1• 8
170-4-1351-1X 8
170-4-1441-1 7
170-4-1621-1▪ 7

170-4-1631-1X• 7
170-4-1641-1▪ 6
170-4-1651-1X• 6
170-4-1681-1 8
170-4-1711-1 8

170-4-1891-1• 8
170-4-1901-1▪ 7
170-4-1911-1▪ 8
250-4-21-1 9
250-4-31-1▪ 9

250-4-41-1X 9
250-4-51-1▪ 9
250-4-61-1X 9
250-4-71-1• 9
250-4-81-1X 9

250-4-91-1▪ 9
250-4-101-1X 9
250-4-131-1▪ 8
250-4-141-1X 8
250-4-151-1▪ 9

250-4-161-1X 9
250-4-191-1▪ 9
250-4-201-1X 9
250-4-211-1▪ 9
250-4-221-1X 9

250-4-231-1• 9
250-4-241-1X 9
250-4-251-1• 9
250-4-271-1 9
250-4-281-1▪ 9

250-4-281-1▪ 9
250-4-291-1X 9
250-4-301-1X 9
250-4-341-1• 9
250-4-341-1• 9

250-4-351-1X 9
250-4-361-1 9
250-4-371-1X▪ 9
250-4-381-1• 8
250-4-391-1X 8

250-4-411-1▪ 8
250-4-421-1X 8
250-4-471-1• 9
250-4-501-1• 9
250-4-511-1• 9

250-4-521-1X 9
250-4-531-1▪ 9
250-4-541-1X 9
250-4-551-1 9
250-4-561-1 9

250-4-601-1▪ 9
250-4-621-1X 9
250-4-641-1 9
250-4-651-1X 9
250-4-701-1▪ 9

250-4-711-1X 9
250-4-751-1• 9
250-4-761-1X 9
250-4-771-1▪ 9
250-4-781-1X• 9

250-4-791-1▪ 9
250-4-801-1X 9
250-4-811-1 9
250-4-901-1• 9
250-4-911-1 10

250-4-1021-1▪ 9
250-4-1031-1▪ 9
131433K 8
131434K 8
131435K 9

131437K 39
131438K 39
131439K 39
131440K 43
131441K 43

131442K 39
131443K 47
131444K 47
131446K 9
131447K 47

131448K 47
131449K 35
131450K 45
131451K 7
131482K 43

131518K 43
131519K 39
131530K 39
132863K 8
132931K 8

5001036▪ 3
5001046 3
5001480 2
5001694▪ 4
5001766• 7

5001768• 6
5001781• 2
5001782▪ 2
5001789 2
5002012▪ 15

5002013▪ 15
5002015▪ 15
5002687▪ 48
5002688• 48
5002872▪ 29

5002873 29
5002874▪ 4
5002875 4
5002876▪ 36
5002877 36

5003087 4
5003329▪ 2
5003330 2
5003553 39
5003555 43

5003556 46
5003557 5
5003558 8
5003560 9
5003634 51

5003950 15
5003952 15
5003954 15
5004159 30
5004358▪ 30

5004772▪ 52
5004773 52
5004785 20
5004898▪ 31
5004899▪ 31

• Part is discontinued ■ Part is available until supply is exhausted ⅄ Not sold separately

5005217▪ 8
5005579▪ 39
5005580• 39
5005581▪ 43
5005582▪ 43
5005679▪ 44
5005680 48
5005681▪ 10
5006607▪ 4
5006608 4
5006714▪ 8
5006976 23
5006977 2
5007193▪ 36
5007597▪ 41
5007598▪ 4
5007599▪ 5
5007600▪ 5
5008270▪ 30
5008438 39
5008439 39
5008440 43
5008441 43
5008442 47
5008443 47
5008444 8
5008445 9
5008446 35
5008447 45
5008448 7
5008449 39
5008450 39
5008451 8
5008452 39
5008453 39
5008454 43
5008455 43
5008456 47
5008457 47
5008458 8
5008459 9
5008461 8
5008577 7
5008578 6
5009705 6
4C-4-11 49
4C-4-21 49
4C-4-31 49
4C-4-41 49
5C-4-41 49
5C-4-51 49
5C-4-61 49
5C-4-71M 49
5C-4-91 49
5C-4-101 49
5C-4-111 49
6C-4-31 49
6C-4-41 50
6C-4-61 49
6C-4-71 49
6C-4-81 49
6C-4-91 49
6C-4-101 49
6C-4-111 49
6C-4-141 49
6C-4-191 49
6C-4-201 49
6C-4-251 49
6C-4-261 50
7C-4-11 51
7C-4-31 50
7C-4-41M 50
7C-4-61 51
7C-4-71 50
7C-4-81 50
7C-4-91 51
7C-4-101 51
7C-4-111M 51
7C-4-121 50
7C-4-131 50
7C-4-141 50
7C-4-151M 50
7C-4-161 51
7C-4-171 51
7C-4-191 51
7C-4-201 50
7C-4-211 50
7C-4-241 50
7C-4-251 50
7C-4-261 50
7C-4-271 51
7C-4-281M 50
7C-4-291 50
7C-4-311 50
7C-4-321 51
7C-4-351 51
7C-4-401M 51
7C-4-471M 51
8.5C-4-11 52
8.5C-4-21 51
8.5C-4-31 52
8.5C-4-41 51
8.5C-4-51 51
8.5C-4-61 51
8.5C-4-71 51
8.5C-4-111 52
8C-4-51 51
8C-4-101 51
9C-4-41• 52
9C-4-81 52
9C-4-91 52
9C-4-111 52
9C-4-211• 52
10C-4-21▪ 52
10C-4-81 52

Dana Holding Corporation
Spicer Service Parts
PO Box 321
Toledo, Ohio 43697-0321
1-800-SAY-DANA (729-3262)

www.spicerparts.com

Dana Holding Corporation
Spicer Service Parts - Canada
5095 South Service Road
Beamsville, Ontario LOR 1BO

Dana Holding Corporation
Spicer Service Parts - International
(419) 861-6325

J300P-4
9/08
Printed in U.S.A

© Dana Limited 2008.
All rights reserved.