

Reservoirs – Saddle Mounted, Single Compartment



Features:

- Long life internal and external corrosion protection.
- Withstands 500 hour salt spray test.
- Valve ports reinforced for extra strength.
- Conforms to SAEJ10B specifications.
- Certified to 150 PSI working pressure.
- Use of isolator pads recommended in any ABS application.

Specifications:

DQ60200 Isolator Pad Kit

Notes:

- 1) All tanks have 1/4" drain port in bottom.
- 2) All tanks have (2) 3/8" charging ports, one on each end.
- 3) Valve ports on same side – **19842** only.

| SKU# | Product Description | Mounting Centers | Diameter | Volume | Valve Mounting Port(s) | Mounting Flanges |
|-------|--|------------------|----------|--------------|-------------------------|-------------------|
| 19810 | Saddle-Mounted Single Compartment Reservoir | 32" | 8" | 1425 cu. in. | (1) 3/4" | Below Center Line |
| 19820 | Saddle-Mounted Single Compartment Reservoir | 29-1/2" | 12" | 2865 cu. in. | (2) 3/4" | Above Center Line |
| 19821 | Saddle-Mounted Single Compartment Reservoir | 29-1/2" | 12" | 2865 cu. in. | (1) 3/4" | Above Center Line |
| 19840 | Saddle-Mounted Single Compartment Reservoir | 27-1/2" | 9-1/2" | 1490 cu. in. | (2) 3/4" | Above Center Line |
| 19841 | Saddle-Mounted Single Compartment Tank Reservoir | 27-1/2" | 9-1/2" | 1490 cu. in. | (2) 1/2" | Below Center Line |
| 19842 | Saddle-Mounted Single Compartment Tank Reservoir | 27-1/2" | 9-1/2" | 1490 cu. in. | (2) 1/2" * see notes | Below Center Line |
| 19845 | Saddle-Mounted Single Compartment Tank Reservoir | 27-1/2" | 9-1/2" | 1490 cu. in. | (1) 1/2" & (1) 3/4" | Below Center Line |
| 19850 | Saddle-Mounted Single Compartment Reservoir | 32" | 8" | 1425 cu. in. | (2) 1/2" | Above Center Line |

Reservoirs – Saddle Mount, Dual Compartment Tank



Features:

- Long life internal and external corrosion protection.
- Withstands 500 hour salt spray test.
- Valve ports reinforced for extra strength.
- Conforms to SAEJ10B specifications.
- Certified to 150 PSI working pressure.
- Use of isolator pads recommended in any ABS application.

Notes:

- 1) (2) 1/4" drain ports in bottom, one in each compartment.
- 2) (2) 1/2" charging ports, one on each end.
- 3) (1) 3/8" top charging port.
- 4) Each compartment has equal volume (1522).

| SKU# | Product Description | Mounting Centers | Diameter | Volume | Valve Mounting Ports | Mounting Flanges |
|--------|---|------------------|----------|--------------|----------------------|-------------------|
| A97471 | Saddle Mount, Dual Compartment Tank Reservoir | 31-1/2" | 12" | 3044 cu. in. | (3) 1/2" | Above Center Line |