

Rubber Air Brake Hose

- Minimum burst pressure of 900 psi.
- Conforms to SAE J1402 and DOT-106 specifications.
- Maximum operating pressure of 225 psi.
- Operating temperature of -40°F to +200°F.
- Perforated hose cover allows moisture to escape from the reinforcement layer.
- Resistant to gasoline, diesel fuel, oil and commonly used road and cleaning chemicals.
- Air brake hose assembly wall rack available - Sloan number 452000.



Air Brake Hose Assemblies

LENGTH	<u>3/8" Hose I. D.</u>			<u>1/2" Hose I.D.</u>		
	1/4"-18 1 fixed,1 swivel	3/8"-18 1 fixed,1 swivel	3/8"-18 2 swivel	3/8"-18 1 fixed,1 swivel	3/8"-18 2 swivel	1/2"-14 fixed 3/8"-18 swivel
8"	453108	453208	453308	452108	452208	452308
12"	453112	453212	453312	452112	452212	452312
14"	453114	453214	453314	452114	452214	452314
16"	453116	453216	453316	452116	452216	452316
18"	453118	453218	453318	452118	452218	452318
20"	453120	453220	453320	452120	452220	452320
22"	453122	453222	453322	452122	452222	452322
24"	453124	453224	453324	452124	452224	452324
26"	453126	453226	453326	452126	452226	452326
28"	453128	453228	453328	452128	452228	452328
30"	453130	453230	453330	452130	452230	452330
32"	453132	453232	453332	452132	452232	452332
34"	453134	453234	453334	452134	452234	452334
36"	453136	453236	453336	452136	452236	452336
38"	453138	453238	453338	452138	452238	452338
40"	453140	453240	453340	452140	452240	452340
42"	453142	453242	453342	452142	452242	452342
44"	453144	453244	453344	452144	452244	452344
46"	453146	453246	453346	452146	452246	452346
48"	453148	453248	453348	452148	452248	452348
50"	453150	453250	453350	452150	452250	452350
52"	453152	453252	453352	452152	452252	452352
54"	453154	453254	---	452154	---	---
56"	453156	453256	453356	452156	452256	452356
60"	453160	453260	453360	452160	452260	452360
66"	453166	453266	453366	452166	452266	452366
72"	453172	453272	453372	452172	452272	452372
84"	453184	453284	453384	452184	452284	452384

* Additional lengths available upon request

NEED BULK HOSE? See pages 26 & 27!